

WILLIAM R. ALLEN SCHOOL RESTORATION AND REHABILITATION PROJECT ARCHITECTURAL DRAWINGS BY CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC AUGUST 8, 2022


RESTORATION AND REHABILITION WILLIAM R. ALLEN SCHOOL


BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

PROJECT:	PROJECT DATA			LIST OF DRAWINGS			
	RESTORATION AND REHABILITATION OF THE WILLIAM R. ALLEN SCHOOL	C	COVER	PROJECT DATA, GENERAL NOTES LIST OF DRAWINGS			B
ADDRESS:	BURLINGTON, BURLINGTON COUNTY, NEW JERSEY	-		MAP, PARTIAL SITE DIAGRAM	No.	DESCR	IP
BLOCK No.: OWNERSHIP:	223 LOT NO.: 2 CITY OF BURLINGTON	1	AD1	BASEMENT FLOOR DEMOLITION PLAN, DEMOLITION/SALVAGE SCHEDULE			
	S1F FOR BURLINGTON 525 HIGH STERET, BURLINGTON, NEW JERSEY 08016	1	AD2	FIRST FLOOR DEMOLITION PLAN, DEMOLITION/SALVAGE SCHEDULE	<u> </u>	-	
AGENT OF THE OWNER:	WILLIAM HARRIS, DEPARTMENT OF HOUSING AND COMMUNITY DEVELOPMENT	- 1	A1	BASEMENT FLOOR PLAN, FLOOR PLAN KEY			
HISTORIC BUILDING:	THIS BUILDING IS LISTED ON THE NEW JERSEY AND THE NATIONAL	ac l	A2	FIRST FLOOR PLAN. FLOOR PLAN KEY			
USE GROUP:		OR .	A3	ROOF PLAN			
	A3 - ASSEMBLY (REHABILITATION SUBCODE) VB - NON-COMBUSTIBLE/COMBUSTIBLE(UNPROTECTED)		A4	NORTH ELEVATION, EAST ELEVATION OF A VICE OF A	No.	DATE	R
THE FOLLOWING	IS A SUMMARY OF THE WORK TO BE COMPANY		A5	NORTH ELEVATION, EAST ELEVATION, SEALANT JOINT, ELEVATION REPAIR KEY			
WOOD FRAMING, PL	ASTER, AND FINISH CARPENTRY RESTORATION, WINDOW AND DOOR RESTORATION		-	SOUTH ELEVATION, WEST ELEVATION, ELEVATION REPAIR KEY SPLITWOOD TRIM REPAIR DETAIL SECONDS			
EXTERIOR AND INCOME	AS I ER, AND FINISH CARPENTRY RESTORATION, STRUCTURAL REPAIR OF THE FLOOR EINSERTION OF NEW MECHANICAL, ELECTRICAL, AND PLUMBING SYSTEM INTO HISTORIC RING KITCHEN AND OFFICE SPACE AND SURFACE PREPARATION AND PAINTING AT THE ERIOR FINISHES. URNISHED FOR INFORMATIONAL PURPOSES ONLY.		46	SPLITWOOD TRIM REPAIR DETAIL. EPOXY REPAIR DETAIL. WOOD DUTCHMAN DETAIL. PAINT SURFACE PREPARE DETAIL, REPOINT OF ERODED JOINT @ BRICK MASONRY, REPOINTING OF MODERATELY PRODED JOINT @ BRICK MASONRY, REPOINTING OF BRICK MASONRY, BRICK REPAIR INJECTION. EPOXY REPAIR DETAIL, BRICK MASONRY CROONEY, BRICK REPAIR NOTES, FINISH CARPENTRY REPAIR NOTES, REPAIR NOTES, FINISH CARPENTRY REPAIR NOTES, RE			
	GENERAL NOTE	A	17	PLASTER ON LATH DETAIL, PLASTER CRACK REPAIR, PLASTER ON BRICK DETAIL, HANDRAIL DETAIL, INTERIOR REPAIR NOTES			
THESE DRAWINGS A	GENERAL NOTES S INSTRUMENTS OF SERVICE, ARE AND SHALL REMAIN THE SOLE PROPERTY OF THE UNDERSTREADED ONLY FOR USE BY THIS OWNER AND ONLY ON THE OPEN OF THE	A		FIRST FLOOR REFLECTED CEILING PLAN, LIGHTING FIXTURE SCHEDULE, PLAN REPAIR KEY			
THE APPROVAL OF T	THE ARCHITECT IS PROHIBITED.	A	A	OPERABLE ACOUSTIC PARTITION SOFFIT DETAIL, OPERABLE ACOUSTIC PARTITION JAMB DETAIL, NEW STEEL LINTEL, EXTERIOR CONCRETE WALK DETAIL, IANDRAIL DETAIL			
BE PERFORMED AND PROCEEDING WITH SUBCONTRACTOR LL	NOTIFY THE ARCHITECT IMMEDIATELY OF ANY UNSATISFACTORY CONDITIONS. THE WORK WITHOUT NOTIFYING THE ARCHITECT SHARMS ACTORY CONDITIONS.	o A	10	ROOM 100 HALL - INTERIOR ELEVATIONS, INTERIOR REPAIR KEY			
VIII CONTINUE	AND SUBCONTRACTORS SHALL FIELD VERIES: ALL DUCTOR OF	A		ROOM 101 COMMUNITY 1 - INTERIOR ELEVATIONS, INTERIOR REPAIR KEY			
ALL CONTRACTORS A OWNER CERTIFICATE	ND SUBCONTRACTORS, PRIOR TO COMMENCING THE WORK	A		ROOM 102 COMMUNITY 2 - INTERIOR ELEVATIONS, INTERIOR REPAIR KEY			
PAYMENT BY THE OW	NER. ABOR SHALL BE GUARANTEED FOR A PERIOD OF ONE YEARS FROM THE DATE OF FINAL.	Al		ROOM 103 COMMUNITY 3 - INTERIOR ELEVATIONS, INTERIOR REPAIR KEY			
MAY NOT BE CHARGE	NBE. NDS SURCONTRACTORS, PRIOR TO COMMENCING THE WORK, SHALL OBTAIN ALL ROM THE GOVERNMENTAL AGENCIES HAVING JURISDICTION OVER THE WORK. ATE UNIFORM CONSTRUCTION ACT, THE OWNER IS A TAX EXEMPT ORGANIZATION, AND DANY LOCAL, STATE, OR FEDERAL TAXES.	A1	1.40	OOM 104 COMMUNITY 4 - INTERIOR ELEVATIONS, INTERIOR REPAIR KEY			
THE PUBLIC AND THE	NO SUBJECTORS SHALL PROVIDE ALL PROTECTION MEASURES FOR THE SAFETY OF	A1	5 RO	OOM 105 COMMUNITY 5 - INTERIOR ELEVATIONS, ROOM 109 VESTIBULE - INTERIOR LEVATIONS, INTERIOR REPAIR KEY			
EACH CONTRACTOR AT	ND SUBCONTRACTOR SHALL BE RESPONSIBLE FOR REMOVAL, CARTING AND DISPOSAL OF	A1	-	ECEPTION, OFFICE AND KITCHEN - INTERIOR ELEVATIONS, INTERIOR REPAIR KEY			
GOVERNMENTAL ACE	HAVE BEEN PROPERLY DISPOSED OF AND ALL DESTRUCTIONS AS CERTIFIED STATEMENT	A1		I ENTERANCE - INTERIOR ELEVATIONS, INTERIOR REPAIR KEY			
TO THE FOLLOWING	NOLES HAVING JURISDICTION OVER THE WORK HAVE REEN FULLY COMPLIED WITH REFORMED TO ALL STATE AND LOCAL REQUIREMENTS, INCLUDING BUT NOT LIMITED CITION CODE (UCC), THE STATE OF NEW JERSEY, AS UPDATED AND INCLUDING BILITATION SUBCODE	A18	1	2 VESTIBULE - INTERIOR ELEVATIONS, INTERIOR REPAIR KEY		-	
NIAC 5:23-7 BARRIER F	LDING CODE/2018, NJ ed.	A19		ITCHEN PLAN, KITCHEN ELEVATION, PLUMBING FIXTURE AND APPLIANCE SCHEDULE			0
INTERNATIONAL ME	D FEURIBING CODE/2018 (NJAC 5:23-3.15)	A20		ITCHEN PLAN (BID ALTERNATE), PLUMBING FIXTURE AND APPLIANCE SCHEDULE	a cost dim	W. Sal	WE
- Just CE	E GAS CODE/2018, (NIAC 5:23-3,22)	A21	AN	NO SHOE DETAIL DESTROOM PLAN, ACCESSIBLE MEN'S RESTROOM FLENGER	1	B Û	Do
SPECT OF THE WORL IN	LY WITH THE SECRETARY OF THE INTERIOR'S <u>STANDARDS FOR THE TREATMENT OF</u> THE SOLE INTERPRETER OF THESE STANDARDS AS THEY RELATE TO THIS PROJECT CT. OBTAIN THE ONLY OF THE ARCHITECT PRIOR TO PROCEEDING WITH ANY FIRST COMMENTARY OF THE TREATMENT OF THE STANDARDS.	A22	AC	CESSIBLE WOMEN'S PROPERTY CLEARANCE DETAIL, RESTROOM SCHEDULE	7	NO AVE PAROLE	1
ORTION OF THE WORL	SHALL FURNISH ALL LABOR, TOOLS, EQUIPMENT MATERIAL AND ARDS.			CESSIBLE WOMEN'S RESTROOM PLAN, ACCESSIBLE WOMEN'S RESTROOM ELEVATION, RRIER-FREE RESTROOM CLEAANCE DETAIL, RESTROOM SCHEDULE	DELAN	WOODLAND A	KEIM .
LL SUBCONTRACTORS' I HE CONTRACTOR IS EX	FEES SHALL INCLUDE SUPERVISION OF THE SUBCONTRACTOR'S EMPLOYEES CLUSIVELY RESPONSIBLE FOR LOSS OR EXPENSE RESULTING FROM INJURY ON THE	A23	DE	OOR SCHEDULE, DOOR HARDWARE SCHEDULE, HEAD/SIDE JAMB DETAIL, DOOR BRICK TAIL	du E	MOORLAND	20
HE CONTRACTOR ASSESS	TO A BOSS ON EXPENSE RESULTING FROM INJURY ON THE	A24	-	OR TYPES	Noice Sales	PRINCETON CIR.	75
ONTRACT	NIES ALL RISKS IN THE PERFORMANCE OF THE WORK PONSIBLE FOR SUPERVISION, SAFETY, ADMINISTRATION AND ALL PHASES OF ITS PONSIBLE FOR SCHEDULING, COORDINATION, MANAGEMENT AND ADMINISTRATION	A25	DET	NDOW REPAIR SCHEDULE, WINDOW SILL REPAIR DETAIL, EXTERIOR STORM WINDOW TAILS	STERIO WAS AND	Soft and Athle	SPEC
CUPATIONAL SAFETY	AND HEALTH STANDARDS AND SOMETHE UNITED STATES DEPARTMENT OF LABOR	A26	WIN	NDOW SCHEDULE	0150	CHARD ST.	10
RDINANCES; AND ANY S.	AFETY RULES OR PROCEDURES ESTABLISHED BY THE	A27	WIN	JDOW TYPES	S. C. C.	O ORCEASE	EIG
JURY.	PROTECT ALL PERSONS NEAR OR ON THE PREMISES PROMISES	A28	FINIS	SH SCHEDULE	Es	wn	4
R THE DURATION OF THE	HE PROJECT.	A29	SIGN, REOL	IAGE SCHEDULE, ROOM SIGN TYPE, TYPICAL MOUNTING HEIGHTS, ROOM SIGN PLACEMENT	So State	427)	1.22
CHITECT AS ADDITION	THE OWNER AS ADDITIONALLY INSURED. THE CONTROL			SOUTH SIGN PLACEMENT	D 80 2	127h	57
E ARCHITECT'S OBSERV. EMED AS SUPERVISION O	ALLY INSURED FOR THIS PROJECT. ATION FOR COMPLIANCE WITH THE DRAWINGS AND SPECIFICATIONS SHALL NOT BE OR CONTROL OF CONSTRUCTION MEANS OR METHODS EMPLOYED BY THE IIS SUBCONTRACTORS.						
ON ON ANY OF I	IIS SUBCONTRACTORS.			MA(7	\ LO	C
				NORT	7 (1	N.	
	<u></u>			NOK	11	NOTE:	ПП









RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

Cranford, N.J. 07016


973 746-4911


LOCATION MAP





COVER







CONNOLLY & HICKEY

HISTORICAL ARCHITECTS, LLC P.O. Box 1726

Cranford, N.J. 07016 973 746-4911




THOMAS B. CONNOLLY, AI NJ 21AI01699200 PA RA403776

MARGARET M. HICKEY, AL-NJ 21A1018244500 PROJECT No.: 2016C

DATE: 08 AUGUST 2022

DRAWN BY: MS, TJ, CB, PK







CONNOLLY & HICKEY

HISTORICAL ARCHITECTS, LLC

P.O. Box 1726 Cranford, N.J. 07016 973 746-4911




THOMAS B. CONNOLLY, AL. NJ 21AI01699200 PA RA403776


MARGARET M. HICKEY, AI NJ 21AI018244500 PROJECT No.: 2016C

DATE: 98 AUGUST 2022 REVISIONS:

DRAWN BY: MS, TJ, CB, PK









HISTORICAL ARCHITECTS, LLC P.O. Box 1726

Cranford, N.J. 07016 973 746-4911

THOMAS B. CONNOLLY, AI NJ 21A101699200 PA RA403776


MARGARET M. HICKEY, AL NJ 21AI018244500

PROJECT No.: 2016C


DATE: 08 AUGUST 2022 REVISIONS:

DRAWN BY: MS, TJ, CB, PK

BASEMENT FLOOR PLAN 1 BA 3/16"




© COPYRIGHT 2022 CONNOLLY & HICKEY HISTORICAL ARCHITECTS. LLC. UNAUTHORIZED REPRODUCTION OF THESE DRAWINGS IS PROHIBITED WITHOUT WRITTEN CONSENT OF THE ARCHITECT





CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC

P.O. Box 1726 Cranford, N.J. 07016




THOMAS B. CONNOLLY, ALA NJ 21A101699200 PA RA403776 MARGARET M. HICKEY, ALA NJ 21A1018244500


PROJECT No.: 2016C

DATE: 08 AUGUST 2022

REVISIONS:

DRAWN BY: MS, TJ, CB, PK





MASONRY REPAIR NOTES

- GENERAL MASONRY NOTES

 1. CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFYING ALL EXISTING CONDITIONS.

 2. REMOVE ALL ABANDONED NAILS, ANCHORS, STRAPS WIRES, CLIPS, FASTENERS OR OTHER ATTACHMENTS FROM ALL MASONRY AND MORTAR JOINTS. FILL HOLES IN MASONRY WITH APPROVED COMPOSITE FATCHING MORTAR AND HOLES IN MORTAR JOINTS WITH APPROVED.
- MORTAR.

 8. RAKE MORTAR JOINTS WHERE POINTING IS NOTED ON THE DRAWINGS TO A DEPTH OF I' OR TO SOUND MATERIAL, WHICH MAY BE AS AUCH AS 2 NOTES IN SOME LOCATIONS. ADDITIONAL DEPTH WILL NOT BE CONSIDERED A CHANGE IN CONTRACT.

 4. REMOY E EXISTING AND INSTALL NEW SEALANT BETWEEN WOOD FRAME AND BRICK STONE AT ALL MASONNY OPENINGS.

 5. PROVIDE DRICK SAMPLES FOR APPROVAL PRIOR TO ORDERING BRICK.

 6. PROVIDED HOCK-UPS FOR MASONNY REPAIRS (COMPOSITE PATCHES, DUTCHMAN, AND REPONTING ETC.) AS FOLLOWS.

 6. COMPOSITE PATCH AS THE STORE NOTES.

 6. COMPOSITE PATCH AS THE PATCHES OF THE PATCHES, DUTCHMAN, AND REPONTING ETC.) AS FOLLOWS.

 7. REPONTING FOR ASSOCIATE INCIDENCE.

 8. REPONTING FOR SOURE PEET ADJACENT TO A CEANED AREA OF BRICK-MORTAR.

 8. ALLOW FOR AT LEAST (3) MOCK-LUTS PER TYPE OF REPAIR TO ACHIEVE FINAL APPROVAL BY NCA HISTORIC ARCHITECT.

- NCA HISTORIC ARCHITECT.

 APPROVED MOCK-UP MAY DECOME PART OF FINISH WORK. IF CHOSEN NOT TO, MOCK-UP MUST REMAIN IN PLACE UNTIL ALL REPAIR WORK IS COMPLETE.

 SPECIFIC STORE MASONYR NOTES.

 I. FIELDSTONE STONE WORK LIMITED TO REPOINTING WITH REPLICATION MORTAR.

 2. BROWNSTONE WORK INCLIDES PAINT REMOVAL (SEE NOTES) AND REPOINTING WITH REPLICATION MORTAR

 SPECIFIC BRICK MASONRY REPAIR NOTES.

 I REMOVE ALL SEVERELY BROKEN, ERODED, MISSING, OR CRACKED BRICK AS NOTED. INSTALL NEW BRICK UNIT AS INDICATED TO MATCH EXISTING UNIT, WHERE APPLICABLE.

 2. CLEAN ALL MASONRY OF ALL GENERAL SOILING AS PER TECHNICAL SPECIFICATIONS. NOTIFY ARE ASSOCIATED AS A STANDARD OF THE MASON OF THE STANDARD OF THE STANDAR

- N.C. A INSTORIC ARCHITECT TO ASSESS CONDITIONS

 REPLACE PATCHED OR SPALLED BRICK WITH CONDITIONS GREATER THAN OR EQUAL TO

 ONE-QUARTER OF ITS SURFACE AREA USING APPROVED BRICK THAT MATCHES THE EXISTING IN
 PROPILE, COLOR AND TEXTURE.
- FAOTHE, COLOR AND TEATURE.
 AT AREAS OF STEP CRACKS, CRACKS IN BRICK, INJECT SPECIFIED COMPOSITE GROUT MORTAR
 INTO SMALL CRACKS (LESS THAN 3/16 INCII), COAT SURFACE WITH SPECIFIED BREATHABLE
 MASONRY COATNO AS REQUIRED TO MATCH COLOR
 AT AREAS OF STEP CRACKS IN BRICK, INJECT SPECIFIED COMPOSITE GROUT MORTAR INTO SMALL CRACKS (LESS TIAN A NCID. COAT SURFACE WITH SPECIFIED BREATHABLE MASONRY COTING A REQUIRED TO MATCH COLOR - SEE TANK (AS A NCID. COL

EXISTING MORTAR -

5 (d) A6 N.

- PAINT REMOVAL FROM BRICK WORK:

 1. APPLY PAINT REMOVERS ACCORDING TO PAINT, REMOVERS MANUFACTURERS WRITTEN INSTRUCTIONS. DO NOT ALLOW PAINT REMOVERS TO REMAIN ON SURFACE FOR PERIODS LONGER THAN THOSE INDICATED OR RECOMMENDED IN WRITING BY MANUFACTURER.

 REMOVE LODGE AND PEELING PAINT USING LOW-TO-MEDIUM-PRESSURE WATER SPRAY (AS DETERMINED BY MOCK-17FS, SCRAPERS, STIFF BRUSHES, OR A COMBINATION OF THESE LET SURFACE BRY THOROUGHLY.

- SUPFACE DRY THOROCORDY.

 APPLY THIS COAT OF PAINT REMOVER TO PAINTED SURFACE WITH NATURAL-PIBER CLEANING BRUSH, DEEP-NAP ROLLER, OR LARGE PAINT BRUSH, APPLY IN ONE OR TWO COATS ACCORDING TO MAINFACTURERS WRITTEN INSTRUCTIONS.

 ALLOW PAINT REMOVER TO REMAIN ON SURFACE FOR FERIOD RECOMMENDED IN WRITTNO BY MAINFACTURER OR AS DETERMINED BY PRECONSTRUCTION TESTING.
 RINSE WITH COLD WATER APPLIED BY LOW-TO-MEDIUM-PIESSURE SPRAY (AS DETERMINED BY DEAD OF MAINFACTURE OR AS DETERMINED BY AND ASSOCIATED FOR MAINFACTURE OR AS DETERMINED BY AND ASSOCIATED FOR MAINFACTURE OR AS DETERMINED BY AND ASSOCIATED FOR MAINFACTURE OR AS DETERMINED BY ADMINISTRATION OF MAINFACTURE OF THE PAINFACTURE PROVIDED BUCK MASONSY.
 FAINT REMOVAL SHALL BE TO THE FEATURE OF THE APPLICATION OF NEW PAINT TO MATCH EXISTING (THIS IS SPECIFIC TO BRICK SEE PAINT REMOVAL FOR BROWNSTONE).

MASONRY TO BE REPOINTED - NOTE THAT ACTUAL FINISH MAY VARY FROM THIS DRAWING

IEW REPOINTING MORTAR

- TOOL TO MATCH ORIGINAL AND ACCORDING TO APPROVED MOCK-UP

NOTES.

1. PROVIDE JOINT MOCK-UPS.

2. PROFILES OR CONDITIONS SHOWN MAY NOT REFLECT ACTUAL EXISTING CONDITIONS - NEW POINTING TO MATCH EXISTING TOOLING AT OLDER/ORIGINAL.

FINISH CARPENTRY REPAIR NOTES

- THE CONTRACTOR IS RESPONSIBLE FOR PROTECTING ADJACENCIES (SUCH AS PEOPLE, LAWNS, WATER SOURCES, ETC.) DURING THE EXECUTION OF FINISH CARPENTRY REPAIRS AND SURFACE PREPARATION AND PARTING.
- SNO JOKE AND THE STATE OF THE STATE OF THE STATE OF THE ARCHITECT SHALL HAVE ACCESS TO THE EXTERIOR OF THE BUILDING TO UNDESTAKE AND REVIEW THE WORK PROVIDING A SAFE WORKING ENVIRONMENT ACCORDING TO OSHA REQUIREMENTS AND OTHER REQUIREMENTS AS SET FORTH IN THE TECHNICAL SPECIFICATIONS

- J. FILL ALL HOLES IN TEMS, SOFETS AND OTHER FINISH CARRENTLY COMPONENTS INCLUDING MINOR GAPS IN WOOD COMPONENTS REDXY OR WOOD FILLER REFER TO TECHNICAL SPECIFICATION. THESE TYPES OF REPAIRS ARE PART OF THE BASE CONTRACT AS PART OF THE SUBFACE PREPARATION REPAIRS.

 PROVIDE MOCK-UPS OF FINISH CARPENTRY REPAIRS (DUTCHMAN AND EPOXY CONSOLIDATION) FOR REVIEW AND APPROVAL PROM THE ARCHITECT.

 ALLOW FOR AT LEAST (3) MOCK-UPS IN ORDER TO OTHAN APPROVALS.

 APPROVED MOCK-UPS AND IN PART OF THE PINISH WORK. IF CHOSEN NOT TO, THE APPROVED HOCK-UPS AND THE PART OF THE PINISH WORK. IF CHOSEN NOT TO, THE APPROVED HOCK-UPS AND THE PART OF THE PINISH WORK. IF CHOSEN NOT TO, THE PART OF THE PINISH WORK. IF CHOSEN NOT TO, THE PART OF THE PINISH WORK IS COMPLETE.

 2. UNDERTAGE ALL STRING NOT PART OF THE PINISH WORD SHALL BE BACK PRIMED PRIOR TO INSTALLATION, REFER TO THE TECHNICAL SPECIFICATION FOR ADDITIONAL INFORMATION ON PINISH CARPENTRY RESTORATION.

 SURPRICE TERPARE ALL LEWS AND EXISTING WOOD SURFACES TO RECEIVE PRIMER AND (2)

- INFORMATION ON FINISH CAMPENTRY RESTORATION.
 SUPPLEMENTARY BEAR BLALEW AND EXISTING WOOD SURFACES TO RECEIVE PRIMER AND (2)
 SUPPLEMENTARY BLALEW AND EXISTING WOOD SURFACES TO RECEIVE PRIMER AND (2)
 SUPPLEMENTARY BEAR BLANDERS OF SUPPLEMENTARY BEAR BEAR BLAND TO A FEATHERED EXPORTING FOR THE PROPERTY OF THE PROPERTY O
- HOWEVER, DEEP RECESSES, ROUGH-EDGED RIDGES AND GOUGES ARE NOT ACCEPTABLE REQUIRING CARE AND CRAFTSMANSHIP IN EXECUTION OF SURFACE PREPARATION TECHNIQUES.

 PROVIDE A MOCK-UP OF SURFACE PREPARATION TECHNIQUES FOR THE ARCHITECTS REVIEW. THE APPROVED MOCK-UP SHALL REMAIN UNTIL ALL SURFACE PREPARATION HAS BEEN COMPLETED SERVING AS A MODEL FOR THE REMAINDER OF THE WORK. AT THE COMPLETED OF ALL SURFACE PREPARATION, THE MOCK-UP MAY BE MADE PART OF THE FINISHED WORK PRODUCT THE ARCHITECT SHALL REVIEW SURFACE PREPARATION, THE MOCK-UP MAY BE MADE PART OF THE FINISHED COAT FINISH FAINT ALL EXTERNOR PRINCH CAPENTRY COMPONENTS INCLUDING BUT NOT LIMITED TO WINDOWS, FRAMES. TRIM, AND SIDING AS SHOWN ON DRAWNING.
- INCLIDING BUT NOT LIMITED TO WINDOWS, FRAMES, IREA, AND SERVICE OF THE APPROVED MOCK-LIP FRAMINGS
 PROVIDE A PAINT MOCK-LIP FOR THE ARCHITECT'S REVIEW. THE APPROVED MOCK-LIP FRAMING HAS BEEN COMPLETED SERVING AS A MODEL FOR THE REMAINDER OF THE WORK. AT THE COMPLETION OF PAINTING, THE MOCK-UP MAY BE MADE PART OF THE FINISHED WORK PRODUCT.

REPAIR ALLOWANCES

WOOD REPAIR ALLOWANCES PER ELEVATION:

1. ALLOW FOR 5 LF (1"X12"X12" UNIT MEASURE) OF DITICHMAN REPAIR/REPLACEMENT OF DETERIORATED WOOD TRIM THIAN SHOWN ON DRAWINGS.

6 A6

SCRAPE AWAY ALL LOOSE AND DETERIORATED WOOD FROM AREA

(3) REBUILD VOID WITH MIXTURE OF HARDENER, PASTE AND RESIN. PASTE TO MATCH ORIGINAL PROFILES AND DIMENSION OF THE MEMBER

TO BE REPAIRED -

- IASONRY REPAIR ALLOWANCES PER ELEVATION:
 ALLOW FOR 15 SF OF ADDITIONAL REPONTING (BRICK AND STONE) PER ELEVATION THAN
 INDICATED. MAKE ASSESSMENT AFTER ALL SURFACE PREPARATION WORK HAS BEEN
 COMPLETED.
 ALLOW FOR 12 SF OF BRICK REPLACEMENT THAN INDICATED. AFTER ALL SURFACE PREPARE
 WORK HAS BEEN COMPLETED.

TYPICAL DAMAGED — WOODEN STRUCTURAL MEMBER OR ORNAMENT (N.T.S.)

- 1. DRILL HOLES 4 8 INCHES O.C.
- INSTALL TEMPORARY FORM AS REQUIRED MIX RESIN & HARDENER* TOGETHER IN
- SQUEEZE BOTTLE LET SET FOR 5 MINUTES (INDUCTION TIME) 5. SQUEEZE LIQUID INTO PRE-DRILLED HOLES
- 6. ALLOW 24 HOURS CURING TIME 7. REMOVE FORM

(A) MINOR DAMAGE (SPONGY)

- I. REMOVE ALL DAMAGED DETERIORATED WOOD PRIME WILIQUID RESIN & HARDENER AS
- ABOVE* (3-5)
 INSTALL TEMPORARY FORMS AS REQUIRED
 MIX RESIN & HARDENER** TOGETHER INTO
- WORK PASTE INTO VOIDS SMOOTH SURFACE W/SPACKLE KNIFE

(B) MAJOR DAMAGE (DECOMPOSED)

GENERAL NOTES

- I. INSTALLER AND HANDLERS SHALL WEAR PROTECTIVE MASKS, GLOVES AND CLOTHING AS PER MANUFACTURERS LATEST PRECAUTIONS 2 "LIQUIDWOOD' AND "WOODEPOX" ARE PROPRIETARY PRODUCTS AS
- MANUFACTURED BY ABATRON, INC. GILBERT, ILLINOIS. CONSULT
- MANUFACTORED BY ADATRON, INC. OILBERT, ILLINOIS. CONSULT MANUFACTURERS LATEST SPECIFICATIONS FOR USE. TOTAL CURING TIME VARIES ACCORDING TO TEMPERATURES. MATERIALS MAY BE NAILED, DRILLED, SAWN, PLANED AND PAINTED UPON CONSULTED AND PAINTED UPON CONSULTED.

• EPOXY REPAIR DETAIL

FOR ORNAMENTAL CARPENTRY REPAIR, MATCH EXISTING PROFILES EXACTLY



MASONRY TO BE REPOINTED - NOTE THAT ACTUAL FINISH MAY VARY


NOTES
1. PROFILES OR CONDITIONS SHOWN MAY NOT REFLECT
ACTUAL EXISTING CONDITIONS - NEW POINTING TO
MATCH EXISTING TOOLING AT OLDER/ORIGINAL
POINTING

SURFACE PROFILE. SPECIES AND TEXTURE

SURFACE USING EPOXY

NOTE: PROFILES OR CONDITIONS SHOWN MAY NOT ACTUALLY REFLECT EXISTING CONDITIONS

FROM THIS DRAWING



BRICK MASONRY COMPOSITE PATCH DETAIL



ONNOLLY & HICKE

ARCHITECTS, LLC

Cranford, N.J. 07016

P.O. Box 1726

973 746-4911

A RA403776

MARGARET M. HICKEY, AI NJ 21AJ018244500

DATE: 08 AUGUST 2022

DRAWN BY: MS, TJ, CB, PK

BRICK UNIT, TYPICAL RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON COUNTY, NEW JER

BRICK MASONRY BACK-UP


EPOXY RESIN THRU BRICK AND ONTO SOUND MASONRY BACKUP. PATCH WITH COMPOSITE MATERIA AND APPLY BREATHABLE MASONRY COATING TO MATCH ADJACENT FINISHED SURFACES, TYPICAL.

ERODED JOINT @ BRICK MASONRY

SET 1/4" O THREADED RODS IN (TYPICALLY @ 8" - 16" o.c.)

REPOINTING OF SEVERELY ERODED JOINT @ BRICK MASONRY

8 BRICK REPAIR INJECTION



NOTES:

SURFACE PREPARE ALL NEW AND EXISTING WOOD SURFACES TO RECEIVE PRIMER AND (2) COASTS FINISH PAINT AS INDICATED ON THE DRAWINGS.

REMOVE ALL LOOSE OR FLAKING PAINT WITH SCRAPERS WITHOUT GAUGING THE WOOD.

SAND TO A FEATHERED EDGE AT HIGH POINTS AND WHERE THERE IS A BUILD-LUP OF PAINT PROVIDING A SMOOTH PAINTABLE SURFACE.

4. IT IS NOT THE INTENTION OF THIS PROJECT TO REMOVE ALL LAYERS OF EXISTING PAINT DUE TO THE HISTORIC NATURE OF THE EXISTING MATERIAL FABRIC.

A6

NOTES:

1 TEST UNIT ATTACHMENT WITH
RUBBER MALLET AFTER EPOXY
RESIN IS FULLY CURED AND BEF
INSTALLATION OF COMPOSITE

ATCH MORTAR MAY NOT REFLECT EXISTING CONDITIONS

PAINT SURFACE PREPARE DETAIL

PROVIDE WOOD FILLER AT SURFACE OF CRACK, TYPICAL

REPOINTING OF ERODED JOINT

@ BRICK MASONRY

AT FRACTURED SURFACES USING MOISTURE



DETERIORATED MEMBER TO BE REPAIRED

AREA OF REPAIR. NOTE THAT II DETERIORATION PENETRATES FULL DEPTH OF MEMBER - THE MEMBER MUST BE REPAIRED WITH A DUTCHMAN

- MASONRY TO BE REPOINTED - NOTE THAT ACTUAL FINISH MAY VARY FROM THIS DRAWING

- COMPOSITE RECESS JOINT TO A VOID JOINT FACE GREATER THAN EXISTING WIDTH

AND FILL WITH APPROVED REPOINTING MORTAR -

NOTES:

1. PROVIDE JOINT MOCK-UP.
2. PROFILES OR CONDITIONS SHOWN MAY NOT REFLECT
ACTUAL EXISTING CONDITIONS - NEW POINTING TO

MATCH EXISTING TOOLING AT OLDER/ORIGINAL

REPOINTING OF MODERATELY


TOOLING TO MATCH OF AND ACCORDING TO APPROVED MOCK-UP

TOOLING TO MATCH ORIGINAL

-1/8" MAXIMUM EROSION

WOOD DUTCHMAN DETAIL
T


© COPYRIGHT 2022 CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC. UNAUTHORIZED REPRODUCTION OF THESE DRAWINGS IS PROHIBITED WITHOUT WRITTEN CONSENT OF THE ARCHITECT




LOST PLASTER KEY

- CUT BACK EXISTING PLASTER FINISH COAT TO ATTACH WASHERS - APPLY NEW FINISH PLASTER OVER AREA OF REPAIR


EXISTING WOOD LATH






INTERIOR REPAIR NOTES









RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

PLASTER ON LATH DETAIL

N. T

PLASTER SCRATCH COAT KEYED TO NEW LATH

PLASTER ON METAL LATH DETAIL

T

EXISTING WOOD LATH

to an to and and

APPLY FINISH PLASTER OVER JOINT BETWEEN EXISTING AND NEW SCRATCH COATS


NEW WOOD LATH



20 0

PLASTER WASHER TYING DISPLACED SCRATCH COAT TO WOOD LATHISTRUCTURE - SET WASHER AND SCREW HEAD BELOW SURFACE OF PLASTER FINISH COAT. CONCEAL ALL

MECHANICAL ATTACHMENTS, TYP.




PLASTER ON BRICK DETAIL




NOTE REFER TO ELECTRICAL LIGHTING FIXTURE SCHEDULE FOR FIXTURE INFORMATION


FIRST FLOOR REFLECTED CEILING PLAN




0

ONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC P.O. Box 1726 Cranford, N.J. 07016









3 EXTERIOR CONCRETE WALK DETAIL
1' 0"

 $\underbrace{\begin{array}{c}
5 \\
A9
\end{array}}_{3"} \underbrace{\begin{array}{c}
HANDRAIL \ DETAIL \\
1'
\end{array}}_{0"}$





OPERABLE ACOUSTIC PARTITION JAMB DETAIL

1'

10"

© COPYRIGHT 2022 CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC. UNAUTHORIZED REPRODUCTION OF THESE DRAWINGS IS PROHIBITED W

CONNOLLY & HICKEY

HISTORICAL ARCHITECTS, LLC P.O. Box 1726

Cranford, N.J. 07016



THOMAS B. CONNOLLY, AIA NJ 21AI01699200 PA RA403776

MARGARET M. HICKEY, AI-NJ 21AI018244500


PROJECT No.: 2016C


DATE: 08 AUGUST 2022


DRAWN BY: MS, TJ, CB, PK


RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

A9










© COPYRIGHT 2022 CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC. UNAUTHORIZED REPRODUCTION OF THESE DRAWINGS IS PROHIBITED WITHOUT WRITTEN CONSENT OF THE ARCHITECT.





INTERIOR REPAIR KEY

NNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC

Cranford, N.J. 07016

973 746-4911


THOMAS B. CONNOLLY, A NJ 21A101699200 PA RA403776


MARGARET M. HICKEY, ALA NJ 21A1018244500

PROJECT No.: 2016C DATE: 08 AUGUST 2022


REVISIONS:

DRAWN BY: MS, TJ, CB, PK





© COPYRIGHT 2022 CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC. UNAUTHORIZED REPRODUCTION OF THESE DRAWINGS IS PROHIBITED WITHOUT WRITTEN CONSENT OF THE ARCHITECT






DRAWN BY: MS, TJ, CB, PK

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

A17

© COPYRIGHT 2022 CONNOLLY & HICKEY HISTORICAL ARCHITECTS LLC. LINALTE







HISTORICAL ARCHITECTS, LLC Cranford, N.J. 07016




THOMAS B. CONNOLLY, AL NJ 21A101699200 PA RA403776


MARGARET M. HICKEY, AIA NJ 21AI018244500


DATE: 08 AUGUST 2022

DRAWN BY : MS, TJ, CB, PK



1. APPLIANCES AND PLUMBING FIXTURES TO BE PROVIDED AND INSTALLED BY CONTRACTOR





CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC

P.O. Box 1726 Cranford, N.J. 07016 973 746-4911



THOMAS B. CONNOLLY, AI NJ 21A101699200 PA RA403776

MARGARET M. HICKEY, AL NJ 21AI018244500 PROJECT No.: 2016C

DATE: 08 AUGUST 2022


DRAWN BY: MS, TJ, CB, PK

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

FOR REPAIRS TO CEILING -

PLUMBIN	G FIXTU	RE AND APPLI ID ALTERNATE NO 1	ANCE SCHEDULE
ITEM	MAKE	MODEL NUMBER	REMARKS
(2) SIDE BY SIDE REFRIDGERATORS	GENERAL ELECTRIC	69.5 INCH /23.2 CU. FT. BUILT-IN - MODEL No GSS23GSKSS	STAINLESS STEEL
RECIRCULATING HOOD	HALIFAX	EXHP448 TYPE 1 4' X 48' COMMERCIAL KITCHEN HOOD SYSTEM	STAINLESS STEEL
COOKTOP	COOKING PERFORMANCE GROUP		STAINLESS STEEL
MICROWAVE OVEN	SHARP	MODEL No. #R1214T ITEM NO. #270185	STAINLESS STEEL
PREP SINK WORK TABLE	REGENCY	MODEL No. ST3048LFT	STAINLESS STEEL
TRIPLE SINK WITH COUNTER	REGENCY	MODEL No. DTC202096LFT	STAINLESS STEEL
DISHWASHER	CHAMPION	MODEL No. DL2000X	STAINLESS STEEL
HAND SINK	REGENCY	MODEL No. HS12	STAINLESS STEEL
COFFEE MAKER	BUNN - AIRPOT COFFEE BREWER	MODEL No. CWTF15-APS	STAINLESS STEEL
ICE MACHINE	MANITOWOC	MODEL No. UYF-014OA Neo 26"	STAINLESS STEEL
PROOFING CABINET (WARMING OVEN)	VULCAN	MODEL No. VP18-1M3ZN	STAINLESS STEEL
WATER COOLER AND REFILL STATION	ELKAY	MODEL No. EZS8WSLK	LIGHT GRAY
REFIGERATORS	GE	MODEL No. GSS23GSKSS	STAINLES STEEL
AUTOMATIC FIRE EXTINGUISHING SYSTEM	ANSUL	R-102 RESTAURANT FIRE SUPPRESSION SYSTEM	AT RANGE HOOD

NOTES:







CONNOLLY & HICKEY

HISTORICAL ARCHITECTS, LLC P.O. Box 1726

Cranford, N.J. 07016





THOMAS B. CONNOLLY, AIA NJ 21A101699200 PA RA403776


MARGARET M. HICKEY, AL NJ 21AI018244500

PROJECT No.: 2016C DATE: 08 AUGUST 2022

REVISIONS:

DRAWN BY: MS, TJ, CB, PK

^{1.} APPLIANCES AND PLUMBING FIXTURES TO BE PROVIDED AND INSTALLED BY CONTRACTOR.



CONNOLLY & HICKE

Cranford, N.J. 07016

973 746-4911

IOMAS B. CONNOLLY,

MARGARET M. HICKEY, AI NJ. 21AI018244500

PROIECT No.: 2016C DATE: 08 AUGUST 2022

DRAWN BY : MS, TJ, CB, PK

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY


© COPYRIGHT 2022 CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC. UNAUTHORIZED REPRODUCTION OF THESE DRAWINGS IS PROHIBITED WITHOUT WRITTEN CONSENT OF THE ARCHITE





NOTES:

1. SEE PLUMBING DRAWINGS FOR FIXTURES AND FITTINGS

SEE MECHANICAL DRAWINGS FOR







© @ WATER CLOSET

ARCHITECTS, LLC P.O. Box 1726 Cranford, N.J. 07016

ONNOLLY & HICKE



THOMAS B. CONNOLLY, AI NI 21AI01699200 NJ 21AI01699: PA RA403776

MARGARET M. HICKEY, AL NJ 21AI018244500


REVISIONS:


PROJECT No.: 2016C DATE: 08 AUGUST 2022

DRAWN BY: MS, TJ, CB, PK

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

BARRIER-FREE RESTROOM CLEARANCES DETAIL (D137)







ACCESSIBLE WOMEN'S RESTROOM PLAN

ACCESSIBLE WOMEN'S RESTROOM ELEVATIONS

	DOOR				DOOR REPAIR		T		
OOR NO	TYPE	MATERIAL	SIZE	FRAME REPAIRS	DOOR REPAIRS	APPLICABLE RATING	GLAZING	HARDWARE SET NO.	REMARKS
ASEMENT					T		_	7	NEW FIRE RATED DOOR, FRAME.
D021	1	STEEL	±2'-8" x ±6'-8"	NEW STEEL FRAME	NEW STEEL DOOR	20 MIN. RATED	•		HARDWARE AND GASKETING
D022	1	STEEL	±2'-10" x ±6'-8"	NEW STEEL FRAME	NEW STEEL DOOR	20 MIN. RATED		7	NEW FIRE RATED DOOR, FRAME, HARDWARE AND GASKETING
RST FLOC	R			SURFACE PREPARE, PRIME AND	1				
D101	A	WOOD	SEE TYPE	2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR		NEW TEMPERED LITES. INSTALL NEW GLAZING PUTTY	4	
D111	c	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR	-	NEW TEMPERED LITES, INSTALL NEW GLAZING PUTTY	4	
D120	В	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR	-	NEW TEMPERED LITES. INSTALL NEW GLAZING PUTTY	4	
D132	F	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR	-	NEW TEMPERED LITES. INSTALL NEW GLAZING PUTTY.	5	
D133	D	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR		NEW FROSTED TEMPERED LITE. INSTALL NEW GLAZING PUTTY.	2	
D134	E	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR		NEW TEMPERED LITES. INSTALL NEW GLAZING PUTTY.	6	
D135	D	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR		NEW TEMPERED LITES. INSTALL NEW GLAZING PUTTY.	6	
D136	D	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR		NEW TEMPERED LITES. INSTALL NEW GLAZING PUTTY	6	
D137	н	WOOD	SEE TYPE	NEW WOOD FRAME, PRIME AND 2-COAT FINISH PAINT	NEW WOOD DOOR, PRIME AND 2-COAT FINISH PAINT		NO LITE	3	
D138	G	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR		NEW TEMPERED LITES. INSTALL NEW GLAZING PUTTY. 5		
D139	D	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR		NEW TEMPERED LITES, INSTALL NEW GLAZING PUTTY	1	
D140	D	wood	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR	-	NEW TEMPERED LITES INSTALL NEW GLAZING PUTTY	1	
D141	D	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR		NEW TEMPERED LITES. INSTALL NEW GLAZING PUTTY	1	
D142	G	WOOD		NEW WOOD FRAME, PRIME AND 2-COAT FINISH PAINT	NEW WOOD DOOR, PRIME AND 2-COAT FINISH PAINT		TEMPERED GLAZING	5	
D143	D	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE. PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR	-	NEW TEMPERED LITES. INSTALL NEW GLAZING PUTTY	1	
D144	D	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT ALL SIX SIDES OF DOOR		NEW TEMPERED LITES. INSTALL NEW GLAZING PUTTY.	1	
D145	н	WOOD	SEE TYPE	NEW WOOD FRAME, PRIME AND 2-COAT FINISH PAINT	NEW WOOD DOOR, PRIME AND 2-COAT FINISH PAINT		TEMPERED GLAZING	1	
D146	н	WOOD	SEE TYPE	NEW WOOD FRAME, PRIME AND 2-COAT FINISH PAINT	NEW WOOD DOOR, PRIME AND 2-COAT FINISH PAINT		NO LITE	3	
D146A	н	WOOD	2'-9"	NEW WOOD FRAME, PRIME AND 2-COAT FINISH PAINT	EXISTING DOOR TO BE FIXED. SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT		REPLACE LITE WITH WOOD PANEL, PRIME AND 2-COAT FINISH PAINT	N/A	EXISTING DOOR TO BE FIXED IN PLAC FROM BEHIND, NO HARDWARE, EPOX REPAIR HOLES IN DOOR.
D149	н	WOOD	SEE TYPE	SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME	SURFACE PREPARE. PRIME AND 2-COAT FINISH PAINT TRIM AND FRAME		-	1	REFAIR HOLES IN DOOR.
D158	н	WOOD		NEW WOOD FRAME, PRIME AND 2-COAT FINISH PAINT	NEW WOOD DOOR, PRIME AND 2-COAT FINISH PAINT		NO LITE	2	
D159	Н	WOOD	SEE TYPE	NEW WOOD FRAME, PRIME AND 2-COAT FINISH PAINT	NEW WOOD DOOR, PRIME AND 2-COAT FINISH PAINT		NO LITE	2	
D160	н	WOOD	SEE TYPE	NEW WOOD FRAME, PRIME AND 2-COAT FINISH PAINT	NEW WOOD DOOR, PRIME AND 2-COAT FINISH PAINT		NO LITE	2	
D161	н	wood	SEE TYPE	NEW WOOD FRAME, PRIME AND 2-COAT FINISH PAINT	NEW WOOD DOOR, PRIME AND 2-COAT FINISH PAINT		TEMPERED GLAZING	1	
D162	н	WOOD		NEW WOOD FRAME, PRIME AND 2-COAT FINISH PAINT	NEW WOOD DOOR, PRIME AND 2-COAT FINISH PAINT	-	NO LITE	2	
D163	н	WOOD		NEW WOOD FRAME, PRIME AND 2-COAT FINISH PAINT	NEW WOOD DOOR, PRIME AND 2-COAT		TEMPERED GLAZING	2	

DOOR REPAIR NOTES:

L RESTORE ALL DOORS TO PERMIT SMOOTH AND EASY OPERATION.

2. REPAIR WOOD PERAME AS INDICATED IN SCILEDIUE. REMOVE DOORS & REPAIR OFF-SITE WHEN REQUIRED.

3. DUTCHMAN REPAIR AT ALL LOSSES LARGER THAIN TWO INCIRES IN ANY DIMENSION.

4. FROMY REPAIR FOR PILLING LOSS AND VOIDS TWO INCIRES OR SMALLER.

5. AT WOOD DOORS TO BE RESTORED. REMOVE PAINT AND MAKE ALL EXISTING BLASSY AND INSTALL NEW LINSEED OIL GLAZING PUTTY.


4. AT DOORS TO BE RESTORED. REMOVE PAINT. AND MAKE ALL EXISTING ILARDWARE OPERABLE.


5. RAKE IONT BETWEEN WOOD PERAME AND TWO COATS FINISH PAINT TO ALL EXFERIOR AND INTERIOR (SUPERACES) OF DOORS AND FRAMES.

6. SURFACE PREPARE. APPLY PRIMER AND TWO CO. COATS FINISH PAINT TO ALL EXFERIOR AND INTERIOR (SUPERACES) OF DOORS AND FRAMES.

7. ALL DOORS SHALL BE TITTED WITH DOOR STON'S ORDER OF PRIGNITY FOR INSTALLATION. AT WALL, AT FLOOR, AT DOOR, AT DOOR, ON HINGE). REVIEW CONDITIONS WITH ARCHITECT PRIOR TO INSTALLATION.

8. ALLOW FOR 3 CU. IN OF PROXY REPAIR PER DOOR AND A TOTAL OF 10 SF OF WOOD DUTCHMAN REPAIR AT THE DOORS.






HEAD/SIDE JAMB DETAIL A23 3'

CONDITIONS (FIELD VERIFY ALL EXISTING CONDITIONS AS PART OF SUBMITTAL PROCESS) DOOR BUCK DETAIL

A23 3" = ...

DOOR HARDWARE SCHEDULE HARDWARE SET NO. 1 ITEM TYPE QUANTITY ITEM DESCRIPTION ITEM TYPE ITEM DESCRIPTION FINISH T SECURITY HINGE SET BUTT SECURITY HINGE SET LOCKSET HANDLE SET LEVER HANDLE BRASS HANDLE SET LEVER HANDLE EXIT DEVICE DOOR NUMBER: D133, D158, D159, D160, D162, D163 ENIT DEVICE TRIM ENIT DEVICE TRIM COORDINATOR COORDINATOR PARALLEL ARM WITH COVER AND BUILT-IN DOOR STOP CLOSER BRASS CLOSER THRESHOLD THRESHOLD CLOSER TO LIMIT DOOR FROM OVER DOOR STOP DOOR STOP THERMISC HARDWARE SET NO. 3 HARDWARE SET NO. 4 ITEM TYPE BUTT SECURITY HINGE SET BRASS BUTT SECURITY HINGE SET LOCKSET ENTRANCE
LEVER HANDLE AT EXTERIOR
SIDE, INTEGRAL WITH PANIC
HARDWARE AT INTERIOR.
BOSTINE ANDLE SET LEVEL HANDLE HANDLE SET POSITIVE
SURFACE MOUNTED VERTICAL
ROD WITH CROSSBAR
HANDLE SET WITH CYLINDER
AND THUMB PRESS EXIT DEVICE EXIT DEVICE DOOR NUMBER: EXIT DEVICE TRIM DOOR NUMBER: EXIT DEVICE TRIN COORDINATOR COORDINATOR PARALLEL ARM WITH COVER AND BUILT-IN DOOR STOP MARBLE THRESHOLD, ADA CLOSER BRASS CLOSER THRESHOLD NEW METAL, ADA COMPLIANT COMPLIANT- SEE CLOSER TO LIMIT DOOR FROM CLOSER TO LIMIT DOOR FROM DOOR STOP DOOR STOP OVER EXTENDING
PROVIDE WEATHERSTRIPPING
AT JAMBS, HEAD AND SILL.
PROVIDE 8" KICK PLATES ON
INTERIOR SIDE. OVIDE 8" KICK PLATES, EACH SIDE CHROME THER/MISC. HARDWARE SET NO. 5 HARDWARE SET NO. 6 ITEM TYPE ITEM DESCRIPTION FINISH OUANTITY ITEM DESCRIPTION 3 PER LEAF, BUTT SECURITY HINGE BUTT SECURITY HINGE SET BRASS LOCKSET LOCKSET LASSROOM HANDLE SET LEVER HANDLE HANDLE SET LEVER HANDLE BRASS POSITIVE WITH FLUSH BOLT SURFACE MOUNTED VERTICAL ROD WITH CROSSBAR LATCH SURFACE MOUNTED VERTICAL ROD WITH CROSSBAR DOOR NUMBER: EXIT DEVICE D132, D138, D142 EXIT DEVICE EXIT DEVICE TRIM LEVER HANDLE BRASS EXIT DEVICE TRIA LEVER HANDLE AS PART OF PANIC EXIT DEVICE COORDINATOR COORDINATOR PARALLEL ARM WITH COVER AND BUILT-IN DOOR STOP VINYL THRESHOLD, ADA COMPLIANT - SEE CLOSER TO LIMIT DOOR FROM OVER EXTENDING PARALLEL ARM WITH COVER AND BUILT-IN DOOR STOP CLOSER CLOSER HRESHOLD THRESHOLD LOSER TO LIMIT DOOR FROM OVE DOOR STOP DOOR STOP PROVIDE 8" KICKPLATES ON EACH THER/MISC. HARDWARE SET NO. 7 HARDWARE SET NO. - NOT USED ITEM DESCRIPTION FINISH ITEM TYPE QUANTITY ITEM DESCRIPTION FINISH STEEL BALL BEARING HINGES LOCKSET CLASSROOM LOCKSET HANDLE SET LEVER HANDLE HANDLE SET LATCH EXIT DEVICE DOOR NUMBER: D021, D022 EXIT DEVICE TRIM EXIT DEVICE TRIA COORDINATOR PARALLEL ARM WITH COVER AN CLOSER THRESHOLD THRESHOLD CLOSER TO LIMIT DOOR FROM OVER EXTENDING 20 MINUTE FIRE RATING, PROVIDE GASKETING DOOR STOP DOOR STOP THER/MISC. OTHER/MISC.



CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC P.O. Box 1726


Cranford, N.J. 07016



THOMAS B. CONNOLLY, A NJ 21AI01699200 PA RA403776 MARGARET M. HICKEY, AL NJ 21AI018244500

PROJECT No. 2016C DATE: 08 AUGUST 2022

DRAWN BY : MS, TJ, CB, PK





HISTORICAL

P.O. Box 1726 Cranford, N.J. 07016



THOMAS B. CONNOLLY, AIAN) 21-AI01699200 PA RA403776

MARGARET M. HICKEY, AI NJ 21AI018244500

PROJECT No.: 2016C

DATE: 08 AUGUST 2022

REVISIONS:

DRAWN BY: MS, TJ, CB, PK

RESTORATION AND REHABILITATION
WILLIAM R. ALLEN SCHOOL
BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

A24

WINDOW REPAIR SCHEDULE										
ASEMENT										
TAG	TYPE/ DESCRIPTION	SIZE	FRAME REPAIRS	SASH REPAIRS	GLAZING	HARDWARE	REMARKS	STORM WINDOWS		
W001	EXISTING A	±2' - 8" x ±4' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL		
W002	EXISTING A	±2' • 8" x ±4' • 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL		
W003	EXISTING A	±2' • 8" x ±4' • 0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW ENTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL		
W005	EXISTING A	±2" - 8" x ±4" - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REFAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORY WINDOW AND INSECT SCREEN - SEE DETAIL		
W007	EXISTING A	±2' - 8" x ±4' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STOR WINDOW AND INSECT SCREEN - SEE DETAIL		
W008	EXISTING A	±2" - 8" x ±4" - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	NEW TEMPERED GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORY WINDOW AND INSECT SCREEN - SEE DETAIL		
W009	EXISTING A	±2" - 8" x ±4" - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE. PRIME, AND 2-COAT FINISH PAINT SASH	NEW TEMPERED GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL		
W010	EXISTING A	±2' - 8" x ±4' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	NEW TEMPERED GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORA WINDOW AND INSECT SCREEN - SEE DETAIL		
W011	EXISTING A	±2" - 8" x ±4" - 0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH	NEW TEMPERED GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL		
W012	EXISTING A	±2" - 8" x ±4" - 0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL		
W013	EXISTING A	±2'-8" x ±4'-0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL		
W014	EXISTING A	±2'-8" x ±4'-0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORY WINDOW AND INSECT SCREEN - SEE DETAIL		
W015	EXISTING A	±2'-8" x ±4'-0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STOR WINDOW AND INSECT SCREEN - SEE DETAIL		
W016	EXISTING A	±2" - 8" x ±4" - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STOR WINDOW AND INSECT SCREEN - SEE DETAIL		
W017	EXISTING A	±2' - 8" x ±4' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORY WINDOW AND INSECT SCREEN - SEE DETAIL		
W018	EXISTING A	±2" - 8" x ±4" - 0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORI WINDOW AND INSECT SCREEN - SEE DETAIL		
W019	EXISTING G	±2"-8" x ±4"-0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STOR! WINDOW AND INSECT SCREEN - SEE DETAIL		
W020	EXISTING A	±2' - 8" x ±4' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STOR WINDOW AND INSECT SCREEN - SEE DETAIL		
W021	EXISTING A	±2'-8" x ±4'-0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPAIRE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORI WINDOW AND INSECT SCREEN - SEE DETAIL		
W022	EXISTING A	±2' - 8" x ±4' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPAIRE, PRIME, AND 2-COAT FINISH PAINT SASH	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STOR WINDOW AND INSECT SCREEN - SEE DETAIL		
W023	EXISTING A	±2'-8" x ±4'-0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STOR WINDOW AND INSECT SCREEN - SEE DETAIL		
\V024	NEW A	±2'-8" x ±4'-0"				HINGES AND HOPPER LOCK	NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STOR WINDOW AND INSECT SCREEN - SEE DETAIL		

WINDOW REPAIR NOTES:

WINDOW REPAIR NOTES:

RESTORE ALL WINDOWS TO PERMIT SMOOTH AND EASY OPERATION

REPAIR WOOD FRAMES AND SASHIES AS INDICATED IN SCHEDULE. RIMOVE SASHES AND REPAIR OFF-SITE WHEN REQUIRED.

DUTCHINAN REPAIR AT ALL LOSSES LAKEER THAN TOOL THE THAN Y IMMENSION

FROM SEPAIR FOR FILLING LOSS AND VOIDS TWO INCIRES OR SMALLE!

AT WINDOWS TO BE RESTORED. REMOVE ALL GLAZING COMPOIND GET AND YEAR AND INSTALL NEW LINSEED OIL GLAZING PUTTY.

AT WINDOWS TO BE RESTORED. REMOVE PAINT, AND MAKE ALL EXISTING HARDWARE OPERABLE.


RAKE JOINT BETWEEN WOOD FRAME AND MASONRY, INSTALL NEW SEALANT. TYPICAL AT ALL WINDOW AND DOOR OPENINGS.

SURFACE PREPAIR. APPLY PRIMER AND TWO (2) COATS FINISH PAINT TO ALL EXTERIOR AND INTERIOR (SURFACES) OF SASH & FRAMES ALLOWANCES:


1. ALLOW FOR TEN (10) ADDITIONAL GLASS PANE (±9 X 12") REPLACEMENTS IN KIND USING RESTORTION GLASS.

(IT IS THE CONTRACTORS RESPONSIBILITY TO USE CARE WHEN REMOVING GLAZING PUTTY SO THAT GLASS IN OTI BROKEN)

2. ALLOW FOR 3 CU. IN. OF EPOXY REPAIR PER WINDOW AND A TOTAL OF 30 LF OF WOOD DUTCHMAN REPAIR AT THE WINDOWS











CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC P.O. Box 1726 Cranford, N.J. 07016 973 746-4911

THOMAS B. CONNOLLY, AL. NJ 21AI01699200 PA RA403776 MARGARET M. HICKEY, ALA NJ 21AI018244500

PROJECT No.: 2016C DATE: 08 AUGUST 2022


DRAWN BY: MS, TJ, CB, PK


	WINDOW REPAIR SCHEDULE (CONTINUED)										
FIRST FI	TYPE/	SIZE	FRAME REPAIRS	SASH REPAIRS	OL AZING						
W102	DESCRIPTION EXISTING K	± 3' - 5" x ± 6' - 5"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND ENTERIOR.	SASH REPAIRS ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SASH, THOROUGHLY SURFACE PREPAIR PRINE, AND 2-COAT FINISH PAINT	GLAZING LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY	HARDWARE	NEW SEALANT BETWEEN TRIM AND BRICK	STORM WINDOWS NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W103	EXISTING D	± 4' - 2" x ± 10' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	SASH. ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE. PRIME. AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW ENTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W104	EXISTING C	± 13' - 3" x ± 10'- 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND ENTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME. AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W105	EXISTING D	± 4' - 2" x ± 10' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W106	EXISTING D	± 4' - 2" x ± 10' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W107	EXISTING C	± 13' • 3" x ± 10'• 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W108	EXISTING D	± 4' - 2" x ± 10' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE. PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W109	EXISTING K	± 3' - 5" x ± 6' - 5"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW ENTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W110	EXISTING K	± 3' - 5" x ± 6' - 5"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME. AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W112	EXISTING D	± 4' - 2" x ± 10' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASII. THOROUGHLY SURFACE PREPARE, PRIME. AND 2-COAT FINISH PAINT SASII.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W113	EXISTING J	± 13' - 3" x ± 10'- 0"	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W114	EXISTING J	± 4' - 2" x ± 10' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASIL THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W115	EXISTING 3	± 3' - 8" x ± 8' - 6"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W116	EXISTING J	± 3' - 8" x ± 8' - 6"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPONY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE. PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W117	EXISTING J	± 3' - 8" x ± 8' - 6"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W118	EXISTING J	± 3' - 8" x ± 8' - 6"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W119	EXISTING J	± 3' - 8" x ± 8' - 6"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W121	EXISTING K	± 3' - 5" x ± 6' - 5"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR. ALLOW FOR MINOR DUTCHMAN AND EPOXY	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH. ALLOW FOR MINOR DUTCHMAN AND EPOXY	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W122	EXISTING J	± 3' - 8" x ± 8' - 6"	REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR. ALLOW FOR MINOR DUTCHMAN AND EPOXY	REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY:		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W123	EXISTING J	± 3' - 8" x ± 8' - 6"	REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE. PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W124	EXISTING J	± 3' - 8" x ± 8' - 6"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W125	EXISTING J	± 3' - 8" X ± 8' - 6"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE. PRIME. AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W126	EXISTING I	± 11' - 9" x ± 8' - 6"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH, THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW ENTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W127	EXISTING J	± 3' - 8" x ± 8' - 6"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W128	EXISTING D	± 4' - 2" x ± 10' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W129	EXISTING C	± 13' - 3" x ± 10'- 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL, PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W130	EXISTING D	± 4' - 2" x ± 10' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			
W131	EXISTING I	± 3' - 5" x ± 6' - 5"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE. PRIME, AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREEN - SEE DETAIL			

			ALLOW FOR MINOR DUTCHMAN AND EPOXY	ALLOW FOR MINOR DUTCHMAN AND EPOXY	LIGHT RESTORATION GLASS	T	NEW SEALANT BETWEEN	NEW EXTERIOR STORM
W201	ENISTING E	± 1' - 10" x ± 3' - 0"	REPAIRS OF SILL. PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR	REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE, PRIME, AND 2-COAT FINISH PAINT SASH.	WITH LINSEED OIL GLAZING PUTTY		TRIM AND BRICK	WINDOW AND INSECT SCREE - SEE DETAIL
W202	EXISTING E	± 1' - 10" x ± 3' - 0"	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SILL PRIME AND 2-COAT FINISH PAINT THE INTERIOR AND EXTERIOR.	ALLOW FOR MINOR DUTCHMAN AND EPOXY REPAIRS OF SASH. THOROUGHLY SURFACE PREPARE. PRIME. AND 2-COAT FINISH PAINT SASH.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		NEW SEALANT BETWEEN TRIM AND BRICK	NEW EXTERIOR STORM WINDOW AND INSECT SCREE - SEE DETAIL
	OOR INTERIOR							
	TYPE/ DESCRIPTION	SIZE	FRAME REPAIRS	SASH REPAIRS	GLAZING	HARDWARE	REMARKS	1
W147	EXISTING H	± 2' - 6" x ± 3' - 4"	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES	REPLACE BROKEN GLAZING			
W148	EXISTING H	± 2' - 6" x ± 3' - 4"	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY			-
W149	EXISTING H	± 2' - 6" x ± 3' - 4"	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES	REPLACE BROKEN GLAZING			
W150	EXISTING H	± 2' - 6" x ± 3' - 4"	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES	REPLACE BROKEN GLAZING			
W151	EXISTING II	± 2' - 6" x ± 3' - 4"	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY			
W152	EXISTING H	± 2' - 6" x ± 3' - 4"	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	LIGHT RESTORATION GLASS WITH LINNEED OIL GLAZING PUTTY			
W153	EXISTING II	± 2' - 6" x ± 3' - 4"	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY			
W154	EXISTING H	± 2' - 6" x ± 3' - 4"	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY			
W155	EXISTING H	± 2' - 6" x ± 3' - 4"	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY			
W156	EXISTING H	± 2' - 6" x ± 3' - 4"	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY			-
W157	EXISTING H	± 2' - 6" x ± 3' - 4"	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY.			
W158	EXISTING 6 / 3 FIXED WOOD WINDOW		PRIME AND 2-COAT FINISH PAINT ALL SIDES.	PRIME AND 2-COAT FINISH PAINT ALL SIDES.	LIGHT RESTORATION GLASS WITH LINSEED OIL GLAZING PUTTY		INTERIOR WINDOW AT MEZZANINE	



A26





CONNOLLY & HICKEY

HISTORICAL ARCHITECTS, LLC P.O. Box 1726

Cranford, N.J. 07016 973 746-4911



THOMAS B. CONNOLLY, AIA NJ 21A101699200 PA RA403776

MARGARET M. HICKEY, AI. NJ 21AI018244500

PROJECT No.: 2016C

DATE: 08 AUGUST 2022 REVISIONS:

DRAWN BY: MS, TJ, CB, PK

ROOM NUMBER	ROOM NAME	SURFACE					FINIC	H COHER						
			MATERIAL	FINISHES / REMARKS				H SCHEDU	JLE					
001	ENTRY	FLOOR - BOTTON LANDING	- INTO CONCRETE		_		WALLS	EMSTING PLASTER	REPAIR AS INDICATED ON ELEVAT SURFACE PREPARE, PRIME AND 2-C FINISH PAINT	IONS.				
		FLOOR - TOP LANDI	NEW OAK STRIP WOOD FLOORING	SAND, SEAL, STAIN AND 3-COAT	_			EXISTING WOOD	FINISH PAINT.	OAT		WALLS	EXISTING PLASTER	REPAIR AS INDICATED ON ELEV
		WALLS	EXISTING PLASTER	REPAIR AS INDICATED ON ELEVATI SURFACE PREPARE, PRIME AND A CO	ONS.		BASE AND CR	***	REPAIR AS INDICATED ON ELEVATI SURFACE PREPARE, PRIME AND 2-C FINISH PAINT.	OAT			EXISTING WOOD AND NEW WOOI	FINISH PAINT.
		BASE AND CROWN	EXISTING WOOD	FINISH PAINT. REPAIR AS INDICATED ON ELEVATIC SURFACE PREPARE, PRIME AND 2-OC FINISH PAINT			TRIM	EXISTING WOOD	REPAIR AS INDICATED ON ELEVATION SURFACE PREPARE, PRIME AND 2-CO	ONS. DAT		BASE AND CR	OMN	SURFACE PREPARE, PRIME AND FINISH PAINT
		TRIM	EXISTING WOOD	REPAIR AS INDICATED ON ELEVATION SURFACE PREPARE PRIME AND A CO			CEILING	EXISTING PLASTER	REPAIR AS INDICATED ON REFLECTI CEILING PLAN. SURFACE PREPARE, PRIME AND 2-COAT FINISH	1		TRIM	EXISTING WOOD AND NEW WOOD	REPAIR AS INDICATED ON ELEVA SURFACE PREPARE, PRIME AND 2 FINISH PAINT.
		CEILING	EXISTING PLASTER	FINISH PAINT. REPAIR AS INDICATED ON REFLECTE CEILING PLAN. SURFACE PREPARE. PRIME AND 2-COAT FINISH PAINT.		COMMUNITY :		NEW OAK STRIP WOOD FLOORING	a a coal finish Paint.				EXISTING PLASTER	REPAIR AS INDICATED ON REFLE CEILING PLAN, SURFACE PREPAR PRIME AND A COATTON
001A A	MECHANICAL ROOM	FLOOR	VINYL SOLID SHEET FLOORING	PRIME AND 2-COAT FINISH PAINT.			Walte	EXISTING PLASTER	SAND, SEAL, STAIN AND 3-COAT WATER-BASED POLYURETHANE			CEILING		PRIME AND 2-COAT FINISH PAINT
		WALLS	EXISTING PLASTER WALLS AND NEW 5%" GYPSUM WALLBOARD - TAPE, SPACKLE AND SAND	SURFACE PREPARE, PRIME AND 2-CO: FINISH PAINT	AT .		WALLS BASE AND CRO	Evleran	SURFACE PREPARE. PRIME AND 2-CO.	AT				
		BASE	4" RUBBER WALL BASE	TAIN!	4		TRIM	EXISTING WOOD	REPAIR AS INDICATED ON ELEVATION SURFACE PREPARE. PRIME AND 2-CO. FINISH PAINT.	AT	CATERING KITCHE	N FLOOR	NEW 6 "x 6" QUARRY TILE OVER "SCHLUTER-KERDI" WATERPROOF	
		CEILING	EXISTING PLASTER	REPAIR AS INDICATED ON REFLECTEI CEILING PLAN. SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT	-		CEILING	EXISTING PLASTER	REPAIR AS INDICATED ON ELEVATION SURFACE PREPARE, PRIME AND 2-CO.9 FINISH PAINT.	AT			MEMBRANE (OR APPROVED EQUAL) NEW 5/8" GYPSUM WALLBOARD. T/ SPACKLE, PRIME AND 2-COAT FINIS PAINT. APPLY NEW FRP PANELS TO FOOT WAINSCOAT	GYPSUM WALLBOARD PROPERTY
002 VESTIBULE	FLOOR	NEW OAK STRIP WOOD FLOORING EXISTING PLASTER	SAND, SEAL, STAIN AND 3-COAT	104	COMMUNITY 4	FLOOR	NEW OAK STRIP WOOD FLOORING	REPAIR AS INDICATED ON REFLECTEL CEILING PLAN. SURFACE PREPARE. PRIME AND 2-COAT FINISH PAINT.	,		WALLS	FOOT WAINSOOT HEIGHT. COVER PANELS WITH PLASTIC COVERS PROVIDED BY FRP PANEL MANUFACTURER.	PROVIDE COLOR SAMPLES FOR FR PANEL FOR ARCHITECT SELECTION	
	L	WALLS	- TOTASTER	SURFACE PREPARE BRIME AND	S.			EXISTING PLASTER	SAND, SEAL, STAIN AND 3-COAT WATER-BASED POLYURETHANE	-		BASE	NEW 6" v 6" CANDELTON	
	BASE AND CROWN	EXISTING WOOD	REPAIR AS INDICATED ON ELEVATIONS SURFACE PREPARE PRIME AND A GOOD			WALLS	EXISTING WOOD	SURFACE PREPARE, PRIME AND 2-COATENISH PAINT	Г		TRIM	COVE BASE TO MATCH FLOOR TILE EXISTING WOOD AND NEW WOOD	REPAIR AS INDICATED ON ELEVAT SURFACE PREPARE, PRIME AND 2-C	
		TRIM	EXISTING WOOD	FINISH PAINT REPAIR AS INDICATED ON ELEVATIONS SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT	_		BASE AND CROW		REPAIR AS INDICATED ON ELEVATIONS SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT.	S.		CEILING	EXISTING PLASTER	SURFACE PREPARE, PRIME AND 2-C FINISH PAINT. REPAIR AS INDICATED ON REFLECT CEILING PLAN. SURFACE PREPARE. PRIME AND 2-COAT FINISH PANDE.
		CEILING	EXISTING PLASTER	REPAIR AS INDICATED ON REFLECTED	-		TRIM	EXISTING WOOD	REPAIR AS INDICATED ON ELEVATIONS SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT			CABINETRY	OVERHEAD CABINETS - PASSPORT B' KRAFTMAID (OR APPROVED EQUAL)	
100	HALL		NEW OAK STRIP WOOD FLOORING	SAND, SEAL STAIN AND A COURT			CEILING	EXISTING PLASTER	REPAIR AS ININGATED ON				EXISTING WOOD AND NEW WOOD	Dinon
	_	WALLS	EXISTING PLASTER	WATER-BASED POLYURETHANE REPAIR AS INDICATED ON ELEVATIONS. SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT	104A	CLOSET	FLOOR	NEW OAK STRIP WOOD FLOORING	PRIME AND 2-COAT FINISH PAINT.	108A	CLOSET	FLOOR		REPAIR AS INDICATED ON ELEVATION SURFACE PREPARE, PRIME AND 2-CO FINISH PAINT.
	-	BASE AND CROWN	EXISTING WOOD	REPAIR AS INDICATED ON ELEVATIONS. SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT			WALLS	EXISTING PLASTER AND NEW 5/8" GYPSUM WALL BOARD TABE OR A GUA	SAND, SEAL, STAIN AND 3-COAT WATER-BASED POLYURETHANE REPAIR AS INDICATED ON ELEVATIONS. E SURFACE PREPARE BEILD.	1		WALLS	VINYL SOLID SHEET FLOORING EXISTING PLASTER AND NEW 5/8" GYPSUM WALLBOARD - TAPE, SPACKL AND SAND	E
	-	IRIM		REPAIR AS INDICATED ON ELEVATIONS. SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT			BASE	AND SAND EXISTING WOOD	FINISH PAINT.	-		BASE	NEW 4" RUBBER BASE EXISTING PLASTER	
00A IANT	ITOR'S CLOSET	CEILING		REPAIR AS INDICATED ON REFLECTED CEILING PLAN. SURFACE PREPARE. PRIME AND 2-COAT FINISH PAINT.				EXISTING PLASTER	FINISH PAINT.	109	VESTIBULE	CEILING	NEW OAK STRIP WOOD FLOORING	REPAIR AS INDICATED ON REFLECTEI CEILING PLAN. SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT.
JANI	HOR'S CLOSET		INYL SOLID SHEET FLOORING	THIS TAIN.			CEILING	Markarak	REPAIR AS INDICATED ON REFLECTED CEILING PLAN. SURFACE PREPARE.				EXISTING PLASTER	SAND, SEAL, STAIN AND 3-COAT
				REPAIR AS INDICATED ON ELEVATIONS. SURFACE PREPARE, PRIME AND 2-COAT TNISH PAINT.	105	COMMUNITY 5	FLOOR	NEW OAK STRIP WOOD FLOORING	PRIME AND 2-COAT FINISH PAINT. SAND, SEAL, STAIN AND 3-COAT WATER-BASED POLYURETHANE			WALLS	EXISTING WOOD	REPAIR AS INDICATED ON ELEVATION SURFACE PREPARE, PRIME AND 2-COA FINISH PAINT
		BASE 4"	RUBBER WALL BASE				WALLS	EXISTING PLASTER	SURFACE PREPARE, PRIME AND 2 CO. IT.			BASE AND CROWN	- will wood	REPAIR AS INDICATED ON ELEVATION SURFACE PREPARE, PRIME AND 2-COAFINISH PAINT.
01 (0)		CEILING	C P	EPAIR AS INDICATED ON REFLECTED EILING PLAN. SURFACE PREPARE. RIME AND 2-COAT FINISH PAINT.			BASE AND CROWN	EXISTING WOOD	FINISH PAINT. REPAIR AS INDICATED ON ELEVATIONS. SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT.			TRIM	EXISTING WOOD	REPAIR AS INDICATED ON ELEVATION: SURFACE PREPARE, PRIME AND 2-COAT
COX	MMUNITY 1		W OAK STRIP WOOD FLOORING SA	AND, SEAL, STAIN AND 3-COAT				EXISTING WOOD				V2550	EXISTING PLASTER	PINISH PAINT.
		EXI	STDIG WAS FI	JRFACE PREPARE, PRIME AND 2-COAT NISH PAINT			TRIM		REPAIR AS INDICATED ON ELEVATIONS. SURFACE PREPARE. PRIME AND 2-COAT FINISH PAINT.	110	WOMEN'S RESTROOM	CEILING		REPAIR AS INDICATED ON REFLECTED CEILING PLAN. SURFACE PREPARE. PRIME AND 2-COAT FINISH PAINT.
	BA	SE AND CROWN		PAIR AS INDICATED ON ELEVATIONS. PREACE PREPARE, PRIME AND 2-COAT NISH PAINT.			CEU	EXISTING PLASTER	REPAIR AS INDICATES				12" x 24" BIO-BASED FLOOR TILE EXISTING PLASTER AND NEW 5/8" WATER RESISTANT GYPSUM	REPAIR AS INDICATED ON ELEVATIONS.
		TRIM		PAIR AS INDICATED ON ELEVATIONS. RFACE PREPARE, PRIME AND 2-COAT USH PAINT	106	RECEPTION / OFFICE	CEILING	NEW CONTROL	REPAIR AS INDICATED ON REFLECTED CEILING PLAN. SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT.				SAND. 3" x 6" CERAMIC WALL TILE WITH	
		CEILING	TING PLASTER REI	PAIR AS INDICATED CALLED				EXISTING PLASTER	SAND, SEAL, STAIN AND 3-COAT WATER-BASED POLYURETHANE REPAIR AS INDICATED ON ELEVATIONS. SURFACE PREPARE BRIDES.				The same of the VATIONS.	DALTILE OR APPROVED EQUAL
COMA	MUNITY 2		PRI	ME AND 2-COAT FINISH PAINT			BASE AND CROWN	EVICTING HIS	REPAIR AS INDICATED ON ELEVATIONS. SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT. REPAIR AS INDICATED ON ELEVATIONS. SURFACE PREPARE, PRIME AND 2-COAT FINISH PAINT		-	CROWN	EXISTING WOOD AND NEW WOOD	REPAIR AS INDICATED
	•		WA'	ND, SEAL, STAIN AND 3-COAT TER-BASED POLYURETHANE		ŀ		Cylorenia				A	EXISTING WOOD	REPAIR AS INDICATED ON ELEVATIONS. BURFACE PREPARE, PRIME AND 2-COAT TINISH PAINT.
							TRIM	S	REPAIR AS INDICATED ON ELEVATIONS. SURFACE PREPARE, PRIME AND 2-COAT SINISH PAINT.		-		XISTING PLASTER	REPAIR AS INDICATED ON ELEVATIONS. URFACE PREPARE, PRIME AND 2-COAT INISH PAINT.
							CEILING	XISTING PLASTER R	EPAIR AS INDICATED ON REFLECTED EILING PLAN, SURFACE PREPARE, RIME AND ACOAT ENTER PROPERTY.	111	MEN'S RESTROOM	CEILING		EPAIR AS INDICATED ON REFLECTED EILING PLAN. SURFACE PREPARE, RIME AND 2-COAT FINISH PAINT.
					107	OFFICE		P	RIME AND 2-COAT FINISH PAINT.					



CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC

P.O. Box 1726 Cranford, N.J. 07016 973 746-4911



THOMAS B. CONNOLLY, AIA NJ 21A101699200 PA RA403776 MARGARET M. HICKEY, AIA NJ 21A1018244500

PROJECT No.: 2016C

DATE: 08 AUGUST 2022

DRAWN BY: MS, TJ, CB, PK


	SIGN	IAGE SCH	IEDULE		
ROOM NO.	ROOM NAME	SIGNAGE TYPE SIGNAGE DESIGNATI		MOUNTING LOCATION	
FIRST FLOOR	i				
001A	MECHANICAL ROOM 1	ROOM SIGN 2 DETAIL	MECHANICAL ROOM	ON DOOR	
002	DOOR 021 TO BASEMENT	ROOM SIGN 2 DETAIL	STAFF ONLY	ON DOOR	
101, 102	COMMUNITY I AND COMMUNITY 2 (WITHIN SPACE)	ROOM SIGN 2 DETAIL	COMMUNITY ROOM 1-2	TO RIGHT OF DOOR CORRIDOR SIDE	
		MAXIMUM OCCUPANCY SIGN	MAXIMUM FIRE SAFETY OCCUPANCY - 150	TO LEFT OF DOOR, CLASSROOM SIDE	
103	COMMUNITY 3 (WITHIN SPACE)	ROOM SIGN 2 DETAIL	COMMUNITY ROOM 3	TO RIGHT OF DOOR CORRIDOR SIDE	
		MAXIMUM OCCUPANCY SIGN	MAXIMUM FIRE SAFETY OCCUPANCY - 28	TO LEFT OF DOOR, CLASSROOM SIDE	
104	COMMUNITY 4 (WITHIN SPACE)	ROOM SIGN 2 DETAIL	COMMUNITY ROOM 4	TO RIGHT OF DOOR CORRIDOR SIDE	
		MAXIMUM OCCUPANCY SIGN	MAXIMUM FIRE SAFETY OCCUPANCY - 26	TO LEFT OF DOOR, CLASSROOM SIDE	
105	COMMUNITY 5 (WITHIN SPACE)	ROOM SIGN 2 DETAIL	COMMUNITY ROOM 5	TO RIGHT OF DOOR CORRIDOR SIDE	
		MAXIMUM OCCUPANCY SIGN	MAXIMUM FIRE SAFETY OCCUPANCY - 26	TO LEFT OF DOOR, CLASSROOM SIDE	
106, 107	RECEPTION/OFFICE	ROOM SIGN 2 DETAIL	ADMINISTRATIVE OFFICE	TO LEFT OF DOOR, CORRIDOR SIDE	
		MAXIMUM OCCUPANCY SIGN	MAXIMUM FIRE SAFETY OCCUPANCY - 3	TO LEFT OF DOOR, CLASSROOM SIDE	
108	CATERING KITCHEN	ROOM SIGN 2 DETAIL	KITCHEN	TO RIGHT OF DOOR CORRIDOR	
		MAXIMUM OCCUPANCY SIGN	MAXIMUM FIRE SAFETY OCCUPANCY - 10	TO LEFT OF DOOR, CLASSROOM SIDE	
110	WOMEN RESTROOM	SIGN I DETAIL	INTERNATIONAL SYMBOLS FOR WOMEN AND FOR ACCESSIBILITY	TO LEFT OF DOOR, ENTRY HALL 2 SIDE	
111	MEN RESTROOM	SIGN 1 DETAIL	INTERNATIONAL SYMBOLS FOR MEN AND FOR ACCESSIBILITY	TO RIGHT OF DOOR, VESTIBULE 2 SIDE	

NOTE


1. ALL SIGNS MUST COMPLY WITH THE NJULC C. BARRIER-FREE SUBCODE AND THE UNIFORM FEDERAL ACCESSIBILITY STANDARDS (U.F.A.S. - A.D.A.A.G.)

2. SIGNS FOR DOORS SHALL BE MOUNTED ON THE DOOR. WITH THE BOTTOM MOST PART BEING 54" ABOVE FINISHED FLOOR (MIN) OR 6" AT FINISHED FLOOR MEASURED TO THE CENTERLINE OF THE UPPERMOST ROW OF CHARACTERS.


3. LOCATE WALL MOUNTED SIGNS ON THE WALL ADJACENT TO THE LATCH SIDE OF THE DOOR (OR THE NEAREST ADJACENT WALL) AT 6" ABOVE PRINSHED FLOOR FROM THE CENTERLINE OF THE SIGN (MAY SIZE) AND OUT OF THE SWING OF THE DOOR. MOUNT SIGNS WITH LATCH SIDE EDGE 4" FROM INSIDE FACE OF THE DOOR JAMB




TYPICAL MOUNTING HEIGHTS



LOCATION OF TEXT .:..::



ROOM SIGN TYPE



B ELEVATION - ADJACENT TO DOOR

© PLAN

ROOM SIGN PLACEMENT REQUIREMENTS 3 A29



CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC

P.O. Box 1726 Cranford, N.J. 07016



THOMAS B. CONNOLLY, AL NJ 21AI01699200 PA RA403776

MARGARET M. HICKEY, AI NJ 21AI018244500

PROJECT No.: 2016C DATE: 08 AUGUST 2022

DRAWN BY: MS, TJ, CB, PK

GOVERNING CODE 2018 INTERNATIONAL BUILDING CODE

- - A. ROOF : 15 PSF B. CEILING : 10 PSF (NO STORAGE) C. FIRST FLOOR : 31 PSF : 5TL BM SELF MEIGHT
- LIVE LOADS

 A. ROOF = 20 PSF (MINIMUM)

 B. CEILING = 10 PSF (NO STORAGE)

 C. FIRST FLOOR = 100 PSF

GENERAL NOTES

- HORS SHALL BE PEPROPED IN ACCORDANCE HTM THE "DOES INTERNATIONAL BULDING CODE "ALL BETTOM" AND ALL PEPPAN AND CITT LANE BUTLAND, GORDANCE AND REGILATIONS IN ANY HANDER AFFECTION STOCK CONDICTS ON THOSE AS INCL. AS CRIDERS OR DECREES HISCH HAVE BEEN PROMALANTED OR BHACTED BY ANY LEAR EDODES OR TRIBINALS HAVING ANY CONTROL ARSOCICTION OVER THE MOOK, MATERIALS, SHET LOSS OR CONTROL THE CONTRACTOR SHALL BE EN ACCORDANCE HIN BUT NOT LIMITED PERSONELS, SAFETY ON THE JOSSITE, GUIDELINGS FOR CONTROLTION SAFETY SHALL BE IN ACCORDANCE HIN BUT NOT LIMITED THE CONTROLTION INCORPTEY ON A AFFETY AND HEAVE THAT SHAMMORD GIVES STROMADIS, AND ANY LOCAL ORGANISMES OR OF
- 2. IN CASE OF CONFLICT BETHEEN THE GENERAL NOTES AND DETAILS, THE MOST RIGID REQUIREMENTS SHALL GOVERN.
- SEE ARCHITECTURAL DRANINGS FOR LOCATIONS OF MASONRY AND DRIVALL NON-LOAD BEARING PARTITIONS, PROVIDE SLIP CONNECTIONS THAT ALLON VERTICAL MOVEMENT THE HEADS OF ALL SUCH PARTITIONS, CONNECTIONS SHALL BE DESIGNED TO SUPPORT THE TOP OF THE HALL'S LATERALLY FOR THE CODE—BEGINED LOAD.
- . ALL COSTS OF INVESTIGATION AND/OR REDESIGN DUE TO THE CONTRACTOR IMPROPER INSTALLATION OF STRUCTURAL ELEMENTS OR OTHER LITEMS NOT IN CONFORMANCE WITH THE CONTRACT DOCUMENTS SHALL BE AT THE CONTRACTORS EMPEIGE.
- I. The structural dramings shall be used in conjection with the architectural and mechanical dramings, if there is a discrepancy between dramings, it is the contractors responsibility to notify the architect prior to performing the
- THE CONTRACTOR SHALL VERIFY ALL EXISTING BUILDING INFORMATION SHOWN (DIMENSIONS, BLEVATIONS, ETC.) AND NOTIFY THE ARCHITECT OF ANY DISCREPANCIES PRIOR TO FARRICATION OF ANY STRUCTURAL COMPONENT, FAILURE TO NOTIFY ARCHITECT OF MRATISPACTORY CONDITIONS.
- IF THE EXISTING FIELD CONDITIONS DO NOT FERRAL THE INSTALLATION OF THE MORK IN ACCORDANCE WITH THE DETAILS SHOWN THE CONDITION WITH THE MACHINET AND PROVIDE A METERIC OF THE CONDITION HITH HIS PROPRIED FOR THE CONDITION HITH HIS PROVIDED AND PROVIDED FOR THE CONDITION HE RESERVED AND PROPRIED FOR WITH LOCATION HE RESERVED AND PROPRIED FOR WITH LOCATION HE RESERVED AND PROPRIED FOR WITH LOCATION HE RESERVED AND PROPRIED FOR THE PROPRIED FOR THE PROPRIED FOR WITH LOCATION HE RESERVED AND PROPRIED FOR THE PROPRIED
- SHOP DRAWNES FOR ALL STRUCTURAL PATERIALS TO BE SUBMITTED TO ARCHITECT FOR REVIEW PRIOR TO THE START OF PAGENCA FOR ON TO A CONTROL OF LOOK, REVIEW PRIOR DWILL BE A MINIMAL OF THE (2) RESES, REPRODUCTION OF ANY PORTION AND A MINIMAL OF REPROSECTION OF ANY PARTICLE AND A MINIMAL OF REJECTION AND REPROSECTION OF RESIDENTIAL AS SOFT DRAWNINGS IN ROPHORISTICS, SHOP DRAWNINGS IN PROMISED SHOP DRAWNINGS IN PROMISED. SHOP DRAWNINGS IN PROMISED SHOP DRAWNING IN PROMISED SHOP DRAWNING IN PROMISED.
- SHOP DRAMINGS SHALL BEAR THE CONTRACTOR'S STAMP OF APPROVAL HIRCH SHALL CONSTITUTE CERTIFICATION THAT THE CONTRACTOR MAS VERNIED ALL CONSTRUCTION CRITERIA MATERIALS, AND SHILLAR DATA AND MAS CHECKED EACH DRAMING FOR COMPLETIESS, COORDINATION, AND COPPLANCE WITH THE CONTRACT DOLUMENTS.
- 10. THE CONTRACTOR SHALL COORDINATE PRINCIPAL OPENINGS IN THE STRUCTURE AS INDICATED ON THE CONTRACT DOCUMENTS, REFER TO THE ARCHITECTURAL, MECHANICAL, ELECTRICAL, AND PLUMENTS DRAWNINGS FOR SLEWES, QUEEN, INSETS, ETC. NOT INDICATED. THE LOCATION OF SLEWES OR OPENINGS IN STRUCTURAL IMPRIESS SHALL BY APPROVED ON THE STRUCTURAL INDICATED.
- 12. THE CONTRACTOR SHALL PROVIDE BRACING AS REQUIRED TO MAINTAIN PLIMBNESS AND STABILITY DURING CONSTRUCTION, CONTRACTOR SHALL PROVIDE SHORING TO MAINTAIN THE STRUCTURAL INTEGRITY OF THE EXISTING STRUCTURE.
- 13. THE SLAB-ON-GRADE SHALL BE UNDERLAIN BY A MINIMUM OF SIX INCHES OF STABLE GRANUAR MATERIAL
- 4. THE SUBGRADE AND EACH LAYER OF FILL OR BACKFILL SHALL BE COMPACTED TO A DRY DENSITY AT LEAST EQUAL TO 45% OF THE MAXIMUM DRY DENSITY ATTAINED BY THE MODIFIED PROCTOR TEST ASTM DISST.
- METHODS, PROCEDURES AND THE SEQUENCES (OTHER THAN THAT NOTED ON THE DRAWINGS) OF CONSTRUCTION ARE THE RESPONSIBILITY OF THE CONTRACTOR. THE CONTRACTOR SHALL TAKE ALL NECESSARY PRECAUTION TO HANTANI AND INSIDE INTEGRITY OF THE STRECTURE A'LL STACES OF CONSTRUCTION AND COORDINATION OF FORCE HAT NECESSARY, AND SELECTRUCAL MORK.
- 16. MORK NOT INDICATED ON A PART OF THE DRAWINGS BUT REASONABLY IMPLIED TO BE SIMILAR TO THAT SHOWN AT CORRESPONDING PLACES SHALL BE PROVIDED BY THE CONTRACTOR AT NO ADDITIONAL COST.
- 17. MINOR DETAILS OR INCIDENTAL ITEMS NOT SHOWN OR SPECIFIED, BUT NECESSARY FOR A PROPER AND COMPLETE INSTALLATION SHALL BE INCLUDED AS REQUIRED.
- 18. MISCELLANEOUS HOOD OR COLD FORMED STEEL BLOCKING, FRAMING MEMBERS, ANCHORS, FASTENERS, ETC.. SHALL BE PROVIDED AS REQUIRED INVESTMEN OR NOT SPECIFICALLY INDICATED ON DRAWINGS.

- FOUNDATIONS HAVE BEEN DESIGNED AND FOOTING ELEVATIONS ESTABLISHED ON THE BASIS IN OF LOCAL MINIMUM CODE REQUIREMENTS AND RECOMMENDATIONS FOR THE COMMON SOIL TYPE BY CONTINUED IN THIS AREA.
- THE FOUNDATION FOR THE STRUCTURE HAS BEEN DESIGNED FOR THE FOLLOWING ALLOWABLE SOIL BEARING PRESGURES AT A BEARING DEPTH OF APPROXIMATELY 36" BELOW FINISHED FLOOR.
- THE POOTING LEVEL SHALL BE TESTED USING DROP-BAR PERCUSSION TEST OR PENETROMETER TO A DEPTH OF 3 OR 4 FEET BELOW BEARING LEVELS TO ENSURE ADECLINE BEARING MATERIALS COMPLY NETH BORING LOGG AND DESIGN CRITERIA.
- THE BOTTOM OF EXTERIOR FOOTINGS SHALL BE A MINIMUM OF THREE (3) FEET BELOW FINISHED GRADE, OR AS REQUIRED BY LOCAL BILLDING CODES.
- EXCAVATION SHALL BE PERFORMED SO AS NOT TO DISTURB EXISTING ADJACENT BUILDINGS, STREETS, AND UTILITY LINES. VERIFY
 LOCATION OF ALL UTILITIES PRIOR TO COMMENCEMENT OF MORK, HAND EXCAVATE AROUND UTILITIES AS REQUIRED.
- REMOVE EXISTING VEGETATION, TOPSOIL, AND UNSATISFACTORY SOILS MATERIALS, PROOF ROLL SUBSPACE TO COSTAIN UNFORFLY
 DESIGNED SUBSTRATA PRIOR TO PLACING FILL MATERIAL EVENLY IN 8" THICK (MAXIMM) LAYERS AND COMPACTING TO REQUIRED
 DESIGNED.
- . The omen sull retain the services of a professional beotechnical disheer, select to the approval of the approval of the select beautiful to their deather levels and deather levels are deather levels. And deather levels deather l
- IF CONDITIONS PROVE TO BE INACCEPTABLE AT THE BEARING BLEVATIONS SHOWN THE POOTING BEARING ELEVATIONS MAY RED TO SHOW THE PROPERTY OF THE PROPERTY OF THE BEARING BLEVATIONS WERE ELEVATIONS AND BLACFUL. BECOMES AND ADDRESS OF THE SHEW THE SHEWARD IS APPROVED TO THE SECTIONALL, EMPRESE.
- THE CONTRACTOR SHALL DESERVE HATER CONDITIONS AT THE SITE AND TAKE THE NECESSARY PRECAUTIONS TO BEIME THAT THE POURDATION EXCAVATIONS REMAIN DRY DURING CONSTRUCTION, ANY SHEETING OR SHORING REQUIRED FOR DEHATERING SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.

CAST-IN-PLACE CONCRETE

- CONCRETE SHALL BE DESIGNED AND DETAILED IN ACCORDANCE WITH THE BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE (ACI-SIB-14), AND CONSTRUCTED IN ACCORDANCE WITH THE CRS HANNAL OF STANDARD PRACTICE.
- CONCRETE IN THE FOLLOWING AREAS SHALL HAVE NATURAL SAND FIRE AGGREGATE AND NORMAL MEIGHT COARSE AGGREGATES
 CONFORMING TO ASTIT COB. TYPE I PORTLAND CEMENT CONFORMING TO ASTIM CISO, AND SHALL HAVE THE FOLLOWING COMPRESSIVE
 STRENGTH IFO' AT 28 DAY.

AIR ENTRAINMENT 48 TO 68 IN ALL EXPOSED CONCRETE.

HAXIMUM AGGREGATE SIZE SHALL BE 1-1/2" FOR FOOTINGS AND 3/4" FOR HALLS AND SLABS

- THE CONCRETE SUPPLIES SHALL SIGNET HIS DESIGNENCE REVENUE CONFRIENCE WE STREAM HAS BE SUBSTANTIANED BY A SUITABLE PROPRIENCE RECORD OF PTHE REPROSE OF SUBSTANTIANED BY A SUITABLE PROPRIENCE RECORD OF PTHE REPROSE OF SUBSTANTIANED BY A SUITABLE PROPRIENCE OF SUPPLIES AND ASSOCIATION OF SUPPLIES AND ASSOCIATION
- A. FOUNDATIONS 050 B. INTERIOR SLABS 0.47
- CONCRETE SHALL BE NORMAL MEIGHT CONCRETE (144 PCF +) HITH ALL CEMENT CONFORMING TO ASTM CISO, TYPE I. MAXIMUM AGGREGATE SIZE SHALL BE I-I/2* FOR FOOTINGS AND 31/4* FOR WALLS AND \$LABS, CONFORMING TO ASTM C330.

- I. HELDED HIRE FABRIC HIER USED SHALL CONFORM TO ASTM AIDS. FABRIC SHALL BE SUPPLIED IN FLAT SHEETS, FABRIC SHALL BE LAPPED TWO MESSES AT SOLUTE.
- GROUT SHALL BE NONEHRINGABLE GROUT CONFORMING TO ASTIM CO27, AND SHALL HAVE SPECIFIED COMPRESSIVE STRENGTH AT 20 DAYS OF 5000 PSI, PREGROUTING OF BASE PLATES WILL NOT BE PERMITTED.
- MINIMAL CONCRETE COVER PROTECTION FOR REINFORCEMENT BARS SHALL BE AS FOLLOWS. (SEE ACI 318-14 SECTION 2016 FOR CONDITIONS NOT NOTED)
- A. CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH 5". B. CONCRETE EXPOSED TO EARTH OR HEATHER
- DAME AND LARGER
 TO BARS AND SHALER
 C. CONCRETE NOT BORDOOD TO HEATHER PLAY
 III DAME AND SHALER
 FRIHARY REMFORCERENT, TIES, STIRRIES, OR SPRALS
 1-12
- O. ALL REINFORCEMENT SHALL BE SECURELY HELD IN PLACE HHILE PLACING CONCRETE. IF REGURED, ADDITIONAL BARS, STIRRUPS OR CHAIRS SHALL BE PROVIDED BY THE CONTRACTOR TO PURNISH SUPPORT FOR ALL BARS.
- II. PLACING OF CONCRETE SHALL NOT START UNTIL THE PLACEMENT OF REINFORCING HAS BEEN APPROVED BY THE INSPECTION AGENCY.
- 2. BONDING AGENT SHALL BE USED WHERE NEW CONCRETE IS PLACED AGAINST EXISTING CONCRETE. 5. PREPARE CONCRETE TEST CYLINDERS FROM EACH DAY'S POUR, CYLINDERS SHALL BE PROPERLY CURED AND STORED. SAMPLE FRESH CONCRETE IN ACCORDANCE WITH ASTM CITY
- 4. RETAIN LABORATORY TO PROVIDE TESTING SERVICE. SLIMP PER ASTM CI432, AIR CONTENT PER ASTM C231 OR CI73, CYLINDER TESTS PER ASTM C31 AID C32, ORE SET OF SIX (6) CYLINDERS FOR EACH 50 CUBIC YARDS FOR EACH MIX USED, REPORTS OF ALL TESTS TO BE SUPPLITTED TO THE ARCHITECT.
- 15. MIXING, TRANSPORTING AND PLACING OF CONCRETE SHALL CONFORM TO ACI 301-16.
- MELDING OF REINFORCEMENT BARS, MICH APPROVED BY THE STRUCTURAL ENGINEER, SHALL CONFORM TO THE AMERICAN MELDING SOCIETY STANDARD DIL-15 AND DIL4-16. ELECTRODES FOR SHOP AND FIELD MELDING OF REINFORCEMENT BARS SHALL CONFORM TO ASTM A235 (J.4.86 FORCE).
- HORIZONTAL JOINTING HILL NOT BE PERHITTED IN CONCRETE CONSTRUCTION EXCEPT AS SHOWN ON THE CONTRACT DOCUMENT. VERTICAL JOINTS SHALL OCCUR AT CENTER OF SPANS AT LOCATIONS APPROVED BY THE STRUCTURAL ENGINEER.
- 6. REPAIR CONCRETE ENGINES VOIGS DE TO SHAF THES, YESPETCOMES: ROCK PROCEETS, AND BANS, SMALLS OR OTHERWESE DANAGED SHEPACES HIND DET PACK OR COEPTI (ABOR), AND PRISH TUBLY HIND A COMMISE SERVICES. AT THE ENGERTION OF THE STRUCTURAL ENGINEET OR AS GUALIFIED BY LAST TESTS, EXCESSIVE INSTRUCTORS, OR ENGINEER PRINCEPORT THAT LIGORARDIZE THE DESIGN SHALL BE REVOYED AND REPLACED AT THE ENGINEER OF THE CONTRACTORS.
- 4. ALL EXPOSED CORNERS SHALL BE CHAPTERED 5/4" UNLESS OTHERWISE INDICATED.
- 20. CONTRACTOR SHALL TAKE EVERY PRECAUTION TO PROTECT FINISHED SUPFACES FROM STAIRS OR ABRASIONS, NO FIRE SHALL BE ALLOWED IN DIRECT CONTACT HITH CONCRETE, PROVIDE ADEQUATE PROTECTION AGAINST INLIRIODS ACTION BY SAN OR HIND, FRESH CONCRETE SHALL BET THOROUGHLY PROTECTED FROM HEAVY RAIN FLOWER HATER AND HECHMICAL INLIRI
- 22. SLIMP TESTS SHALL BE MADE PRIOR TO THE ADDITION OF PLASTICIZERS, CONCRETE FOR THE PREPARATION OF TEST CYLINDERS SHALL BE TAXEN FROM THE MOSE BID FOR CONCRETE PLACED BY PAIMP.
- 23. MATER SHALL NOT ER ADDED TO THE CONCRETE AT THE JODNITE. ITS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE THE REQUIREMENTS OF THE CONCRETE SHALL READ MY PHYPER TO DESIGNE PHYPER AND THROUGH THE PHYPER AND THE CONTRACTOR SHALL EX AT THE CONTRACTOR SHALLEST TO THE APPROAD OF THE STRUCTURES UNDESIGNED AND THE CONTRACTOR SHALLEST TO THE APPROAD OF THE STRUCTURES UNDESIGNED AND THE CONTRACTOR SHALLEST TO THE APPROAD OF THE STRUCTURES UNDESIGNED AND THE CONTRACTOR SHALLEST TO THE APPROAD OF THE STRUCTURES UNDESIGNED FOR THE CONTRACTOR SHALL SHALL NOT BE PERSONALLY AND OTHER ADDITIVES. USE OF CALCIUM E CHAORIDE OR OTHER CHAORIDE BRAINS SHALL SHALL NOT BE PERSONALLY SHALL SHALL NOT BE PERSONALLY SHALL SHAL
- 24. PLACE CONCRETE IN A MANNER SO AS TO PREVENT SEGREGATION OF THE MIX. DELAY FLOATING AND TROVELING OPERATIONS WITH.
 THE CONCRETE MAS LOST SURFACE MATER SHEEN OR ALL PREE SLAB SURFACE. FINISHING OF SLAB SURFACES SHALL COMPLY WITH ACI
 RECOMPREDATIONS 5021R-15 AND SORFACE.
- 25. PROVIDE 1 DAY CURING IMMEDIATELY AFTER FINISHING USING ONE OF THE FOLLOWING METHODS:
- 27. REPER TO THE MANUFACTURER'S SPECIFICATIONS FOR REQUIREMENTS, PROTECT THE CONCRETE SURFACE BETWEEN FINISHING OPERATIONS ON HOT, DRY DAYS OR ANY THE PLASTIC SHRINKASHE CRACKS DEVELOP USING HET BURLAP, PLASTIC MEMBRANES OR FORSHIN, PORTECT CONCRETE DECK AT ALL TIMES PROM RAIN HALL OR OTHER ILLIBURG SHPECTS.
- 28. SLABS SHALL BE REINFORCED MTH MELDED MIRE FABRIC AT -1" FROM TOP OF SLAB. THE MELDED MIRE FABRIC SHALL BE SECURELY HELD IN PLACE MTM ADDITIONAL BARS STRREPS OR CHAIRS.
- 24. PROVIDE POUR STOP MATERIAL HIERE NOT INDICATED ON PLAN AS REQUIRED TO COMPLETE JOB.
- 80. NOT HEATHER CONCRETING, INEN CONCRETING IS TO BE DONE IN NOT HEATHER CONDITIONS THAT COULD ADVERSELY AFFECT THE PROPERTIES AND SERVICEABILITY OF CONCRETE, REPARATIONS AND PROCEDURES CUTLINED IN ACI 3058-05 SHOULD BE FOLLOWED INLESS OFFERINGE NOTED IN CONSTRUCTION SPECIFICATIONS.
- N. COLD MEATHER CONCRETING IMEN CONCRETING IS TO BE DONE IN COLD MEATHER CONDITIONS THAT COULD ADVERSELY AFFECT THE PROPERTIES AND SERVICEABILITY OF CONCRETE, PREPARATIONS AND PROCEDURES OUTLINED IN ACI SOOK-OS SHOULD BE FOLLOWED.

STRUCTURAL STEEL

- FABRICATION AND ERECTION OF STRUCTURAL STEEL SHALL COMFORM TO THE STEEL CONSTRUCTION MANUAL!, FIFTEENIM EDITION, AMERICAN INSTITUTE OF STEEL CONSTRUCTION MICLIONES THE 2018 FESCIPICATION FOR STRUCTURAL STEEL BUILDINGS, THE 2018 KCSC SPECIFICATION FOR STRUCTURAL JOSEPH STRUCTURAL STRUCTURAL JOSEPH STRUCTURAL STRUCTURAL JOSEPH STRUCTURAL STRUCTURAL JOSEPH STRUCTURAL STRUCTU
- ASTM APPZ OR AST2, GRADE 50.
- 2. HIDE FLANGE SHAPES: ASTM ARR2 OR AST2, GRA
 3. STRUCTURAL SHAPES I PLATES: ASTM A36, AST2 OR ARR2.
- 4. STEEL PIPE ASTM ASS, GRADE B.
- 6. ANCHOR RODS SHALL CONFORM TO ASTM F1954, GRADE 95, OR ASTM ABOT UNLESS NOTED OTHERWISE.
- CONSCITOR BOATS FOR STRUCTURAL STIEL HENDERS SHALL HEET OR BUCKED THE REGISTERNIS OF ASTM AZZS BOATS SHALL BE CONSCITOR BOATS FOR STRUCTURAL STIEL HENDERS SHALL HEET OR BUCKED THE REGISTERNIS OF ASTM AZZS BOATS SHALL BE HELD THE "SHAD THE SHAD BOATS AND THE ADD IN THE AND STRUCTURAL CONTROL BERN AND THE ADD OF AND HELD THE SHAD BEACHES CONTROL HENDERS OF THE INSTITUTION OF SHALL ADMITS BRIEF AND THE ADD OF ADD ADMITS BOATS AND SHALL BE REFINED BY THE INSTITUTION OF SHALL INTO ON SHALL INTILE LOAD BOATS FOR THE BOATS AND SHALL BE REFINED BY THE INSTITUTION OF SHALL INTILE LOAD BOATS FOR THE BOATS AND SHALL BE REFINED BY THE REFINED BY THE REFINED OF SHALL INTILE LOAD BOATS FOR THE BOATS AND SHALL BE REFINED BY THE REFINED BY THE
- TO PER APPRIAD TO BE RESPONDED FOR THE SELECTION DESIGN AND DETAILED OF ALL CONNECTIONS NOT TRALLY DETAILED IN THE PER APPRIAD TO BE RESPONDED FOR THE PER APPRIAD THE SELECTION THE PER APPRIAD THE PER APPRIAD THE PER APPRIAD THE SELECTION THE PER APPRIAD THE PER APPRIAD
- ALL CONSCITORS SHALL BE SYMMETRICAL ABOUT THE AXIS OF THE MEMBER CONNECTED. PROVIDE ONLY ONE SRADE OF BOLT FOR EACH BOLT DIAMETER TO BE USED IN THE CONNECTIONS, DO NOT MIX SHADE OF BOLTS.
- O. HELDING SHALL, CONFORM TO THE AMERICAN MELDING SOCIETY STANDARD DUHS, 1-60 ELECTRODES FOR SHOP AND FIELD MELDS SHALL CONFORM TO ANS ASI OR ANS ASI CLASS ETOXX, LON HYDROGEN, MINIMAM HELD SIZE SHALL BE 3/16/LALESS NOTED CONFERENCE.
- II. CUTS, HOLES, COPINS, ETC. REQUIRED FOR OTHER TRADES OR FIELD CONDITIONS SHALL BE SHOPN ON THE SHOP DRAHINSS AND MADE IN THE SHOP, CUTTING OR BURNING OF MAIN STRUCTURAL MEMBERS IN THE FIELD HILL NOT BE PERMITTED.
- 2. STEBL MEMBERS SHOWN ON PLAN SHALL BE EQUALLY SPACED UNLESS NOTED OTHERWISE
- 19. THE GENERAL CONTRACTOR AND STEEL ERECTOR SHALL NOTIFY THE STRUCTURAL ENGINEER OF ANY FABRICATION OR ERECTION ERRORS OR DEVIATIONS AND RECEIVE NOTITEN APPROVAL BEFORE ANY FIELD CORRECTIONS ARE MADE
- 14. WELDING TO THE EXISTING STEEL HILL NOT BE ALLOHED AND THE CONTRACTOR SHALL ANTICIPATE USING FIELD BOLTED CONNECTIONS TO THE EXISTING STEEL.
- 15. ALL STEEL SHALL BE PARTED WITH SHOP STANDARD PRIMER UNLESS NOTED OTHER
- 6. STEEL ANSLES AND PLATES ALONS WITH BOLTS AND HASPERS, IN DIRECT CONTACT WITH EXTERIOR FINISH MASONRY, AND ALL EXTERIOR EXPOSED STRUCTURAL STEEL, SHALL BE PARITED WITH INORGANIC ZINC PRIMER EQUIVALENT TO SOUTHERN CONTINGS CHEMITE, AND STRUCTURAL STEEL, SHALL BE PARITED WITH INORGANIC ZINC PRIMER EQUIVALENT TO SOUTHERN CONTINGS
- 17. SPLICING OF STRUCTURAL STEEL MEMBERS INSERS NOT DETAILED ON THE CONTRACT DOCUMENTS IS PROHIBITED MITHOUT PRIOR PRINTED APPROVAL OF THE STRUCTURAL ENGINEER AS TO LOCATION TYPE OF SPLICE AND CONNECTION TO BE MADE.
- IB, BEAMS SHALL BE CAMBERED IPWARD INVERE SHOWN ON THE CONTRACT DOCUMENTS, WHERE NO UPWARD CAMBER IS INDICATED, ANY MILL CAMBER SHALL BE DETAILED UPWARD IN THE BEAMS, CAMBER INDICATED ON PLAN IS AFTER FINAL ERECTION INCLUDING MILL TO BEAMSER SHALL BE DETAILED UPWARD IN THE BEAMS, CAMBER INDICATED ON PLAN IS AFTER FINAL ERECTION INCLUDING MILL
- M. PROVIDE LODGE OR HANGING LINTELS NOT SHOWN ON DRAWINGS AS REQUIRED TO COMPLETE JOB, COORDINATE WITH ARCHITECTURA AND STRUCTURAL DRAWINGS, CONTACT STRUCTURAL DISINEER AS PER ANY DESIGN INFORMATION REQUIRED, FIELD WILD ALL AD LISTABLE LINTEL, COMPACTIONS AFTER FINAL ALL INSPIRIT.
- 20. FIELD HELDED SURFACES HITHIN FOUR (4) INCHES OF HELD SHALL BE CLEAVED AND GROUND SMOOTH. AFTER HELDING COAT THE EMPOSED AREA HITH APPROPRIATE PRIMERUPAINTS AS SPECIFIED.
- 21. IF STEEL IS GALVANIZED, COAT THE EXPOSED AREA WITH GALVANIZING REPAIR PAINT, GALVANIZING REPAIR PAINT SHALL BE A HIGH ZING DUST CONTENT PAINT COPPLYING WITH PEDERAL SPECIFICATIONS DOD-P-210355A OR 55PC-PAINT-20, COLD GALVANIZING COMPANIED BY THE ORDINATS CO. OR SMALL
- 22. YISBALLY INSPECT ALL FILLET HELDS, IO'S OF ALL FIELD FILLET HELDS IN PRIMARY CONNECTIONS AND MULTI-PASS HELDS SHALL BY TESTED BY THE MAGNETIC PARTICLE METHOD, COMPLYING MITH EICH, PERFORMED ON THE ROOT PASS AND ON THE FINISHED MELD.
- 23. ALL DISSIMILAR METALS SHALL BE TREATED OR PROPERLY SEPARATED TO PREVENT GALVANIC AND/OR CORROSIVE EFFECTS.

MOOD CONSTRUCTION

- DESIGN FABRICATION, AND CONSTRUCTION OF MOOD FRAMING SHALL COMPLY WITH THE "THE NATIONAL DESIGN SPECIFICATION OF MOOD CONSTRUCTION" 2018 (WITH 2018 SUPPLEMENT), NATIONAL FOREST AND PAPER ASSOCIATION.
- KEEP STRUCTURAL THESER PROTECTED DURING DELIVERY, STORAGE, HANDLING AND ERECTION, DO NOT STORE IN AREAS EITHER EXCESSIVELY HIGH OR EXCESSIVELY LOSI NAMIDITY.
- 3. COMPLY WITH GRADING RILES OF GRADING AGENCY FOR SPECIES OF TIMBER USED
- SPIB SOUTHERN PINE INSPECTION BUREAU HCLIB HEST COAST LUMBER INSPECTION BUREAU HSPA HESTERN HOOD PRODUCTS ASSOCIATION
- ALL GRADES OF THEER MUST PULFILL THESE REQUIREMENTS FOR SPECIES, STRESS RATINGS, MOISTURE CONTENT AND OTHER PROVISIONS AS SHOWN AND SPECIFIED.
- MINIMAM STREES RATING, EXCEPT HYERE INDICATED AS NON-STRESS RATED, PROVIDE THESE WHICH HAS BEEN EITHER GRADED OR TESTED AND CERTIFIED HITH ALLOWARLE STRESS RATINGS BASED ON DOUGLAS FIR-LARCH F2 (PSI) OF, Fb = 900, F1 = 515, Fc = 1950 FC FERRENGULLAR + 625 F = 180, and E = 1,600,200.
- MOISTURE CONTENT: EXCEPT AS OTHERWISE INDICATED, PROVIDE TIMBER DRIED TO MAXIMUM MOISTURE CONTENT OF 19th, AND INCLIDE "S-DRY" OR SHILLAR INDICATION IN GRADE MARKING OR CERTIFICATION OF GRADE.
- 1. DRESSING: PROVIDE TIMBER WHICH HAS BEEN DRESSED ON 4 SIDES (S45) AT MILL. PRIOR TO GRADING, COMPLY WITH GRADE SUPE. PSL (PARALLAM) SHALL BE OF MIDTH AND DEPTH AS SPECIFIED ON DRAMINGS, MULTIPLE PLY MEMBERS SHALL BE ASSOMBLED IN ACCORDANCE MITH THE MANUFACTURERS ASSOMBLY DETAILS, THE FOLLOWING MINIMUM STRUCTURAL PROPERTIES SHALL APPLY.
- Pb = 2,000 PSI FOR 12" DEPTH FOR OTHER HULTIPLY BY (12/d)O.III FV = 240 PSI FV" + 650 PSI E = 2,000,000 PSI
- LVI. (LAMINATED VENEER LIMBER) SHALL BE OF HIDTH AND DEPTH AS SPECIFIED ON DRAHBUS, HILTIPLE PLY MEMBERS SHALL BE ASSEMBLED IN ACCORDANCE HITH THE MANUFACTURERS ASSEMBLY DETAILS OR AS NOTED ON THE DRAHBUS, THE FOLLOWING MINIMUM STRUCTURAL PROPERTIES SHALL APPLY.

BASED DESIGN VALUES FOR MOOD STUD AND BRACING SHALL BE DOUG-FIR OR DOUG FIR STUD GRADE OR BETTER. THE FOLLOWING MINIMUM STRUCTURAL PROPERTIES SHALL APPLY:

- Pb = 2600 PSI POR 12" DEPTH FOR OTHER MILTIPLY BY (12/d)0/356 Fc = 150 PSI E = 1500,000 PSI
- ALL STRUCTURAL FLOOR FRAMING SHALL BE DOUG-FIR NO 2 OR BETTER. THE FOLLOWING MINIMUM STRUCTURAL PROPERTIES SHALL APPLY.
- Pb = 400 P51 Pv = 180 P51 Pc^ = 625 P51 (PERPENDICULAR TO GRAIN) E = 1800,000 P51



ADDRESS:

P.O. BOX 628 FARMINGDALE, NJ 0772 PHONE: 732.938.2666

FAX: 732.938.2661 CERTIFICATE OF AUTHORIZATION NO. 24GA2812830

PROJECT TITLE:

ALTERATIONS SCHOOL RENOVATIONS & A FOR: JAM R. ALLEN S WILLIAM

INTERIOR


DATE: REVISION: NOTES

DRAWING TITLE: GENERAL


DESIGNED BY:
MDB DRAWN BY: DMD DATE:

11/23/22 SCALE: AS NOTED PROJECT #: PROJECT #: 2182MT 01 DRAWING NUMBER:

S_{0.1}




S1.1



DMD DATE:

11/23/22 SCALE: AS NOTED
PROJECT #: 2182MT 01 DRAWING NUMBER:

S1.2



PROFESSIONAL ENGINEERS ADDRESS: P.O. BOX 628 FARMINGDALE, NJ 07727 PHONE:

732.938.2666

732.938.2661 CERTIFICATE OF AUTHORIZATION NO.

24GA28128300

PROJECT TITLE:

INTERIOR RENOVATIONS & ALTERATIONS WILLIAM R. ALLEN SCHOOL

DATE: REVISION:


DRAWING TITLE:
CEILING

FRAMING PLAN
DESIGNED BY: MDB

DRAWN BY: DATE: 11/23/22 SCALE: AS NOTED

PROJECT #: 2182MT 01 DRAWING NUMBER: S1.3

COORDINATION 11/23/22 ISSUED FOR



INTERIOR RENOVATIONS & ALTERATIONS FOR WILLIAM R. ALLEN SCHOOL COORDINATION 11/23/22 DATE: REVISION: DRAWING TITLE: **DETAILS** DESIGNED BY: DRAWN BY: DMD DATE: 11/23/22 SCALE

AS NOTED

PROJECT #: 2182MT 01 DRAWING NUMBER: S2.1

732.938.2666

24GA28128300

ISSUED FOR

PROJECT GENERAL NOTES

- MOTOR CONTROLLERS, MOTOR STARTERS & DISCONNECTS SHALL BE FURNISHED BY DIVISION 23 AND INSTALLED UNDER DIVISION 26.
- POWER WIRING TO MECHANICAL EQUIPMENT, MOTOR CONTROLLERS AND CONTROL PANELS SHALL BE PROVIDED UNDER DIVISION 26.
- 3. HVAC CONTROL WIRING SHALL BE PROVIDED UNDER DIVISION 23.
- DISCONNECT SWITCHES SHALL BE HEAVY DUTY TYPE WITH LOCKABLE HANDLE. DISCONNECTS FOR ALL ELECTRICALLY DRIVEN HVAC EQUIPMENT SHALL BE FURNISHED BY DIVISION 23 AND INSTALLED BY DIVISION 26.
- 5. STARTERS SHALL BE NEMA COMBINATION MAGNETIC MOTOR STARTERS SIZED PER MOTOR HORSE POWER. COORDINATE MOTOR STARTER TYPE AND FEATURES WITH THE REQUIREMENTS OF THE MECHANICAL EQUIPMENT AND THE CONTROL SYSTEM. PROVIDE OVERLOAD, UNDER VOLTAGE AND PHASE LOSS PROTECTION IN ALL STARTERS. STARTERS FOR MOTORS 50 HORSE POWER AND LARGER SHALL BE REDUCED VOLTAGE TYPE.
- DUCTWORK AND PIPING LAYOUTS ARE SCHEMATIC DIAGRAMS AND ARE INTENDED TO SHOW GENERAL ARRANGEMENT, SIZE AND CAPACITY AND DO NOT INDICATE WHICH PIPE OR DUCT IS ABOVE OR BELOW THE OTHER. ALL OFFSETS ARE NOT NECESSARILY SHOWN, CONTRACTOR SHALL ARRANGE AND COORDINATE THE WORK, FURNISH NECESSARY OFFSETS, VALVES, VENTS, AND FITTINGS TO AVOID CONFLICT WITH OTHER MECHANICAL AND ELECTRICAL SERVICES AND STRUCTURAL AND ARCHITECTURAL ELEMENTS WITHOUT ADDITIONAL COST TO THE OWNER. IF AREAS OF CONFLICT ARE ENCOUNTERED, THE ENGINEER SHALL BE NOTHED AND CONTRACTORS RECOMMENDATIONS SHALL BE SUIBMITED TO THE ENGINEER SHALL BE NOTHED AND CONTRACTORS RECOMMENDATIONS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE WORK HAS BEGUN.
- ENTIRE INSTALLATION SHALL COMPLY WITH ALL LOCAL AND STATE CODES AND OTHER AUTHORITIES
 HAVING JURISDICTION.
- CONTRACTOR SHALL SECURE AND PAY FOR ALL REQUIRED PERMITS AND SHALL ARRANGE ALL REQUIRED INSPECTIONS.
- 9 PROPER FIRE PROTECTION MEASURES, SATISFACTORY TO THE LOCAL FIRE DEPARTMENT SHALL BE TAKEN WHEN WELDING OR CUTTING WITH TORCHES OR ELECTRIC ARC.
- 10. PROVIDE FLEXIBLE CONNECTIONS ON ALL ROTATING EQUIPMENT.
- CONTRACTOR SHALL PROVIDE ALL NECESSARY MISCELLANEOUS STEEL FOR THE SUPPORT OF ALL EQUIPMENT, PIPING, CONDUIT, AND DUCTWORK, SUSPEND FROM SLAB, STEEL, WALL, OR TRUSS
- 12. BALANCE AND CERTIFY ALL AIR SYSTEMS AS PER SPECIFICATIONS.
- 13. CONTRACTOR SHALL COORDINATE HIS WORK WITH THE WORK OF ALL OTHER TRADES AND THE EXISTING FIELD CONDITIONS.
- 14. PROVIDE SHUT OFF VALVES AT ALL BRANCH PIPING CONNECTIONS.
- CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CUTTING AND PATCHING OF SLAB REQUIRED AS A RESULT OF HIS WORK.
- 16. MINIMUM SIZE OF ALL CONDENSATE DRAIN PIPING SHALL BE 3/4". MINIMUM SLOPE SHALL BE 1/8" PER FOOT.
- ALL MECHANICAL CONTROLS (THERMOSTATS, ETC.) SHALL BE FURNISHED AND INSTALLED AS PER BARRIER-FREE SUB-CODE OF THE LOCAL GOVERNING CODE.
- 18. UNLESS OTHER WISE NOTED ON THE DRAWINGS, ALL MECHANICAL EQUIPMENT SHALL BE MOUNTED ON VIBRATION ISOLATORS TO PREVENT THE TRANSMISSION OF SOUND TO THE BUILDING STRUCTURE VIBRATION ISOLATORS SHALL BE IN ACCORDANCE WITH THE SPECIFICATIONS AND ON ACTUAL WEIGHT DISTRIBUTION OF THE EQUIPMENT FURNISHED. DEFLECTIONS SHALL BE AS NOTED ON THE EQUIPMENT SHOP DRAWING SUBMITIALS.
- 19. ALL CONDENSATE DRAIN LINES SHALL COMPLY WITH NSPC.
- CONTRACTOR TO PATCH ALL DISTURBED FINISHES WITH MATERIAL AND ASSEMBLIES TO MATCH EXISTING ADJACENT SURFACES AND FINISHES.
- 21. ALL REMOVED EQUIPMENT, MATERIAL AND DEBRIS SHALL BE LEGALLY DISPOSED OF BY THIS
- 22. CONTRACTOR SHALL ENSURE THAT ALL MECHANICAL DEVICES WILL BE INSTALLED IN A LOCATION WHICH AFFORDS ACCESSIBILITY FOR MAINTENANCE AND REPAIR. COORDINATE INSTALLATION AMONG ALL TRADES TO AVOID INTERFERENCE, AND LOCATE EQUIPMENT TO PROVIDE CLEARANCE OR EXCEED THOSE RECOMMENDED BY THE MANUFACTURER.
- INSTALL ALL DIELECTRIC UNIONS IN A MANNER WHICH MAKE THEM READILY ACCESSIBLE FOR FUTURE REPAIR OR REPLACEMENT.
- 24. CONTRACTOR SHALL VISIT JOB SITE AND VERIFY EXISTING CONDITIONS PRIOR TO SUBMISSION OF BID.
- 25. ALL INTERIOR PIPING SHALL BE SUPPORTED FROM THE STRUCTURE ABOVE.
- 26. ALL CONTROL WIRING SHALL BE INSTALLED IN CONDUIT IF RUN IN MECH ROOM OR OPEN TO DAMAGE. WIRING ABOVE CEILING OR CONCEALED LOCATIONS (SAFE FROM DAMAGE) CAN BE ROUTED AS PLENUM RATED CABLE.
- 27. WHERE PIPING CONNECTIONS FOR THE EQUIPMENT SUCH AS PUMPS, AC UNITS, COILS, ETC. DIFFER FORM THE LINE SIZE, IT SHALL BE THE RESPONSIBILITY OF THE MECHANICAL CONTRACTOR TO FURNISH AND INSTALL THE NECESSARY REDUCERS OR EXPANDER FITTINGS TO ENABLE CONNECTION BETWEEN THE PIPING SYSTEM AND THE EQUIPMENT.
- 28. ALL DRAINAGE PIPING SHALL BE SLOPED AT A MINIMUM OF 1/8" PER FOOT.
- ALL INSULATION PROVIDED FOR THE PROJECT MUST MEET A MAXIMUM FLAME SPREAD RATING OF 25 AND SMOKE DEVELOPED OF 50 OR LESS, AS TESTED IN ACCORDANCE WITH ASTM, NFPA & U.L. GUIDELINES.
- 30. ALL EQUIPMENT FOR THIS PROJECT SHALL BE LISTED BY A NATIONALLY RECOGNIZED TESTING
- 31. CONTRACTOR SHALL SUBMIT DIMENSIONED COORDINATED SHOP DRAWINGS FOR ENGINEERS APPROVAL DRAWING SHALL INDICATE ALL TRADES, (ELECTRICAL, MECHANICAL, PLUMBING, FIRE PROTECTION AND INFRASTRUCTURE).
- 32. THE CONTRACTOR SHALL PROVIDE THE OWNER WITH A ONE (1) YEAR WRITTEN GUARANTEE OF ALL WORK (LABOR AND MATERIALS) STARTING FROM THE DATE OF ISSUANCE OF SUBSTANTIAL COMPLETION.
- 33. UNLESS OTHERWISE SPECIFIED, ALL MOTORS ½ H.P. AND ABOVE SHALL BE 3 PHASE AND MOTORS UNDER ½ H.P. SHALL BE SINGLE PHASE.
- 34. THE MECHANICAL CONTRACTOR SHALL COORDINATE THE ELECTRICAL REQUIREMENTS OF HIS WORK WITH THE GENERAL AND ELECTRICAL CONTRACTORS PRIOR TO SUBMISSION OF BIDS.

GENERAL ABBREVIATIONS

DENTIFIER	DESCRIPTION	IDENTIFIER	DESCRIPTION	IDENTIFIE
AFF	ABOVE FINISHED FLOOR	MC	MECHANICAL CONTRACTOR	HWS
AFG	ABOVE FINISHED GRADE	MCA	MINIMUM CIRCUIT AMPS	
ATC	AUTOMATIC TEMPERATURE CONTROLS	MEZZ	MEZZANINE	→ HWR —
BFG	BELOW FINISHED GRADE	MFG	MANUFACTURER	
BLDG	BUILDING	мн	MOUNTING HEIGHT	12.0
CONN'S	CONNECTIONS	MIN	MINIMUM	
CLG	CEILING	MOD	MOTOR OPERATED DAMPER	v
co	COMPANY	MTD	MOUNTED	•77
CONTR	CONTRACTOR	NC	NORMALLY CLOSED	1 most
CTE	CONNECT TO EXISTING	NIC	NOT IN CONTRACT	
DN	DOWN	NO	NORMALLY OPEN	, ,,,,,
DWG(S)	DRAWING(S)	NTS	NOT TO SCALE	· · · · · · · ·
EC	ELECTRICAL CONTRACTOR	OC	ON CENTER	٠ ٩
EM	EMERGENCY	PC	PLUMBING CONTRACTOR	,
EQUIP	EQUIPMENT	PSI	POUNDS PER SQUARE INCH	, 4
ETR	EXISTING TO REMAIN	PVC	POLYVINYL CHLORIDE	× × ·
EWC	ELECTRIC WATER COOLER	R	EXISTING EQUIPMENT TO BE REMOVED	- 74
EX	EXISTING	RL	EXISTING EQUIPMENT TO BE RELOCATED	
FLA	FULL LOAD AMPS	RLA	RUNNING LOAD AMPS	, φ
FS	FLOW SWITCH	RPM	REVOLUTIONS PER MINUTE	^^
GC	GENERAL CONTRACTOR	SDD	DUCT SMOKE DETECTOR	<u>, Υ</u>
HP	HORSEPOWER	SQ. FT.	SQUARE FEET	——
MAX	MAXIMUM	TYP	TYPICAL	
		VSD	VARIABLE SPEED DRIVE	,
				<u> </u>
HOTE THE NO	T ALL ABBREVIATIONS APPLY TO THE PROJECT	NOTE THAT N	NOT ALL ABBREVIATIONS APPLY TO THE PROJECT	

MECHANICAL ABBREVIATIONS

CFM	CUBIC FEET PER MINUTE	R/A	RETURN AIR
CR	CEILING REGISTER	RAV	RELIEF AIR VENT
CU	CONDENSING UNIT	RG	RETURN GRILLE
CW	COLD WATER	RH	RELATIVE HUMIDITY
DB	DRY BULB	RR	RETURN REGISTER
DN	DOWN	S/A	SUPPLY AIR
E/A	EXHAUST AIR	SD	SMOKE DAMPER
EAT	ENTERING AIR TEMPERATURE	SE	SMOKE EXHAUST
EDB	ENTERING DRY BULB	SF	SUPPLY FAN
EER	ENERGY EFFICIENCY RATIO	SR	SUPPLY REGISTER
EG	EXHAUST GRILLE	T	THERMOSTAT
EH	ELECTRIC HEATER	TG	TRANSFER GRILLE
ESP	EXTERNAL STATIC PRESSURE	TO	TRANSFER OPENING
EMB	ENTERING WET BULB	TR	TOP REGISTER
EF	EXHAUST FAN	π	THERMOSTATIC TRAP
FD	FIRE DAMPER WITH ACCESS DOOR	UH	UNIT HEATER
FPM	FEET PER MINUTE	UV	UNIT VENTILATOR
G	GAS	VD	VOLUME DAMPER
GPM	GALLONS PER MINUTE	WB	WET BULB
нх	HEAT EXCHANGER	w.c.	WATER COLUMN
LAT	LEAVING AIR TEMPERATURE	WG	WATER GAUGE
LPS	LOW PRESSURE STEAM	WMS	WIRE MESH SCREEN
LPC	LOW PRESSURE CONDENSATE	XEF	EXISTING EXHAUST FAN
MAU	MAKE UP AIR UNIT	XB	EXISTING BOILER
MBH	THOUSAND BTU PER HOUR	х	EXISTING
MOD	MOTOR OPERATED DAMPER	XUV	EXISTING UNIT VENT
N.C.	NORMALLY CLOSED	XRAD	EXISTING RADIATOR
N.O.	NORMALLY OPEN	XUV	EXISTING UNIT VENTILATOR
O/A	OUTSIDE AIR	XWAC	EXISTING WINDOW AIR CONDITIONER
OAI	OUTSIDE AIR INTAKE		
OED	OPEN ENDED DUCT		

. NOTE THAT NOT ALL SYMBOLS APPLY TO THE PROJECT

MECHANICAL SYMBOLS

IDENTIFIER

—O—

 \boxtimes

0

₩--

HHHH

____M

--

1

XICEM

44444

压到

医光

DESCRIPTION

REDUCER (ECCENTRIC)

PRESSURE RELIEF VALVE

CONTROL VALVE (2-PORT)

DUCT UNDER POSITIVE PRESSURE

DUCT UNDER NEGATIVE PRESSURE

RETURN OR EXHAUST REGISTER

FIRE DAMPER W/ACCESS DOOR

VALVE ON RISER

ANGLE VALVE

PIPE ANCHOR

ROUND DUCT

SUPPLY REGISTER

VOLUME DAMPER

BACKDRAFT DAMPER

MOTORIZED DAMPER

- AIR DEVICE TYPE

SENSOR

AIRFLOW THRU UNDERCUT

AIRFLOW THRU LOUVERED DOOR

THERMOSTAT (WALL MOUNTED)

DUCTWORK TO BE DEMOLISHED

EXISTING DUCTWORK TO REMAIN

EXISTING SUPPLY DIFFUSER

EXISTING RETURN OR EXHAUST GRILLE

FLEXIBLE CONNECTION

THERMOMETER

DESCRIPTION

CONDENSATE DRAIN

PUMPED CONDENSATI

THERMOMETER W/ SHUT-OFF

UNION

MANUAL AIR VENT

AUTOMATIC AIR VENT

PIPE TURNING UP

PIPE TURNING DOWN

DIRECTION OF FLOW

PITCH DOWN

CAPPED PIPE

BALL VALVE

GATE VALVE

GLOBE VALVE

BUTTERFLY VALVE

EXPANSION JOINT

SWING TYPE CHECK VALVE

CALIBRATED BALANCING VALVE

PRESSURE REGULATOR (LOCK UP TYPE)

REDUCER (CONCENTRIC)

SANITARY SEWER PIPING

SANITARY VENT PIPING

GAS COCK

GAS PIPING

STEAM TRAP

IDENTIFIER

├

— 5 — 7

⊢−β−−

⊢—G—→

---s---

-- - ∨ - - - →

8

GENERAL NOTES

- THE CONTRACTOR SHALL COORDINATE WITH ALL OTHER TRADES FOR POSSIBLE INTERFERENCE WITH HIS WORK AND THE WORK OF OTHERS FROM NEW AND EXISTING CONDITIONS.
- DUCTWORK AND PIPING LAYOUTS ARE DIAGRAMMATIC AND INTEND TO SHOW A GENERAL ARRANGEMENT, SIZE AND CAPACITY, ALL OFFSETS ARE NOT NECESSARILY SHOWN. CONTRACTOR SHALL ARRANGE AND COORDINATE THE WORK, FURNISH NECESSARY OFFSETS, VALVES, VENTS, AND FITTINGS TO AVOID CONFLICT WITH OTHER MECHANICAL AND ELECTRICAL SERVICES AND WITH STRUCTURAL AND ARCHITECTURAL ELEMENTS.
- WHILE ALL ATTEMPTS AT ACCURACY HAVE BEEN TAKEN, NO GUARANTEE OF AN EXACT REPRESENTATION OR COMPLETENESS IS IMPLIED. RESPONSIBILITY FOR FINAL VERIFICATION FALLS TO THE CONTRACTOR, ANY UNRESOLVED DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER FOR RESOLUTION.
- 4. SEE SCHEDULES AND DETAILS FOR ADDITIONAL INFORMATION
- ALL SYSTEMS TO REMAIN THAT ARE DAMAGED DURING DEMOLITION PHASE OF WORK SHALL BE RESTORED TO ORIGINAL CONDITION AT NO ADDITIONAL COST.
- ALL REMOVED MATERIALS AND EQUIPMENT SHALL BE REMOVED FROM THE SITE AND LECALLY DISPOSED OF BY THE CONTRACTOR. OWNER RESERVES THE RIGHT TO RETAIN ANY MATERIAL, WHICH SHALL BE STORED AT HIS DIRECTION.
- IT IS THE INTENT OF THESE DOCUMENTS THAT ALL EXISTING HAAC EQUIPMENT AND SYSTEMS THAT ARE NOT TO BE RE-USED BE DISCONNECTED AND REMOVED IN THEIR ENTIRETY. ALL DUCTYORK, PIPING AND EQUIPMENT, WHICH THE INDICATED ON THESE DRAWINGS OR NOT, SHALL BE REMOVED UNLESS NOTED OTHERWISE, CONTRACTOR SHALL VISIT SITE AND MAKE NOTE OF ALL EXISTING CONDITIONS PRIOR TO SUBMITTING HIS BID.
- ALL PENETRATIONS THROUGH EXISTING CORRIDOR WALLS SHALL BE TREATED AS RATED PENETRATIONS AND SEALED AS PER DETAILS.
- ALL CONTROLLERS AND THERMOSTATS LOCATED IN PUBLIC AREAS SHALL HAVE PLASTIC, LOCKABLE COVERS INSTALLED ON THEM.
- 10. ALL CONTROL WIRING SHALL BE ROUTED CONCEALED, IN ANY CASES WHERE THE WIRING MUST BE ROUTED EXPOSED, PROVIDE AND INSTALL ONE-PIECE NONMETALLIC RACEWAY AND JOINING PIECES TO CONCEAL AND PROTECT WIRING, RACEWAY SHALL BE SIMILAR TO SERIES 2700 AS PRODUCED BY WIREMOLD OR EQUAL.
- 11. PATCH ALL PENETRATIONS FROM REMOVED EQUIPMENT WITH SIMILAR MATERIALS.
 COORDINATE WITH ROOF CONTRACTOR UNDER SEPARATE CONTRACT SO AS NOT TO
 AVOID ANY ROOF WARRANTIES.

HVAC DESIGN CRITERIA

HVAC DESIGN CRITERIA

- 1. APPLICABLE CODES AND REFERENCES:
- AFFICIAGLE COURS AND REFERENCES:

 A. INTERNATIONAL BUILDING CODE 2018 NJ EDITION

 B. ASHRAE / IES STANDARD 90.1 2016

 C. INTERNATIONAL MECHANICAL CODE 2018

 D. INTERNATIONAL FUEL GAS CODE 2018

 E. NATIONAL STANDARD PLUMBING CODE 2018

 F. UNIFORM CONSTRUCTION CODE OF NEW JERSEY

 G. NATIONAL ELECTRIC CODE 2017
- 2. SUMMER OUTDOOR DESIGN CONDITIONS (PER ASHRAE FUNDAMENTALS 2017): A. DRY BULB: 94.3 DEG. F. B. WET BULB: 74.4 DEG. F. *
- ASHRAE 0.4 % COOLING DRY BULB/MEAN WET BULB FOR NEWARK, NEW JERSEY.
- 3. SUMMER INDOOR DESIGN CONDITIONS:
- A. DRY BULB: 75 DEG. F. (+/- 2 DEG. F.)
 B. RELATIVE HUMIDITY: 50%
- 4. WINTER OUTDOOR DESIGN CONDITIONS (PER ASHRAE FUNDAMENTALS 2017): A. DRY BULB: 12.8 DEG. F. *
 *ASHRAE 99.6 % DESIGN DAY DRY BULB FOR NEWARK, NEW JERSEY.
- 5. WINTER INDOOR DESIGN CONDITIONS (FOR SPACES WHERE HEATING PROVIDED): A. DRY BULB: 70 DEG. F. (+/- 2 DEG. F.)

 B. RELATIVE HUMIDITY: NO MINIMUM HUMIDITY CONTROL PROVIDED



CONNOLLY & HICKEY

HISTORICAL

P.O. Box 1726

Cranford, N.1, 07016

973 746-4911



THOMAS B. CONNOLLY, AIA NJ 21A101699200 PA RA403776

MARGARET M. HICKEY, AIR NJ 21AI018244500

PROJECT No.: 2016C

DATE: 08 AUGUST 2022

DRAWN BY : MEMIC CB. PK

JERSEY

N AND REHABILITATION .. ALLEN SCHOOL URLINGTON COUNTY, NEW JER RESTORATION / WILLIAM R. A BURLINGTON, BURL

M0.1

ADDRESS: O. BOX 628 FARMINGDALE, NJ 077. PHONE: 732.938.2666

FAX: 732.938.2521 CERTIFICATE OF AUTHORIZATION NO. 24GA28124300

FOR THE PLATFORM OF SAME PROPERTY A VIOLATION OF THE PROFESSIONAL CODE OF THIS CAND. OF COMPANY ASSETS BOTH OF WHECH SHAP PROSECUTED TO THE FULLEST EXTENT OF CURRENT STATUTES Pard Reports P.E. Professional Engineer State of New Jersey

1 PLAN NORTH


NOTE THAT NOT ALL ABBREVIATIONS APPLY TO THE PROJECT
 NOTE THAT NOT ALL ABBREVIATIONS APPLY TO THE PROJECT


SYMBOL LIST


SYMBOL DESCRIPTION DRAWING # TO LOCATE SECTION DETAIL # ELEVATION TAG DRAWING # TO LOCATE ELEVATION DETAIL # M2 -0 KEY NOTE SYMBOL KEY NOTES APPLYING TO SAME ITEM 02 CONNECT TO EXISTING


© COPYRIGHT 2022 CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC. UNAUTHORIZED REPPODUCTION OF THESE DRAWINGS IS PROHIBITED WITHOUT WRITTEN CONSENT OF THE ARCHITECT


NEW JERSEY PROFESSIONAL ENGINEE












MECHANICAL KITCHEN PLAN - ALTERNATE 01 **MECH** M1.1A 1/4"=1'-0"

KEY NOTES

- DX COOLING FAN COIL WITH ECONOMIZER SUPPORTED FROM STRUCTURE ABOVE WITH VIBRATION ISOLATORS PER MANUFACTURER'S RECOMMENDATIONS IN ATTIC SPACE ABOVE. PROVIDE DRIP PAN BELOW WITH PAN ALARM ROUTE CONDENSATE TO JANTIORS SINK.
- 2. NEW DIRECT VENT GAS DUCT FURNACE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.
- ECONOMIZER RELIEF FAN SUPPORTED FROM STRUCTURE ABOVE WITH VIBRATION ISOLATORS PER MANUFACTURER'S RECOMMENDATIONS.
- BATHROOM EXHAUST FAN SUPPORTED FROM STRUCTURE ABOVE WITH VIBRATION ISOLATORS PER MANUFACTURER'S RECOMMENDATIONS.
- 5. 10X8 EXHAUST DUCT DOWN.
- 6. 40X20 EXHAUST DUCT UP.
- 7. 40X12 OUTDOOR AIR INTAKE DUCT UP.
- AIR COOLED CONDENSER INSTALLED ON EQUIPMENT PAD. ROUTE REFRIGERANT LINES SIZED PER MANUFACTURER'S RECOMMENDATIONS AND CONTROL WIRING IN CONDUIT TO RESPECTIVE INDOOR UNIT.
- 9. NEW TEMPERATURE SENSOR. VERIFY MOUNTING HEIGHT AND LOCATION WITH OWNER.
- 10. FURNACE WITH DX COIL HUNG FROM STRUCTURE ABOVE WITH SPRING ISOLATORS PER MANUFACTURER'S RECOMMENDATIONS. PROVIDE AUXILIARY DRAIN PAN CONDENSATE PUMP AND ROUTE CONDENSATE DRAIN PIPING TO MOP SINK AND SPILL INDIRECTLY. PROVIDE AND INISTALL FILTER ROW WITH FILTERS ON UNIT RETURN OPENING. SEE INSTALLATION DETAILS ON M2.1.
- 11. FURNACE VENT AND COMBUSTION AIR INTAKE SIZED PER MANUFACTURER'S RECOMMENDATIONS UP THROUGH ROOF TERMINATE CONCENTRIC FURNACE VENT PROVIDED BY MANUFACTURER.
- 12. 8X8 INTAKE DUCT UP. CONNECT TO COOK PR12 GRAVITY INTAKE VENTILATOR WITH BIRDSCREEN INSTALLED ON SLOPED CURB ON ROOF ABOVE.



CONNOLLY & HICKEY

HISTORICAL ARCHITECTS, LLC

P.O. Box 1726

Cranford, N.J. 07016 973 746-4911



THOMAS B. CONNOLLY, AIA NJ 21A101699200 PA RA403776

MARGARET M. HICKEY, AIA NJ 21AI018244500

PROJECT No.: 2016C

DATE: 08 AUGUST 2022

REVISIONS:

DRAWN BY: MEXIX CB, PK

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

ADDRESS:

P.O. BOX 628 FARMINGDALE, NJ 07727
PHONE:


732.938.2666 FAX: 732 938 2521


CERTIFICATE OF AUTHORIZATION NO. 24GA28124300 ALL DRAWFIGS AND SHITTIN IMPLEMENT ATTACKS INTERPRETATION OF THE ENCASTITUTE ORIGINAL AND ENGINEER OF THE ENCASE. THE REPREDATE THOSE THE PAPER OF THE DRAWFIGS THE PAPER OF THE CHARGE OF THE PAPER OF

Paul Rijesh, P.E. Professional Engineer State of New Jessey

M1.1A DATE
KSI PROJECT # 2082M_07


NEW JERSEY PROFESSIONAL ENGINEER
LICENSE NUMBER 4518800







- PROVIDE AT FLEXIBLE DUCT CONNECTION A METAL DRAWNBAND ON THE INTERIOR FLEXIBLE DUCT. SECURE THE INSULATION OVER THE DRAW BAND WITH AN ADDITIONAL DRAWBAND.
- PROVIDE MINIMUM 2" COLLARS FOR ATTACHMENT OF THE FLEX DUCT TO ROUND DUCT, DAMPERS AND DIFFUSERS.
- BAND RIGID ROUND DUCT INSULATION TO DUCT AND PROVIDE TAPE FOR INSULATION OVERLAP.


O2 FLEXIBLE DUCT INSTALLATION














- DETAIL SIMILAR FOR ALL INSTALLATIONS, UNLESS OTHERWISE INDICATED. CONTRACTOR TO ADJUST CONFIGURATION TO SUIT FIELD CONDITIONS.
- 2. REFER TO FLOOR PLANS FOR DUCT SIZING. ARE STSTEMS SMALL BE INSTALLED IN STRICT ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS, INCLUDING REFRIGERAIT PIPE SIZING & MAXIMUM RUN VEHT PIPING.
- FLOOR PLANS DO NOT INCLUDE ALL REQUIRED DETAILS OF THIS INSTALLATION.
- 5. MAINTAIN REQUIRED ACCESS FOR MAINTENANCE & CLEARANCE TO COMBUSTIBLES.
- NEOPRENE VIBRATION PAD WITH UNITSTRU-SLEEPERS AS REQUIRED TO ACCOMMODATE CONDENSATE TRAP. FLEXIBLE DUCT CONNECTION.
- PVC A/C CONDENSATE DRAIN.
- 3/4" PVC TO DISCHARGE IN JANITOR'S SINK IN MECHANICAL CLOSET 80 FEET FROM FURTHEST UNIT. MAINTAIN SLOPE OF § PER FOOT.
- 5. REFRIGERANT PIPING TO ASSOCIATED CONDENSING UNIT.
- AUXILLARY DRAIN PAN UNDER UNIT WITH PAN ALARM INTERLOCKED WITH UNIT SHUT DOWN.
- 8. 4" RAISED PLATFORM/HOUSEKEEPING PAD.
- HOT WATER SUPPLY AND RETURN. SEE COIL CONNECTION DETAIL THIS DRAWING

O7 TYPICAL AIR HANDLER INSTALLATION DETAIL
M2.1 N.T.S







ALL DRAWNING AND WITTEN MATERIALS APPLACATION OF THE PROPERTY OF THE AND INFO HE SHID ON OF THE PROPERTY OF THE SHIP OF THE SH

CONNOLLY & HICKEY

HISTORICAL ARCHITECTS, LLC

P.O. Box 1726

973 746-4911

THOMAS B. CONNOLLY, AIA NJ 21AI01699200 PA RA403776


MARGARET M. HICKEY, AIA NJ 21AI018244500

PROJECT No.: 2016C DATE: 08 AUGUST 2022

DRAWN BY: MKMIC CB, PK


REVISIONS:


Cranford, N.J. 07016




GLOBE VALVE-









O3 TYPICAL EXPANSION TANK DETAIL





CHEMICAL POT FEEDER 02 CHE



BOILER PIPING SCHEMATIC
M2.2 NONE



FAX:

732.938.2521
CERTIFICATE OF AUTHORIZATION NO. 24GA28124300

ALL DRAWINGS AND WRITTEN MATERIALS APPEAUS HEREK (NONTITUT) GRIEGAL, AND LOWIR BRIDG MOT THE BENDERS THE HEREGORY CORE OF THE START FOR THE STRONG FOR STRONG OF COPPING THE MORE OF RETNERN SAID DRAWNS GRALL SE COSSIDEDED A VIGATION OF BOTH HER START AT HER FOR COMPANY ASSETS BOTH OF WHICH SILLL SEE PROSECUTED TO THE PLALEST EXTENT OF CURRENT STATUTES Paul Rajush, P.E. Professional Engineer State of New Jersey MEP PROGRESS SET 08/08/2022

DATE
LSI PROJECT # 2082M_97
NEW JERSEY PROFESSIONAL ENGINEE
LICENSE NUMBER 4515800

M2.2

THOMAS B. CONNOLLY, AIA NJ 21A101699200 PA RA403776

MARGARET M. HICKEY, AIA NJ 21AI018244500

PROJECT No.: 2016C DATE: 08 AUGUST 2022

DRAWN BY: MINIC CB, PK

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

		AREA	SUPPLY FAN				COOLING COI	L				HEATING CO	L(REHEAT POSIT	IION)						ELECTRICAL					T	
INIT ID	MODEL	SERVED	SUPPLY CFM	OA CFM	ESP IN. W.G.	MOTOR HP	TOTAL MBH	SENSIBLE MBH	EAT DB/WB	LAT DB/WB	ROWS	TOTAL MBH	EAT DB/WB	LAT DB/WB	EWT	LWT	GPM	WATER PD	ROWS	VOLTS	PHASE	HERT2	MCA	MOP	WEIGHT	NOTES
AHU-1	BCHE072	COMMUNITY RM 1	2000	425	0.5	1.5	72.3	53.75	80/67	55.5/55.4	6	88	55	95	180	152.4	6.38	1.01	1	200	7	60	0.5	16	170	1 TUDOUGU
AHU-2	BCHE072	COMMUNITY RM 2	2000	425	0.5	1.5	69.3	50.08	80/67	57.2/55.9	3	88	55	95	180	152.4	6.38	1.01		200	3	60	9.5	15	430	1 THROUGH
AHU-3	BCHE054	COMMUNITY RM 3	1500	260	0.75	1	48.3	38.03	80/67	56 9/56 8	6	56	60	0.5	100	141.4	0.56	0.70		200	3	60	9.5	15	397	1 THROUGH
AHU-4	BCHE036	KITCHEN/OFFICE	1200	260	0.75	1	37	20.8	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	575/573		45	60	95	180	141.4	2.9	0.39	1	208	3	60	5./5	15	346	1 THROUGH
AUII 5	BCHEOE4	COMMUNITY RM 5		170	0.75	1	- 57	29.0	80/67	57.5/57.3	0	45	60	95	180	137.6	2.12	1.5	1	208	3	60	5.75	15	293	1 THROUGH
A110-3	BCHLU34		1650	170	0.5	1	48.4	40	80/67	57.9/57.8	6	58	62	95	180	140.4	2.93	0.4	1	208	3	60	5.75	15	346	1 THROUGH
AHU-6	BCHE036	COMMUNITY RM 4	1200	170	0.5	1	36.9	29.7	80/67	57.5/57.3	6	46.2	60	95	180	140.4	233	1 70		200	7	60	E 75	15	207	1 1111100011
AHU-7	BCHE036	CORRIDOR	1100	100	0.75	1	33.6	25.8	80/67	58.7/57.4	3	40	63	95	180	130.7	1.6	0.0		200	3	60	5.75	15	293	1 THROUGH

SELECTION BASED ON TRANE.

2. COOLING PERFORMANCE AT 95F OUTDOOR AIR TEMP 3. COMBINATION STARTER/DISCONNECT

4. MERV 13 FITLERS
5. WIRELESS DISPLAY SENSOR WITH UNIT MOUNTED RECIEVER

5. WIRELESS DISPLAY SENSOR WITH UNIT MOUNTED RECIEVER

6. FACTORY MOUNTED CONTROLLER WITH FAN STATUS, CONDENSATE OVERFLOW

LOW LIMIT, OUTSIDE AIR, AND DISCHARGE AIR SENSOR, AHU-1&AHU-2 TO HAVE ECONOMIZER CONTROLLER WITH DUAL ENTHALPY.

5. DEHUMIDIFICATION WITH LOCAL HUMIDITY SENSOR
6. DELUXE PIPING PACKAGE INCLUDES SHUT OFF BALL VALVE, STRAINER, CIRUIT SETTER CIRCUIT SETTER TWO WAY CONTROL VALVE AND BALANCING FITTING ON BYPASS

Unit	Nominal	Model	Matched	Cooli	ng Perform	ance		Electrical Data			Net	NOTES
No.	Cooling Cap (Tons)		Indoor Unit	Outdoor D.B (°F)	Total (MBH)	Sensible (MBH)	DX Cooling Efficiency EER/SEER	Voltage	MCA	MOCP	Wt (lbs)	
CU-1	6	TTA07243	AHU-1	95	72.3	53.75	11.5	208/230-3-60	27	45	241	1,2,3,
CU-2	6	TTA07243	AHU-1	95	69.3	50.08	11.5	208/230-3-60	27	45	241	1,2,3,
CU-3	4	4TTA7048	AHU-3	95	48.3	38.03	17	208/230-3-60	18	30	248	1,2,3
CU-4	3	4TTA7036	AHU-4	95	37	29.8	17	208/230-3-60	15	25	245	1,2,3
CU-5	4	4TTR7048	AHU-5	95	48.4	40	17	208/230-3-60	18	30	248	1,2,3
CU-6	3	4TTR7036	AHU-6	95	36.9	29.7	17	208/230-3-60	15	25	245	1.2.3
CU-7	3	4TTA7036	AHU-7	95	33.6	25.8	17	208/230-3-60	15	25	245	1,2,3
	1. S 2. P 3. H	IOTES: IELECTIONS BASED ON FOOWER DISCONNECT SWITHALLGUARD OWERED CONVIENCE OU	ГСН	TURED BY TRANS	Ē.							

UNIT ID	MODEL NUMBER	TYPE	INTERLOCKED WITH	CFM	ESP	DRIVE	MOTOR	WEIGHT	ELECTRICAL			NOTES
					IN, W.G.		HP	LBS	VOLTS	PHASE	HERTZ	
EF-1	135SQN17DEC	INLINE	AHU-1	2,000	0.5	DIRECT	3/4	76	115	1	60	
EF-2	135SQN17DEC -	INLINE	AHU-2	2,000	0.5	DIRECT	3/4	76	115	1	60	
EF-3	70SQN-B	INLINE	AHU-3	260	0.75	BELT	1/4	100	208	3	60	+
EF-4	70SQN-B	INLINE	AHU-3	260	0.75	BELT	1/4	100	208	3	60	

NOTES:

1. SELECTION BASED ON LOREN COOK OR APPROVED EQUAL.
2. PROVIDE DISCONNECT
3. MOTOR OPERATED DAMPER

NO.	MANUFACTURER	MODEL	MBH	OUTPUT MBH	FLUE SIZE (")	EFFIECIENCY (%)	WEIGHT (LBS)	NOTES
B-1	TRIANGLE TUBE	SOLO 250	65-245	240	3	95	142	1 THRU
B-2	TRIANGLE TUBE	SOLO 250	65-245	240	3	95	142	1 THRU
2. S 3. 3	ULL MODULATION FROM 25% TAINLESS STEEL HEAT EXCHA O PSI PRESSURE RELIEF VAL UTOMATIC AIR VENT	NIGER & BURNER			3. 10 YEAR			

5. PRESSURE GUAGE 6. CONDENSATE DRAIN ASSEMBLY

120V POWER SWITCH
 BOILER TO BE COMPLETE WITH GRAPHIC INTERFACE CONNTROLLER WITH OUTDOOR RESET PRESET CURVES AND CIRCULATOR CONTROL

NTC TEMPERATURE SENSORS ON THE
BOILER SUPPLY/RETURN AND FLUE
120V POWER SWITCH

HOT WAT	ER UNIT HEAT	ER SCHEDULE	(UH &	CUH)							
UNIT ID	LOCATION	MODEL NUMBER	CFM	GPM	MBH	PD	HP	VOLTS	PH	AMPS	NOTES
UH-1-10	BASEMENT	UH\$-18	395	1.3	10	0.01	16 W	115	1	1	1,2,3,4
CUH-1	VESTIBULE 002	FFEB02	200	1.9	20	4	1/8	115	1	2.7	1,2,3,4
CUH-2	VESTIBULE 109	FFBB02	200	1.0	20	2	1/8	115	1	2.2	1,2,3,4

NOTES:

1 SELECTION BASED ON TRANE
2. PROVIDE THERMOSTAT.
3. PIPING PACKAGE W/ 2-WAY CONTROL VALVE
4. PROVIDE DISCONNECT SWITCH AND MOTOR STATER

						HEAD	PUMP	MOTOR	ELECTRICAL			
INIT ID	MODEL NUMBER	TYPE	LOCATION	SERVICE	GPM	FT.	RPM	W/HP	VOLTS	PHASE	HERTZ	NOTES
2P-1	ASTRO 210	IN-LINE CIRCULATOR	MECH RM	B-1	20	12		200 W	115	1	60	1.2
BP-2	ASTRO 210	IN-LINE CIRCULATOR	MECH RM	8-2	20	12		200 W	115	1	60	1.2
P-1		IN-LINE CIRCULATOR	MECH RM		40			1	115	1	60	1.2
P-2		IN-LINE CIRCULATOR	MECH RM		40			1	115	1	60	1.2

ND REGISTER	SCHEDULE		
MODEL,	SIZE	DESCRIPTION	REMARKS
ASCDA	24" × 24"	ALUMINUM SUPPLY DIFFUSER, ROUND NECK, 4 CONE, FULL FACE.	1 THROUGH 7
ASCDA	12" × 12"	ALUMINUM SUPPLY DIFFUSER, ROUND NECK, 4 CONE, FULL FACE, 6" NECK	1 THROUGH 7
630D	24" × 24"	ALUMINUM SINGLE DEFLECTION LOUVERED RETURN WITH 45 DEGREE ANGLE AND 3/4" SPACING	1,2,3,4,6
630D	12" x 12"	ALUMINUM SINGLE DEFLECTION LOUVERED RETURN WITH 45 DEGREE ANGLE AND 3/4" SPACING	1,2,3,4,6
	MODEL ASCDA ASCDA 630D	ASCDA 24" x 24" ASCDA 12" x 12" 630D 24" x 24"	MODEL SIZE DESCRIPTION ASCDA 24" x 24" ALUMINUM SUPPLY DIFFUSER, ROUND NECK, 4 CONE, FULL FACE. ASCDA 12" x 12" ALUMINUM SUPPLY DIFFUSER, ROUND NECK, 4 CONE, FULL FACE, 6" NECK 630D 24" x 24" ALUMINUM SINGLE DEFLECTION LOUVERED RETURN WITH 45 DEGREE AND 3/4" SPACING

1. SELECTIONS ARE BASED ON PRICE INDUSTRIES. 2. FLEXIBLE DUCTS CONNECTING THE DIFFUSERS SHALL BE FULL SIZE OF NECK DIAMETER OR EQUIVALENT.

MAXIMUM NOISE CRITERION RATING < 25 DBA.

4. BAKED ENAMEL WHITE FINISH

DIFFUSERS SHALL BE 4-WAY BLOW UNLESS OTHERWISE INDICATED ON PLANS.
 MOUNTING FRAME TYPE SHALL BE COORDINATED WITH CEILING/WALL CONSTRUCTION TYPE.

7. NECK SIZE TO BE PER TABLE.

NECK SIZE TABLE

UP TO 275 CFM - 8" DIAMETER 276 TO 380 CFM - 10" DIAMETER 381 TO 500 CFM - 12" DIAMETER

501 TO 700 CFM - 14" DIAMETER 701 TO 901 CFM - 15" DIAMETER

ADDRESS:

24GA28124300 Paul Ripish, P.E. Professional Engineer State of New Jersey DATE KSI PROJECT # 2082M_67 NEW JERSEY PROFESSIONAL ENGINE LICENSE NUMBER 4515800

© COPYRIGHT 2022 CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC. UNAUTHORIZED REPRODUCTION OF THESE DRAWINGS IS PROBBITED WITHOUT WRITTEN

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY P.O. BOX 628 FARMINGDALE, NJ 07727
PHONE: 732.938.2666 732,938,2666
FAX:
732,938,2521
CERTIFICATE OF AUTHORIZATION NO.

M3.1

CONNOLLY & HICKEY

P.O. Box 1726 Cranford, N.1. 07016 973 746-4911

THOMAS B. CONNOLLY, AIA NJ 21AI01699200 PA RA403776

MARGARET M. HICKEY, AIA NJ 21AI018244500 PROJECT No.: 2016C DATE: 08 AUGUST 2022 REVISIONS:

DRAWN BY: MIMIT, CB, PK

- 1. DO NOT SCALE FROM THESE DRAWINGS DO NOT MAKE ANY CHANGES OR SUBSTITUTIONS WITHOUT SPECIFIC WRITTEN APPROVAL FROM THE ARCHITECT OR ENGINEER.
- 3. ALL INDICATED WORK SHALL BE PERFORMED BY THE PLUMBING CONTRACTOR UNLESS OTHERWISE NOTED.
- 4. PROVIDE C.O.'S AT THE BASE OF ALL SANITARY AND STORM STACKS.
- 5. IT IS THE RESPONSIBILITY OF THE PLUMBING CONTRACTOR TO REVIEW THESE PLANS AND SPECIFICATIONS, AS WELL AS THE RELATED HVAC, FIRE PROTECTION, ELECTRICAL, STRUCTURAL, ARCHITECTURAL, INTERIOR DECOR AND SITE ENGINEERING DRAWING TO BECOME FAMILIAR WITH THE FULL PROJECT SCOPE. IN ADDITION, THIS SITE ENGINEERING DRAWING TO BECOME FAMILIAR WITH THE FULL PROJECT SCOPE. IN ADDITION, THIS SCHICKLING WITH AD WOMEN REPRESENTATIVE TO FULLY UNDERSTAND ALL REQUIREMENTS WHICH MAY NOT BE SPECIFIED HEREIN AND WHICH THE OWNER MAY CONSIDER PART OF THIS CONTRACT, DURING THE COURSE OF CONSTRUCTION, OTOORDINATION INSTRUCTION, IT IS THE RESPONSITIVETY OF THE PLUMBING CONTRACTOR TO WORK CLOSELY WITH ALL ACCOMPANYING CONTRACTORS AND TRADESMEN IN ORDER TO FINISHER A SURGITH BIUNING AND CARFULLY COORDINATED INSTALLATION. TO ENSURE A SMOOTH RUNNING AND CAREFULLY COORDINATED INSTALLATION
- ANY DISCREPANCIES OR INADEQUACIES WITHIN THESE BID DOCUMENTS OR BETWEEN THESE BID DOCUMENTS AND THE RELATED HYAC, FIRE PROTECTION, ELECTRICAL, STRUCTURAL, ARCHITECTURAL, INTERIOR DECOR AND SITE ENGINEERING DRAWINGS, OR BETWEEN THESE BID DOCUMENTS AND FIELD CONDITIONS MUST BE BROUGHT TO THE ATTENTION OF THE OWNER, ARCHITECT AND ENGINEER PRIOR TO BID SUBMISSION.
- ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS INCLUDING BUT NOT LIMITED TO NATIONAL CITY, STATE, LOCAL CODES AND ORDINANCES WHICH MAY BE IN EFFECT. ALL PLUMBING MATERIALS, INSTALLATION PROCEDURES AND SYSTEM LAVOURS SHALL BE APPROVED BY ALL APPLICABLE CODE ENFORCEMENT AUTHORITIES HAVING JURISDICTION, AND IT SHALL BE THE PLUMBING CONTRACTOR'S RESPONSIBILITY TO OBTAIN AND PAY FOR ALL NECESSARY PERMITS AND APPROVALS FOR THIS INSTALLATION.
- THE PLUMBING CONTRACTOR MUST VISIT THE SITE AND NOTE ALL EXISTING CONDITIONS AS WELL AS ALL CONDITIONS TO BE MET, PRIOR TO BID SUBMISSION. LACK OF A THOROUGH UNDERSTANDING OF THE PROJECT SCOPE AND CONDITIONS SHALL NOT CONSTITUTE AN EXCUSE FOR ERRORS OR OMISSIONS, NOR FOR A REQUEST FOR EXTRA COMPENSATION.
- IT IS CRITICAL THAT THE PLUMBING CONTRACTOR FIELD VERIFIES ALL EXISTING INVERTS PRIOR TO BID SUBMISSION. IF ANY CONFLICTS EXIST BETWEEN THE NEW PLUMBING SYSTEMS AND THE EXISTING SITE LEVEL SYSTEMS, THEY SHOULD BE BROUGHT TO THE ATTENTION OF AN OWNER'S REPRESENTATIVE AND THE ENGINEER PRIOR TO BID SUBMISSION. EXTRA COMPENSATION WILL NOT BE ALLOWED FOR ANY EXTRA WORK WHICH RESULTS FROM AN INABILITY TO MEET THE INVERTS OF THE EXISTING SITE LEVEL PIPING SYSTEMS.
- 10. THE PLUMBING CONTRACTOR SHALL PROVIDE A COMPLETE SET OF RECORD "AS-BUILT" DRAWINGS INDICATING THE PRECISE LOCATION OF ALL SYSTEMS, EQUIPMENT CONCEALED OR EMBEDDED PIPING, PIPING CONNECTIONS AND ACCESS DOORS. THESE DRAWINGS SHALL ALSO INCLUDE ALL CHANGES AND DEVAIDINGS FROM DOCUMENTS.
- RUN ALL DOMESTIC, WASTE & VENT PIPING AS HIGH AS POSSIBLE THROUGHOUT ENTIRE BUILDING, INSTALL LONG RUNS OF PIPING WITHIN STEEL (JOIST) SPACE AND OTHER PIPING TIGHT TO BOTTOM OF STEEL COORDINATE AND VERIFY WITH OTHER CONTRACTORS AS NOT TO INTERFERE WITH DUCTWORK, FIRE PROTECTION PIPING, LIGHTING SYSTEMS, ETC.
- 12 ALL EXPOSED HORIZONTAL AND VERTICAL PIPING SHALL BE INSTALLED IN A NEAT ARRANGEMENT IN LOCATIONS WHICH ARE THE MOST INCONSPICUOUS. VERTICAL DROPS SHALL BE KEPT TO AN ABSOLUTE MINIMUM AND THEIR FINAL LOCATIONS SHALL BE CORDINATED AND RUN WITHIN CHASES, WALLS, SOFFIS WITH OTHER MECHANICAL/ELECTRICAL FEEDS. ALL SUCH LOCATIONS ARE TO BE REVIEWED WITH A OWNER REPRESENTATIVE AND ARCHITECT PRIOR TO INSTALLATION.
- ALL PLUMBING FIXTURES/APPLIANCES SHALL HAVE THEIR OWN INDEPENDENT SHUT-OFF VALVES, INSTALLED IN AN EASILY ACCESSIBLE AND CONVENIENT LOCATION.
- 14. ALL DOMESTIC WATER BRANCH LINES SHALL HAVE THEIR OWN RESPECTIVE SHUT-OFF VALVES
- 15. DOMESTIC HOT WATER HEATER TEMPERATURE/PRESSURE RELIEF VALVES SHALL BE PIPED FULL SIZE TO THE NEAREST APPROVED STANDPIPE OR FLOOR DRAIN. THIS REQUIREMENT SHALL BE APPLICABLE TO ALL DOMESTIC WATER HEATERS EXCEPT INSTANTANEOUS WATER HEATERS.
- 16. ALL PLUMBING VENT LINES NOTED AS "V. UP" OR "VENT UP" SHALL BE CONNECTED TO THE NEAREST APPROVED "V.T.R." OR "VENT THRU ROOF."
- 17. PRIOR TO INSTALLING SYSTEMS, THE PLUMBING CONTRACTOR SHALL MEET WITH THE ARCHITECTS REPRESENTATIVE TO FIELD VERIFY THE EXACT LOCATION OF ALL PROPOSED EQUIPMENT WHICH MAY NOT BE CLEARLY INDICATED ON THE DRAWINGS.
- 18. SANITARY SEWER PIPING SHOWN IS BASED ON .25" PER FOOT FALL FOR ALL PIPING SMALLER THAN 4", AND .125" PER FOOT FALL FOR ALL PIPING 4" AND LARGER.

DEMOLITION NOTES

- ALL PIPING AND EQUIPMENT TO BE REMOVED SHALL BE REMOVED BACK TO NEAREST STACK, RISER, OR MAIN IN ACCORDANCE WITH ALL STATE AND LOCAL REGULATIONS/STANDARDS, CODES AND AUTHORITY HAVING JURISDICTION.
- REMOVE ANY ABANDONED AND/OR UNUSED PIPING DISCOVERED DURING DEMOLITION. THERE SHALL BE NO DEAD—ENDS GREATER THAN 24 INCHES IN ANY PLUMBING PIPING SYSTEMS.
- DURING DEMOLITION ANY DAMAGES DISCOVERED IN EXISTING PIPING TO REMAIN SHOULD BE BROUGHT TO THE ATTENTION OF THE ENGINEER.
- ALL EXISTING PIPING AND APPURTENANCES TO REMAIN SHALL BE PROTECTED FROM DAMAGE DURING DEMOLITION. ANY DAMAGES INCURRED SHALL BE REPAIRED OR REPLACED AT NO COST BY THIS CONTRACTOR.
- THE CONTRACTOR SHALL COORDINATE, NOTIFY, AND SCHEDULE ALL REMOVALS WITH THE CONSTRUCTION MANAGER PRIOR TO PROCEEDING WITH THE WORK.
- 6. THIS CONTRACTOR SHALL INCLUDE ALL COSTS FOR REMOVAL AND RELOCATIONS IN THE CONTRACT.
- THE CONTRACTOR PRIOR TO BID SHALL VISIT THE SITE, EXAMINE THE EXISTING CONDITIONS, DRAWINGS AND COORDINATE THE EXACT SCOPE OF WORK WITH THE ARCHITECT AND CONSTRUCTION MANAGER.
- THE CONTRACTOR SHALL COORDINATE ALL SHUTDOWNS AND IDENTIFY ANY WORK WHICH MAY BE REQUIRED TO BE PERFORMED ON OVERTIME IN ORDER NOT TO DISTURB OCCUPIED SPACES WHICH ARE NOT WITHIN THE SCOPE OF THIS CONTRACT. OBTAIN WRITTEN APPROVAL OF THE CONSTRUCTION MANAGER PRIOR TO PERFORMING ANY SHUTDOWNS OR PERFORMING WORK ON ON OVERTIME.
- 9. REFER TO ARCHITECTURAL DRAWINGS FOR ADDITIONAL DEMOLITION INFORMATION AND PHASING SEQUENCE.

				VENT TERMINATION KIT.
s	SANITARY WASTE	A.F.W.H.	ANTI-FREEZE WALL HYDRANT	
	VENT LINE	A.D.	ACCESS DOOR	NOTE: DOMESTIC WATER HEATER
	VENT LINE	A.F.F.	ABOVE FINISHED FLOOR	INSTALLATION SHALL COMPLY ROOF
G	PROPANE GAS	B.F.P.	BACK FLOW PREVENTOR	WITH ASHRAE 90.1. TO FIXTURES —
		CA	COMPRESSED AIR	
	COLD WATER	CO.	CLEAN OUT	INTAKE / EXHAUST P.V.C., (BY THIS CONTRACTOR)
	HOT WATER	C.O.D.P.	CLEAN OUT DECK PLATE	(BY THIS CONTRACTOR) 3" PIPE NOT TO EXCEED 120'-0"
		D.I.	DRAINAGE INLET	WITH 1 ELBOW. REDUCE 5' FROM
	HOT WATER RETURN	EXIST.	EXISTING	VENTING DISTANCE FOR EACH ADDITIONAL ELBOW.
		E.W.C.	ELECTRIC WATER COOLER	INSTALL AS PER MANUFACTURER'S
H	BALL VALVE	F.A.I.	FRESH AIR INLET	RECOMMENDATION. PROVIDE CONDENSATE
	CHECK VALVE	FD.	FLOOOR DRAIN	NEUTRALIZATION KIT.
N	CHECK VALVE	G.E.	GRADE ELEVATION	
· ·	BALANCING VALVE	H.B.	HOSE BIBB	THERMOSTAT (TYP.)
		I.E.	INVERT ELEVATION	
a	GAS PRESSURE REGULATOR	LAV.	LAVATORY	PROVIDE WITH
0	CLEAN OUT DECK PLATE	LDR.	LEADER	A.S.M.E. PROVIDE WITH TIME CLOCK.
ä	HORIZONTAL CLEANOUT	N.C.	NORMALLY CLOSED	RELIEF VALVE
**	HORIZONIAL CLEANOUT	N.I.C.	NOT IN CONTRACT	
→	GAS COCK	0.F.	OVERFLOW LEADER	(FULL SIZE)
а	FLOOR DRAIN	O.R.D.	OVER-FLOW ROOF DRAIN	
-		O.W.	OIL WASTE	
ს ⊱ 40	P TRAP	R.D.	ROOF DRAIN	GAS FIRED
~	TRAP	S.	SANITARY	WATER HTR. CP "RECIRC PUMP"
→	PIPE DOWN, DROP & RISE	SK.	SINK	DRAIN VALVE AQUASTAT
	PIPE DOWN, DRUP & RISE	S.S.	SERVICE SINK	EXPANSION TANK AMTROL: ST-12
⊸	PIPE UP	ST	STORM DRAINAGE	UNION (TYPICAL)
	775 71411 117	T.E.	TOP ELEVATION	SPILL ABOVE ORT LEG
	TEE PLAN UP	UR.	URINAL	FLOOR ORALN
	TEE PLAN DOWN	VAC	VACUUM	
		V.B.	VACUUM BREAKER	
1	KEY NOTE	V.T.R	VENT THRU ROOF	4° CONCRETE DIO
		W.	WASTE	4" CONCRETE PAD
		W.C.	WATER CLOSET	WATER HEATER INSTALLATION
		W.C.O.	WALL CLEAN OUT	
				P0.1 N.T.S.

PLUMBING ABBREVIATIONS


NO.	FIXTURE	MFG.	TYPE AND	TRIM NO.	SUPPLY	TRAP NO.	SUPPORT		P	PE SIZE	S		REMARKS
			MODEL NO.		PIPE NO.		NO.	TRAP	WASTE	VENT	CW	HW	
P-1	WATER CLOSET	AMERICAN STANDARD	MADERA 3451001.020	SLOAN ROYAL 111-1,28	-	-	-	-	4"	2"	1"	-	ELONGATED OPEN FRONT SEAT. 1.28 G.P.F. SENSOR OPERATED FLUSH VALVE.
P-1A	WATER CLOSET (ADA)	AMERICAN STANDARD	MADERA 3461001,020	SLOAN ROYAL 111-1.28	-	-	=	-	4"	2"	1"	-	ELONGATED OPEN FRONT SEAT. 1.28 G.P.F. SENSOR OPERATED FLUSH VALVE.
P-2	URINAL	AMERICAN STANDARD	WASHBROOK 6590.001	SLOAN ROYAL 186-0.125	-	-	MIFAB	2"	2"	1-1/2"	1"		0.125 G.P.F.
P-3	LAVATORY 2 STATION	BRADLEY	LD-3010-2-SL-T01-SW BS-BSS-FA-TMA-PT-LDTRAP	IR-DCD	McGUIRE 158-LK	LD-TRAP P-TRAP-C	-	1-1/4x 1-1/2"	1-1/2"	1-1/2"	1/2"		DUAL STATION LAVATORY W/WASTE RECEPTACLE, SOAP DISPENSER, THERMOSTATIC MIXING VALVE, SENSOR FAUCET, PLUG IN TRANSFORMER
P-4	MOP RECEPTOR	FIAT	MSB2424	830-AA 1453-BB	-	-	-	3"	3"	2"	3/4"	3/4"	WITH WALL GUARD, 889-CC MOP BRACKET, 832-AA HOSE & BRACKET,
P-5	ELECTRIC WATER COOLER	ELKAY	LZSTL8WSLK	_	McGUIRE 158	-	-	1-1/4x 1-1/2"	1-1/2"	1-1/2"	1/2"		8.0 GPH, 6 AMPS, 370 WATTS, 115 V.
FD	FLOOR DRAIN	MIFAB	FD230	_	-	P-TRAP	-				-	-	PROVIDE WITH STAINLESS STEEL STRAINER.
F.S.	FLOOR SINK	MIFAB	FS1720-150	-	-	P-TRAP	-				_	-	WITH 1/2 GRATE AND DOME STRAINER.
A.F.W.H.	ANTI FREEZE WALL HYDRANT	MIFAB	MYH-20	1=1	-	-	-				-	-	PROVIDE WITH VACUUM BREAKER AND OPERATION KEY.
T.P.	TRAP PRIMER	PPP, INC.	-	-	1 171 1	-	-			-	-	_	PROVIDE TRAP PRIMER TO ALL FLOOR DRAINS.


PROVIDE TRAP PRIMERS ON ALL TOILET ROOM FLOOR DRAINS.


PLUMBING SYMBOLS


- PROVIDE McGUIRE PRO-WRAP INSULATING KIT ON TRAPS AND HOT AND COLD WATER SUPPLIES TO ALL HANDICAPPED LAVATORIES. SEE ARCHITECTURAL DRAWINGS FOR LOCATIONS OF HANDICAPPED FIXTURES.
- PRIOR TO SUBMITTING SHOP DRAWINGS, THE CONTRACTOR SHALL COORDINATE FIXTURE TYPES AND COLORS WITH THE ARCHITECT.
- REFER TO THE ARCHITECTS DRAWINGS FOR LOCATION AND QUANTITIES OF HANDICAPPED FIXTURES. ALL HANDICAPPED FIXTURES SHALL BE INSTALLED AS PER ICC/ANSI A117.1-2009 REQUIREMENTS.

PLUMBIN	G EQUIPMENT S	CHEDULE										
GENERAL				DESIGN DATA		ELECTRICAL					REMARKS	
ITEM	SERVICE	MFR.	NO.	LOCATION	CAPACITY	PUMP HEAD	H.P./K.W.	R.P.M.	VOLTS	PHASE	HZ.	
WH-1	WATER HEATER	BRADFORD WHITE	EF-60T-125E-3N	SEE DWG'S	60 GAL	160 GAL @ 90 DEG, RISE			115	1	60	
G.I.	GREASE INTERCEPTOR	SCHIER	GB-2	SEE DWG'S	35 CPW/130 LBS GREASE CAPACITY					_		PROVIDE EXTENSION RISER. INSTALL FLUSH WITH FINISHED FLOOR
CP-1	CIRC. PUMP	BELL&GOSSETT	NBF-85/LW	SEE DWG'S	1 G.P.M.	1 G.P.M. @ 7 T.D.H.	39 WATTS	2800	120	1		PROVIDE WITH TIME CLOCK TC-1









- VENT TERMINATION KIT



ADDRESS: O. BOX 628 FARMINGDALE, NJ 0772 PHONE: 732.938.2666 FAX: 732 938 2521 CERTIFICATE OF AUTHORIZATION NO. 24GA28124300 OF COMPANY ASSETS BOTH OF WHICH SHALL BE PROSECUTED TO THE FULLEST EXTENT OF CURRENT STATUTES Paul Ripish, P.E. Professional Engineer State of New Jersey MEP PROGRESS SE 08/08/2022

ATION

RESTORATIC WILLIAM BURLINGTON, I

CONNOLLY & HICKEY

ARCHITECTS, LLC

Cranford, N.J. 07016

THOMAS B. CONNOLLY, A NI 21AI01699200 PA RA403776

MARGARET M. HICKEY, AL NJ 21AI018244500

PROJECT No.: 2016C DATE: 08 AUGUST 2022

DRAWN BY : MSAM CB, PK

JER

N AND REHABILITATION


ALLEN SCHOOL


URLINGTON COUNTY, NEW JEI

REVISIONS:


973 746-4911









DOT SHE PROBLEM OF THE ARCHITECT SHEAL OF THE







KEY NOTES


- AIR ADMITTANCE VALVE.
- 2" V. RISE & AIR ADMITTANCE VALVE.
- 3. H.&C.W. UP THRU FL.
- 4. CONNECT TO COFFEE MAKER.
- 5. CONNECT TO ICE AND COFFEE MAKER, PROVIDE SHUT-OFF VALVE AND BFP.
- 6. C.W. UP THRU FL.

GENERAL NOTES

1. PROVIDE TRAP SEALS FOR ALL FLOOR DRAINS.

2. PROVIDE SHOCK ARRESTERS ON WATER SUPPLY TO WATER CLOSET.

PROVIDE THERMOSTATIC MIXING VALVE AT LAVATORIES. TEMPERATURE AT LAVATORY SHALL



CONNOLLY & HICKEY

HISTORICAL ARCHITECTS, LLC

P.O. Box 1726 Cranford, N.J. 07016

973 746-4911



THOMAS B. CONNOLLY, AIA NJ 21AI01699200 PA RA403776

MARGARET M. HICKEY, AIA NJ 21AI018244500

PROJECT No.: 2016C DATE: 08 AUGUST 2022

REVISIONS:

DRAWN BY: MAHI, CB, PK

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY


P1.1A


732.938.2521

CERTIFICATE OF AUTHORIZATION NO.
24GA28124300

Paul Ripish, P.E. Professional Engineer State of New Jersey

P.O. BOX 628 FARMINGDALE, NJ 07727
PHONE:
732.938.2666 FAX





RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY P.O. BOX 628 FARMINGDALE, NJ 07727 PHONE: 732.938.2666 FAX: 732 938 2521

CERTIFICATE OF AUTHORIZATION NO. 24GA 28124300

CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC

P.O. Box 1726

973 746-4911

Cranford, N.J. 07016


THOMAS B. CONNOLLY, AIA NJ 21AI01699200 PA RA403776 MARGARET M. HICKEY, AIA NJ 21AI018244500 PROJECT No. : 2016C DATE: 08 AUGUST 2022 REVISIONS:

DRAWN BY: MANI, CB, PK

P2.1 MEP PROGRESS SET 08/08/2022 DATE
KSI PROJECT * 2082M_07
NEW JERSEY PROFESSIO
LICENSE NUMBER

FLOOR M.R. FLOOR 3"(3 D.F.U.) BASEMENT O3 SANITARY RISER DIAGRAM
P2.1 N.T.S.

O2 GAS RISER DIAGRAM
N.T.S.



KEY NOTES (1), 2, ETC.)

GENERAL NOTES

FIRE PROTECTION DESIGN CRITERIA

WET TYPE SPRINKLER SYSTEM SYSTEM TYPE: OCCUPANCY CLASS: DENSITY:

WET TYPE SPRINKLER SYSTEM SYSTEM TYPE:
OCCUPANCY CLASS:
DENSITY:

AREA OF APPLICATION: MAX. SPRINKLER HEAD COVERAGE

DENSITY:
AREA OF APPLICATION:
MAX. SPRINKLER HEAD COVERAGE

- 6" FIRE PROTECTION WATER SERVICE INSTALL WATER MAIN ACCORDANCE TO N.F.P.A. 24 AND UTILITY COMPANY REQUIREMENTS.
- BACK FLOW PREVENTION DEVICE AND WET TYPE VALVE. PIPE TEST DRAIN LINES TO OUTSIDE OF BUILDING.
- 3. FIRE DEPARTMENT LOCATION. OBTAIN APPROVAL FOR LOCATION AND CONNECTION TYPE FROM LOCAL AUTHORITY HAVING JURISDICTION PRIOR TO INSTALLATION.

INSTALL SPRINKLERS IN COMBUSTIBLE CONCEALED SPACES IN ACCORDANCE WITH N.F.P.A. 13.
 ALL NEW PIPING SHALL BE INSTALLED IN CONCEALED SPACES, COORDINATION OF ALL NEW PIPE ROUTING SHALL BE COORDINATED PRIOR TO INSTALLATION OF PIPING.
 ALL ATTIC SPACES SHALL BE PROTECTED IN ACCORDANCE WITH NFPA 13. REFER TO ARCHITECTURE DRAWNINGS FOR ROOF PLANS AND BUILDING SECTIONS.

WET PIPE SYSTEM ORDINARY HAZARD 0.15 GPM/SO FT 1,500 SO FT 130 SQ FT



CONNOLLY & HICKEY

HISTORICAL ARCHITECTS, LLC

P.O. Box 1726

Cranford, N.J. 07016 973 746-4911

THOMAS B. CONNOLLY, ALA NJ 21AI01699200 PA RA403776

MARGARET M. HICKEY, AIA NJ 21AI018244500

PROJECT No.: 2016C

DATE: 08 AUGUST 2022

REVISIONS:

OR OWNERS ABOUT OR BU

DRAWN BY: MSARJ, CB, PK

ON AND REHABILITATION

R. ALLEN SCHOOL

BURLINGTON COUNTY, NEW JERSEY

KSI CONSULTING ENGINEERS LI

KSI CONSULTING ENGINEERS, LLC
ADDRESS:
P.O. BOX 628 FARMINGDALE, NJ 0772

PHONE: 732.938.2666

FAX: 732,938,2521

CERTIFICATE OF AUTHORIZATION NO. 24GA28124300


ALI DIE VENNOS AND BETTITTS MATERIALS ARTEAS ARTEAS

MEP PROGRESS SET 08:08-2022


FP1.1

RESTORATION A WILLIAM R. A BURLINGTON, BURLINGTON,

D COPYRIGHT 1022 CONNOLLY & NICLEY HISTORICAL ARCHITECTS, LLC. UNAUTHORIZED REPRODUCTION OF THESE DRAWINGS IS PROHIBITED WITHOUT WRITTEN CONSENT OF THE ARCHITECT







EXTERIOR LIGHTING CONTROL DIAGRAM

ADDRESS: P.O. BOX 628 FARMINGDALE, NJ 07727 PHONE: 732.938.2666 CERTIFICATE OF AUTHORIZATION NO. 24GA28124300

OF COMPANY ASSETS BOTH OF WHECH SHALL PROSCUTED TO THE FULLEST EXTENT OF CURRENT STATUSTS. Paul Ripish, P.E. Professional Engineer

E0.1

CONNOLLY & HICKEY

Cranford, N.J. 07016

THOMAS B. CONNOLLY, AL.

MARGARET M. HICKEY, AIA NJ. 21AI018244500

DATE: 08 AUGUST 2022

DRAWN BY: MAKE, CB, PK

JEW JERSEY

ON AND REHABILITATION

R. ALLEN SCHOOL


BURLINGTON COUNTY, NEW JEI

SCHOOI COUNTY, N

WILLIAM BURLINGTON, I

PROJECT No : 20160

973 746-4911



KEY NOTES

- 1. ALL EXISTING ELECTRICAL DEVICES ON THE WALL SHALL BE DEMOLISHED.
- 2. EXISTING ELECTRICAL SERVICE SHALL BE DEMOLISHED,

DEMOLITION GENERAL NOTES

- CONTRACTOR SHALL VISIT THE SITE TO VERIFY EXISTING CONDITIONS PRIOR TO SUBMISSION OF BID. NO ADDITIONAL COMPENSATION SHALL BE CONSIDERED FOR FAILURE TO OBSERVE THIS REQUIREMENT.
- THE CONTRACTOR SHALL DISCONNECT AND REMOVE ALL ELECTRICAL WIRING AND EQUIPMENT AS
 REQUIRED WITHIN ALL AREAS TO BE RENOVATED. THIS SHALL INCLUDE BUT NOT BE LIMITED TO
 FIXTURES, DEVICES, OUTLETS, SWITCHES, RECEPTACLES, STARTERS, DISCONNECTS, PANELS, FEEDERS,
 ETC.
- THE CONTRACTOR SHALL DISCONNECT AND REMOVE ALL EXISTING CIRCUITS TO MECHANICAL EQUIPMENT BEING REMOVED. REFER TO ALL MECHANICAL DEMOLITION DRAWINGS OR NOTES FOR LOCATIONS.
- WHERE ELECTRICAL ITEMS ARE REMOVED, ALL BRANCH DEVICE'S WIRING SHALL BE REMOVED BACK TO PANEL SERVICING THE EQUIPMENT. WHERE CIRCUITS SERVE ADDITIONAL DEVICES OR EQUIPMENT REMAINING, WIRING SHALL BE REMOVED BACK TO THE NEAREST ACTIVE JUNCTION BOX.
- THE CONTRACTOR SHALL MAINTAIN CONTINUITY OF EXISTING CIRCUITS THAT ARE TO REMAIN IN OPERATION AND SCHEDULE FOR RE-FEEDING FROM NEW PANELS. FORWARD FINDINGS TO ENGINEER FOR REVIEW AND COORDINATION.
- ALL UNUSED CIRCUITS REMAINING AFTER REMOVALS SHALL BECOME SPARE IN PANELS AND LABELED AS SPARE.
- THE CONTRACTOR SHALL REFER TO ARCHITECTURAL DEMOLITION DRAWINGS FOR ADDITIONAL INFORMATION AND SCOPE OF DEMOLITION.
- ALL MATERIALS AND EQUIPMENT REMOVALS SHALL BE DISPOSED OF AS DIRECTED BY THE OWNER OR THE ARCHITECT. OWNER HAS RIGHT OF FIRST REFUSAL FOR ALL DEMOLISHED DEVICES.



ADDRESS: P.O. BOX 628 FARMINGDALE, NJ 07727

732.938.2666 FAX:

732.938.2521 CERTIFICATE OF AUTHORIZATION NO. 24GA28124300

BOTH THE PROFESSIONAL CODE OF FIDICS AND A THE OF COMPANY ASSETS BOTH OF WHICH SHALL BE IPOSECUTED TO THE FULLEST EXTENT OF CURRENT STATUTES.


DATE KSI PROJECT # 2082M_67 NEW JERSEY PROFESS

ED1.0

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

HISTORICAL ARCHITECTS, LLC P.O. Box 1726

Cranford, N.J. 07016 973 746-4911



DEMOLITION GENERAL NOTES

- CONTRACTOR SHALL VISIT THE SITE TO VERIFY EXISTING CONDITIONS PRIOR TO SUBMISSION OF BID. NO ADDITIONAL COMPENSATION SHALL BE CONSIDERED FOR FAILURE TO OBSERVE THIS REQUIREMENT
- THE CONTRACTOR SHALL DISCONNECT AND REMOVE ALL ELECTRICAL WIRING AND EQUIPMENT AS
 REQUIRED WITHIN ALL AREAS TO BE RENOVATED. THIS SHALL INCLUDE BUT NOT BE LIMITED TO
 FIXTURES, DEVICES, OUTLETS, SWITCHES, RECEPTACLES, STARTERS, DISCONNECTS, PANELS, FEEDERS,
 ETC.
- 3 THE CONTRACTOR SHALL DISCONNECT AND REMOVE ALL EXISTING CIRCUITS TO MECHANICAL EQUIPMENT BEING REMOVED. REFER TO ALL MECHANICAL DEMOLITION DRAWINGS OR NOTES FOR LOCATIONS.
- WHERE ELECTRICAL ITEMS ARE REMOVED, ALL BRANCH DEVICE'S WIRING SHALL BE REMOVED BACK TO PANEL SERVICIONS THE ECOUPMENT. WHERE CIRCUITS SERVE ADDITIONAL DEVICES OR EQUIPMENT REMAINING, WIRING SHALL BE REMOVED BACK TO THE NEAREST ACTIVE JUNCTION BOX.
- THE CONTRACTOR SHALL MAINTAIN CONTINUITY OF EXISTING CIRCUITS THAT ARE TO REMAIN IN OPERATION AND SCHEDULE FOR RE-FEEDING FROM NEW PANELS. FORWARD FINDINGS TO ENCINEER FOR REVIEW AND COORDINATION.
- ALL UNUSED CIRCUITS REMAINING AFTER REMOVALS SHALL BECOME SPARE IN PANELS AND LABELED AS SPARE.
- THE CONTRACTOR SHALL REFER TO ARCHITECTURAL DEMOLITION DRAWINGS FOR ADDITIONAL INFORMATION AND SCOPE OF DEMOLITION.
- B. ALL MATERIALS AND EQUIPMENT REMOVALS SHALL BE DISPOSED OF AS DIRECTED BY THE OWNER OR THE ARCHITECT. OWNER HAS RIGHT OF FIRST REFUSAL FOR ALL DEMOLISHED DEVICES.



KSI CONSULTING ENGINEERS, LLC
ADDRESS:
P.O. BOX 628 FARMINGDALE, NJ 07727

PHONE: 732.938.2666

732.938.2521
CERTIFICATE OF AUTHORIZATION NO.
24GA28124300

ALL DRAWDIGS AND WRITTEN MATERIALS AFFEARING
REBER CHYCHTHE TO REBINALL VIOLOGYPELLOND WERE
FOR THE PHENORS OF COPPING THE SHOCK OR REPENSING,
SAD DRAWDIGS SHALL BE CONDECTED A TORK ATTOR ATTOR
HOTH THE PHENORS OF COPPING THE SHOCK OR REPENSING.
HOTH THE PHENORS OF COPPING THE SHOCK OR REPENSING
HOTH THE PHENORS OF THE SHOCK OF THE SHORT OF THE SHOT OF THE SHORT OF THE SHORT OF THE SHORT OF THE SHORT OF THE SHOT OF THE SHORT OF THE SHORT OF THE SHORT OF THE SHORT OF THE SHOT OF THE SHORT OF THE SHORT OF THE SHORT OF THE SHORT OF THE SHOT OF THE SHORT OF THE SHOT OF THE SHORT OF THE SHOT OF THE SHOT

Paul Ripish, P.E. Professional Engineer State of New Jersey

1/EP PROGRESS SET 08/08/2022

ATE SI PROJECT # 2082M_07 NEW JERSEY PROFESSIONAL ENGIN ED1.1

CONNOLLY & HICKEY

Cranford, N.J. 07016 973 746-4911


THOMAS B. CONNOLLY, AIA NJ 21AI01699200 PA RA403776 MARGARET M. HICKEY, AIA NJ 21AI018244500


PROJECT No.: 2016C


DATE: 08 AUGUST 2022

DRAWN BY: MNRS, CB, PK

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY







 $\underbrace{ \text{ }_{\text{E1.1A}} \text{ } }_{\text{1/4"=1'-0"}} \text{ } \underbrace{ \text{ELECTRICAL KITCHEN LIGHTING PLAN - ALTERNATE} }_{\text{1}}$

GENERAL NOTES

- 1. ALL FIXTURES SHALL BE CIRCUITED TO PANEL PP-1A UNLESS OTHERWISE NOTED.
- 2. ALL EXIT AND EMERGENCY FIXTURES SHALL BE CIRCUITED TO THE LOCAL LIGHTING CIRCUIT AHEAD OF SWITCHING WITH $(2)\sharp12+(1)12G$ IN 3/4" CONDUIT.
- 3. ALL FIXTURES SHALL BE TYPE A UNLESS OTHERWISE NOTED.
- CONTRACTOR SHALL COORDINATE MOUNTING HEIGHT AND LOCATION OF ALL EXTERIOR LIGHTING FIXTURES WITH OWNER AND ARCHITECT PRIOR TO ROUGH—IN.
- PROVIDE AND INSTALL (4) TYPE 'M' FIXTURES IN ATTIC ABOVE FIRST FLOOR. PROVIDE AND INSTALL
 (1) 120V TOGGLE SWITCH WITH PILOT LIGHT FOR CONTROL NEAR ATTIC HATCH. PROVIDE AND INSTALL
 (1) CONVENIENCE GFCI TYPE RECEPTACLE IN ATTIC.



CONNOLLY & HICKEY

HISTORICAL ARCHITECTS, LLC

P.O. Box 1726 Cranford, N.J. 07016 973 746-4911



THOMAS B. CONNOLLY, AIA NJ 21A101699200 PA RA403776

MARGARET M. HICKEY, AIA NJ 21AI018244500

PROJECT No.: 2016C DATE: 08 AUGUST 2022

REVISIONS:

DRAWN BY: MERE, CB, PK

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY





732.938,2666


FAX: 732.938.2521

CERTIFICATE OF AUTHORIZATION NO. 24GA28124300

E1.1A







ELECTRICAL KITCHEN POWER PLAN - ALTERNATE
1/4"=1"-0" 01 E2.1A

KEY NOTES

GENERAL NOTES

1. JUNCTION BOX PROVIDED FOR KITCHEN RANGE HOOD.

ALL NEW ELECTRICAL DEVICES AND SHALL BE CIRCUITED TO PANEL PP-1A UNLESS OTHERWISE NOTED.

CONTRACTOR SHALL COORDINATE THE LOCATION OF ALL DEVICES WITH THE ARCHITECT PRIOR TO ROUGH-IN.



CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC

P.O. Box 1726

Cranford, N.J. 07016 973 746-4911



THOMAS B. CONNOLLY, AIA NJ 21AI01699200 PA RA403776

MARGARET M. HICKEY, AIA NJ 21AI018244500

PROJECT No.: 2016C

DATE: 08 AUGUST 2022

REVISIONS:

DRAWN BY : MERE, CB, PK

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY



732.938.2666

FAX: 732,938,2521

CERTIFICATE OF AUTHORIZATION NO. 24GA 28124300

ALL DRAWNOS AND WITTIN MATERALS APPEARS
HERENCOASTITUTE PROCESS. AND INVESTIGATION OF THE INSENSE
FOR THE REPORTS. THE REPORT ON OF THE INSENSE
FOR THE REPORTS OF COPYING THIS WORK OR REVISION
AND DRAWNOS SHALL BE CONSTITUTED A VOILATION OF
ROTH THE PROFESSIONAL CODE OF THICK SHALL BE
PROJECUTED TO THE PLLEST EXTENT OF
COMPANY ASSETS BOTH OF WHICH SHALL BE
PROJECUTED TO THE PLLEST EXTENT OF
CURRAIN'S TATUTES Paul Ripish, P.E. Professional Engineer State of New Josep

DATE
RSI PROJECT # 2082M_07

NEW JERSEY PROFESSIONAL ENGINE
LICENSE NUMBER 4515800

E2.1A

ANE	L MDF	SCHEDULE	_	COMMENTS:		NEW PA	WEL						400A MAIN CIRCUIT BREAKER									
	L LOCA	TION	BASEMENT														NUMBER O	F POLES:	42	1		
208/120 VOLTS, 3 PHASE, 4 WIRE					150A	BUS :	BUS SIZE									PANEL SHORT CIRCUIT			KAIC			
C.B.	C.B. TRIP	C.B.	LOAD DESCRIPTION	CIR NO		FDR.DA	TA		PHASE A	PHASE B	PHASE C	FDR.DA		DATA		CIR NO	LOAD DESCRIPTION	C.B.	C.B.	C.B.		
NO.	AMPS	V'A		1	No.	WIRE	GND	COND	1			No.	WIRE	GND	COND	1		VA	AMPS	NO.		
3	125	8,606	PANEL PP-18	3	4	1	6	2	22784	18026	_	4	1	6	2	2	PANEL PP-1A	14,178 9,540	125	1		
		8.222		5			1000	- 1			16862	1			`	6	70.00	8,640	123	1		
		3,249		7					5415							8		2,166				
3	45		CU-1	9	3	8	10	1		5415		3	10	10	3/4	10	CU-3	2,166	30	3		
		3,249		11	\Box		_				5415	ட				12		2,166	1			
3	45	3,249		13	0.61		676		5054						100	14		1,805				
3	45	3,249	CU-2	15	3	8	10	1		5054	5054	3	10	10	3/4	16	CU-4	1,805	25	3		
		2,166		19					4332							20		2.166				
3	30		CU-5	21	3	10	10	3/4		4332		3	10	10	3/4	22	CU-6	2,166	30	3		
-	_	2,166		23							4332	Ш				24	200	2,166	7.000	1		
3		1,805		25					1805								SPACE					
٠,١	25	1,805	LU-7	27	3	10	10	3/4	_	1805		-	_	_	_		SPACE					
\neg	-	300			Н	-		_	300		1805		_		_		SPACE					
3	15		EF-3 &EF-4	33	١, ١	12	12	3/4	300	300	-	\vdash	_		-		SPACE	-	_	_		
ř I	,,,	300	L -3 LL -4	35	3	12	12	3/4	-	390	300	-	_	_	-		SPACE SPACE	-	-	-		
\neg	_	400		37	\vdash	_	-	_	400	_	300	-	_	_	-		SPACE	-	⊢	₩		
3	40		PANEL PP-B	39	3	8	10	3	400	400		-	_		_		SPACE	-	-	-		
		800	THROUGH CONTACTOR	41		- 5	4.5			100	800		_	_	_		SPACE	+	-	-		
OUI	NTING:		SURFACE		PH	-LDAI	1	_	40000	35332		V/A				- 14	PANEL TYPE : NEMA 1,	MATLE	_	_		
	FROM:		ELECTRICAL UTILITY		1000		LOAD		10000	110	KVA	1.7	1		AMPS		GROUNDING TERMINAL 10					

ANE	PP-	-1B	SCHEDULE		COM	MENTS:	NEW P	ANEL							125A MAIN CIRCUIT BREAKER								
ANE	L LOCA	TION	CLOSET		1												NUMBER OF	POLES-	42	1			
08	/120	755	VOLTS, 3 PHASE, 4 WIRE			125A	BUS	SIZE									PANEL SHORT CIRCUIT		_	KAIC			
B.	C.B. TRIP	C.B.	LOAD DESCRIPTION	CIR	L	FDR DA	TA		PRASE	PHASE	PHASE C		FDR.DA	TA		CIR	LOAD DESCRIPTION	C.B LOAD	C.B. TRIP	C.B.			
NO.	AMPS	VA			No.	WIRE	GND	COND				No.	WIRE	GND	COND			VA	AMPS	NO.			
1	20	540	COMMUNITY RECS 2	1	2	12	12	3/4	1260			2	12	12	3/4	2	COMMUNITY RECS 2	720	20	1			
1	20	720	MENS OF AND COMM, RECS	3	2	12	12	3/4		1440	A	2	12	12	3/4	4	COMMUNITY RECS 3	720	20	1			
1	20	720	COMMUNITY RECS 4	5	2	12	12	3/4			1440	2	12	12	3/4	6	COMMUNITY RECS 5	720	20	1			
1	20	600	HALL LIGHTS	7	2	12	12	3/4	1200			2	12	12	3/4	8	COMMUNITY LIGHTS	600	20	1			
1	20	600	COMMUNITY LIGHTS 2	9	2	12	12	3/4		1100		2	12	12	3/4	10	STAIR & MEN'S LICHTS	500	20	1			
1	20	336	BASEMENT KITCH LIGHTS	11	2	12	12	3/4			936	2	12	12	3/4	12	WATER COOLER	600	20	1			
1	15	200	UH-1 THROUGH UH-3	13	2	12	12	3/4	400			2	12	12	3/4	14	UH-4 THROUGH 6	200	20	1			
1	20	200	UH-7 THROUGH UH-10	15						892					_	18		692		1			
		1,143		17	1						1835	2	12	12	3/4	20	AHU-5	692	1 15	3			
3	15	1,143	AHU-1	19	2	12	12	3/4	1835			1				22		692	1				
_		1,143		21	L.,				-	1835						24		692		1			
		1,143		23	Г						1835	2	12	12	3/4	26	AHU-6	692	15	3			
3	15		AHU-2	25	2	12	12	3/4	1835			1				28		692	1	1			
_		1.143		27	L					1835						30		692		1			
		692		59							1384	1 2	12	12	3/4	32	AHU-7	692	1.5	3			
3	15	692	AHU-3	31	2	12	12	3/4	1384						2.500	34		692	1	1,000			
_		692		33	L		100			692						34	SPACE	1					
		692		35							692					36	SPACE			1			
3	15	692	AHU-4	37	2	12	12	3/4	692							38	SPACE			1			
		692		39	<u>1</u>			100		692						40	SPACE						
1	15	100	MOTOR OPERATED DAMPER	41	2	12	12	3/4			100					42	SPACE			1			
OUI	VTING:		SURFACE		PH	-LOA			8606	8486	8222	VA					PANEL TYPE : NEMA 1. 1	MTH					
ED	FROM:		PANEL MDP		lon	NECTE	LOAD			25	KVA	_	70 AMPS				GROUNDING TERMINAL 100	W NELT	DAL				

ANE	PP-	14	SCHEDULE		COM	MENTS:	HEW P	MNEL							1	25A	MAIN CIRCUIT BREAKER			_
ANE	LOCA	MOIT	JANITOR				1										NUMBER OF	POLES.	42	1
808	08/120 VOLTS, 3 PHASE, 4 WIRE					125A BUS SIZE PANE										ANEL SHORT CIRCUIT RATING:		KAIS		
C.B.	C.B TRIP	LOAD	LOAD DESCRIPTION	CIR NO		FDR.D.			PHASE A	PHASE B	PHASE C	\vdash	FDR.DA	_	_	CIR NO	LOAD DESCRIPTION	C.B.	C.B. TRIP	C.B
ND.	20	360	WOMENS & HALL RECS	+	No.	WIRE		COND				No.		GND	COND	_		VA	AMPS	NO
1	20	720	COMMUNITY RECS	1	-	12	12	3/4	1260	-	_	2		12	3/4		COMMUNITY RECS	900	20	1
÷	20	720	COMMUNITY RECS 2	3	2	12	12	3/4	_	1440		2		12	3/4		COMMUNITY RECS 2	720	20	
: 	20	540	RECEPT OFFICE RECS	7		12	12	3/4	-		1260	2	12	12	3/4		RECEPT OFFICE & HALL RECS	540	20	
+	70		RECEPT OFFICE RECS 2		2	12	12	3/4	900		_	2		12	3/4		RECEPT OFFICE QUAD	360	20	
÷	20	900	OFFICE & COMMUNITY RECS	9	2	12	12	3/4		1620		2	12	12	3/4		OFFICE RECS	900	20	
! 	20	600		11	2	12	12	3/4			1500	2	12	12	3/4		COMMUNITY LIGHTS 2	600	20	
1	20		COMMUNITY LIGHTS	13	2	12	12	3/4	1200			2	12	12	3/4		KITCHEN LIGHTS	600	20	
1		600	HALL LIGHTS	15	2	12	12	3/4		1200		2	12	12	3/4		KITCHEN LIGHTS 2	600	20	
1	20	600	WIAN'S BATH & KITCH LIGHTS	17	5	12	12	3/4			1000	2	12	12	3/4		OFFICE LIGHTS	400	20	
1	20	200	ENTRY LIGHTS	19	2	12	12	3/4	400			2	12	12	3/4		TIMECLOCK	200	20	
1	20	600	ICE MACHINE	21	5	12	12	3/4		2400		2	12	12	3/4	22	DISHWASHER	1,800	*20	Τ.
•1	*20	400	RANGE	23	2	12	12	3/4			700	2	12	12	3/4		RANGE HOOD	300	•20	1
1	20	1,000	MICROWAVE	25	2	12	12	3/4	6450			2	12	12	3/4	26	KITCHEN COUNTER RECS	5,450	20	\Box
1	20	540	KITCHEN GENERAL RECS	27	2	12	12	3/4	100	1540		2	12	12	3/4	88	WARMING CABINET	1,000	20	
1	20	1,000	WARWING CABINET #Z	29	2	12	12	3/4			2000	2	12	12	3/4	30	WARMING CABINET #3	1,000	20	
1	20	1,320	COFFEE MAKER	31	2	12	12	3/4	2640			2	12	12	3/4	32	COFFEE MAKER	1,320	20	
1	20	400	FACP	33	2	12	12	3/4		940		2	12	12	3/4	34	KITCHEN GENERAL RECS	540	20	
•1	*20	480	WATER FILL STATION	35	2	12	12	3/4			1880	2	12	12	3/4	36	EF-3	1,400	20	
1	20	600	FREEZER	37	2	12	12	3/4	1328			2	12	12	3/4	38	CUH-2	528	15	\top
1	20	400	WATER HEATER WH-1	39	2	12	12	3/4		400						40	SPARE		20	1
1	20	300	EXTERIOR LIGHTS	41	2	12	12	3/4			300					42	SPARE		20	1
OUI	NTING:		SURFACE		PH	-LOA	D		14178	9540	8640	VA			_		PANEL TYPE : NEMA 1.	WITH		-
ED	FROM:		PANEL MDP		100	MICCTO	D LOAD			32	KVA		1	00	AMPS		GROUNDING TERMINAL 100		200	

ELECTRICAL PANEL SCHEDULES

YPE	DESCRIPTION	MANUFACTURER	CATALOG #		_	LAMP	MOUNTING	BALLAST/	CONTROL
				VOLT	#	CATALOG #		DRIVER	44111100
A	PENDANT MOUNTED LIGHTING FIXTURE WITH 16" GLASS SHADE AND LINCANDESCANT EQUIVALENT LED GLASS	REJUVENATION	EASTMORELAND 6" FITTER PENDANT WITH 16" OPAL CLASSIC SCHOOLHOUSE SHADE	120V	-	-	PENDANT	E26 LED 60W EQUIVALENT DIMMABLE 3500K	OCCUPANCY SENSORS
В	PENDANT MOUNTED LIGHITNG FIXTURE WITH 18" GLASS SHADE AND INCANDESCENT EQUIVALENT LED BULB	REJUVENATION	ROSE CITY 6" FITTER CHAIN PENDANT WITH 18" OPAL CLASSIC SCHOOLHOUSE SHADE	120V	-	-	CHAIN PENDANT	DIMMABLE 3500K	OCCUPANCY SENSORS
С	6" RECESSED DOWNLIGHT	LITHONIA	WF6-LED-27K30K35K-90CRI-MW	120V	-	-	RECESSED	ELECTRONIC	LOCAL
D	PENDANT MOUNTED LIGHTING FIXTURE WITH 6" GLASS SHADE	REJUVENATION	EASTMORELAND 2 - 1/4" PENDANT WITH 6" OPAL CLASSIC BELL SHADE		-	-	PENDANT	ELECTRONIC	LOCAL/ OCCUPANCY SENSORS
E	EXISTING LIGHTING FIXTURE TO BE RE-FURBISHED	N/A	N/A	120V		-	PENDANT	ELECTRONIC	LOCAL/ OCCUPANCY SENSORS
F	27" WIDE LED VANITY LIGHT	KICHLER	INDECO 2 LIGHT 27" WIDE INTEGRATED LED BATH BAR	120V	-	-	WALL	ELECTRONIC	LOCAL/ OCCUPANCY SENSORS
G	1'X2' LED GASKETED LIGHTING FIXTURE WITH ACRYLIC LENS	LITHONIA	FEML24-3,000LM-LPAFL-MD-MVOLT-40K-80CRI	120V	-	-	SURFACE	ELECTRONIC	LOCAL
х	LED EXIT LIGHT WITH DUAL EMERGENCY HEADS AND INTEGRAL BATTERY COORDINATE COLOR AND LETTER COLOR WITH ARCHITECT	LITHONIA	LHQM-LED-X-X	120V	-	-	AS SHOWN ON DRAWINGS	-	LOCAL LIGHTING CIRCUIT AHEAD OF SWITCHING
X1	INTERIOR EMERGENCY EGRESS FIXTURE WITH 2 BOARDS AND INTEGRAL BATTERY	LITHONIA	ELM2-LED-X	120V	-	-	WALL	-	LOCAL LIGHTING CIRCUIT AHEAD OF SWITCHING
XS	EXTERIOR EMERGENCY EGRESS FIXTURE WITH 2 BOARDS	LITHONIA	AF0-X	120V	-	-	WALL	-	LOCAL LIGHTING CIRCUIT AHEAD OF SWITCHING

LIGHTING FIXTURE SCHEDULE

1. ALL FLUORESCENT FIXTURES SHALL BE EQUIPPED WITH ENERGY SAVING LAMPS AND ELECTRONIC BALLASTS.

2. ALL LAMPS BASED OIT PHILLIPS CATALOR NUMBERS, WITH OSRAW AND SYLVANIA AS APPROVED EQUALS.

3. ALL NORMAL BALLASTS SHALL BE EITHER MICHAEL OR ADVANCED. U.O.N.

4. ELECTRONIC BALLASTS SHALL BE CHIFTER MICHAEL OR ADVANCED. U.O.N.

5. EMERGENCY FIXTURES SHALL BE CAPABLE OF ILLUMINATION OF 2 LAMPS FOR 90 MINUTES AND SHALL BE WIRED AHEAD OF LOCAL SWITCHING(BODINE BALLASTS WHERE APPLICABLE).

6. PROVIDE ALL NECESSARY MOUNTING HARDWARE.

7. PROVIDE UNIVERSAL MOUNTE CANDRY WITH CELLING MOUNTED EXIT SIGNS.

8. PROVIDE MICHAEL AND MOUNTE CANDRY WITH CELLING MOUNTED EXIT SIGNS.

9. PROVIDE ALLAST OPTION FOR FIXTURES AS INDICATED IN DRAWINGS.

BUILDING WALL -COORDINATE CONNECTION

TO UTILITY TRANSFORMER
WITH JCP&L. ROOF 4)400KCMIL +(1)#4G IN 3-1/2"C NEW PANEL MDP NEW PANEL PP-1A NEW PANEL PP-1B 400A NEMA 3R RATED METER PAN & CT CABINET 208V, 3ø, – 4W PER JCP&L REQUIREMENTS (4)400KCMIL IN 3-1/2"C-JAN. 100A FIRST FLOOR 400A LOCKABLE SERVICE AND NEMA 3R RATED DISCONNECT SWITCH 208V/3ø,4W___ PER JCP&L REQUIREMENTS BASEMENT BUILDING WALL-

ELECTRICAL RISER DIAGRAM

ADDRESS: P.O. BOX 628 FARMINGDALE, NJ 07727 PHONE: 732.938.2666 FAX: 732.938.2521 CERTIFICATE OF AUTHORIZATION NO. 24GA28124300 ALL DRAWNOS AND WEITEN MATERIALS AFFEAD.

BEERIN CONTINUE GRIEFS AL NO INFRIGUENDE WAS
OF THE EXCELSE THE REPRODUCTION OF THE DRAWN
FOR THE PAPPAGE OF CUPTAGE THIS WAS OF EVENING.
AND DRAWNOS BRALL BE CORRESIDED A VIDALIZOR OF
BRITH HIP FREFT-SINDMA CODE OF THICK AND A THEFT
OF COMPANY ASSETS BUTTON OF WEIGHT SHALL BE
PRODUCTED TO THE PRILLEST EXTENT OF
CURRANT STATUTES

Paul Rapish, P.E. Professional Engineer State of New Jersey

E3.1

CONNOLLY & HICKEY

HISTORICAL ARCHITECTS, LLC P.O. Box 1726 Cranford, N.J. 07016 973 746-4911

THOMAS B. CONNOLLY, AIA NJ 21AI01699200 PA RA403776 MARGARET M. HICKEY, AIA NJ. 21Al018244500 PROJECT No. 2016C

DATE: 08 AUGUST 2022 REVISIONS:

DRAWN BY : MERE, CB, PK

RESTORATION AND REHABILITATION WILLIAM R. ALLEN SCHOOL BURLINGTON, BURLINGTON COUNTY, NEW JERSEY

ELECTRICAL LIGHTING FIXTURE SCHEDULE 02 EL E3.1 NTS

© COPYRIGHT 2022 CONNOLLY & HICKEY HISTORICAL ARCHITECTS, LLC. UNAUTHORIZED REPRODUCTION OF THESE DRAWINGS IS PROBBITED WITHOUT WRITTEN CONSENT OF THE ARCHITECT